

Ice Storage Ice Transport | Ice Handling



Follett ice storage, ice transport and ice handling equipment

Complete line of products for all your ice storage, transport and handling needs

- for use with commercial ice machines
- can be configured for most applications

Powerful design features make ice transport easier, guicker, safer

SmartGATE[®] ice shield

- slides up smoothly for controlled access to ice safely controls ice flow for minimal ice spillage
- dislodge minor ice bridges by sliding SmartGATE up and down
- permits bridge breaking through access slots reduces risk of injury when bridge dislodges
- FIFO First ice in; first ice out
 - first ice made is first ice used, delivering fresher, cleaner tasting ice
- FIFO product line: Upright bins, Ice•DevIce[™] chuted bin and cart systems, ice storage and transport systems (ITS) and Ice Pro[™] automatic ice bagging and dispensing bins vs slope front bins which first ice in is last ice out

PowerHinge[™] door hinge

- one hand open and close no awkward catches
- three position lock
- no clumsy latches, no unexpected closures

3-day lead time for shipment from order receipt

Slope front ice storage bins

 ice storage up to standard with state 	1030 lb (467 kg) ainless top, front and si	des	 standard no ice is access 			
Model Number	Max. bin capacity lb (kg)	Width in (cm)	Depth in (cm)	Height in (cm)	Required door access in (cm)	650-44
300-22	300 (136)	22.00 (55.9)	29.50 (74.9)	40.00 (101.6)	23.00 (58.4)	050-44
425-30	430 (195)	30.00 (76.2)	29.50 (74.9)	40.00 (101.6)	31.00 (78.7)	
650-44	660 (299)	44.00 (111.8)	29.50 (74.9)	40.00 (101.6)	32.00 (81.2)	
950-48	950 (431)	48.00 (121.9)	28.25 (71.8)	50.00 (127.0)	32.00 (81.2)	
1025-52	1030 (467)	52.00 (132.1)	28.25 (71.8)	50.00 (127.0)	32.00 (81.2)	

Depth

in (cm)

31.00 (78.7)

31.00 (78.7)

31.00 (78.7)

31.00 (78.7)

31.00 (78.7)

31.00 (78.7)

31.00 (78.7)

31.00 (78.7)

31.00 (78.7)

31.00 (78.7)

31.00 (78.7)

31.00 (78.7)

31.00 (78.7)

31.00 (78.7)

Single door upright ice storage bins with SmartGATE ice shield

Width

in (cm)

30.00 (76.2)

30.00 (76.2)

36.00 (91.4)

48.00 (121.9)

48.00 (121.9)

48.00 (121.9)

48.00 (121.9)

56.00 (142.2)

56.00 (142.2)

60.00 (152.4)

60.00 (152.4)

60.00 (152.4)

60.00 (152.4)

60.00 (152.4)

-	ice storage from 460 to 1660 lb (209 to 753 kg)
-	easy to clean, corrosion-resistant ABS/poly tops

Max. bin capacity

lb (kg)

460 (209)

680 (308)

990 (449)

860 (390)

1000 (454)

1185 (538)

1320 (599)

1170 (531)

1360 (617)

1080 (490)

1325 (601)

1490 (676)

1660 (753)

2000 (908)

No. of

Doors

1

1

1

1

1

complete stainless exterior

Model Number

SG500S-30

SG700S-30

SG1000S-36²

SG1010S-48

SG1175S-48

SG1300S-48

SG1160S-56

SG1350S-56

SG1080S-60

SG1325S-60

SG1475S-60

SG1650S-60

SG2000S-603

SG860S-48

- easy removal of ice with scoop or shovel through access door at the bottom of the bin - first ice made is first ice used

Heiaht

in (cm)

44.50 (113.0)

60.00 (152.4)

69.50 (176.5)

46.50 (118.1)

56.00 (142.4)

62.00 (157.5)

65.00 (165.1)

56.00 (142.2)

62.00 (157.5)

46.50 (118.1)

56.00 (142.2)

62.00 (157.5)

65.00 (165.1)

80.00 (203.2)

Required door access

in (cm)

31.00 (78.7)

31.00 (78.7)

32.00 (81.3)

32.00 (81.3)

32.00 (81.3)

32.00 (81.3)

32.00 (81.3)

32.00 (81.3)

32.00 (81.3)

32.00 (81.3)

32.00 (81.3)

32.00 (81.3)

32.00 (81.3)

32.00 (81.3)

-

SG1010S-48

¹ 10.00" (25.4 cm) flanged legs available which replace base unit, height from floor to bottom of chute equals 15.50" (39.4 cm), overall height reduced by 9.75" (24.8 cm)

Includes one Totes ice carrier instead of cart and uses 4.00" (10.16 cm) chute.

² Bagger kit includes 250 plastic bags of 10 lb (4.5 kg) capacity

³ Add 8" (20.32 cm) to depth for lower door assembly (easily removed for installation access). ⁴ Deduct 14.75" (37.47 cm) for low profile "LP" model configurations.

⁵ DEV500SG-30, DEV860SG-48 and DEV1080SG-60 do not have upper inspection window

Double door upright ice storage bins with SmartGATE ice shield

- ice storage from 1870 to 4640 lb (848 to 2105 kg)
- easy to clean, corrosion-resistant ABS/poly tops
- complete stainless exterior

- first ice made is first ice used

- easy removal of ice with scoop or shovel through access door at the bottom of the bin

Model Number	No. of Doors	Max. bin capacity lb (kg)	Width in (cm)	Depth ¹ in (cm)	Height in (cm)	Required door access in (cm)
SG1850-96	2	1870 (848)	96.00 (243.8)	31.00 (78.7)	51.00 (129.5)	32.00 (81.3)
SG2100-72	2	2110 (957)	72.00 (182.9)	40.00 (101.6)	57.00 (144.8)	41.00 (104.1)
SG2250-72	2	2250 (1021)	72.00 (182.9)	48.00 (121.9)	50.50 (128.3)	49.00 (124.5)
SG2650-72	2	2650 (1202)	72.00 (182.9)	40.00 (101.6)	66.50 (168.9)	41.00 (104.1)
SG3200-72	2	3240 (1470)	72.00 (182.9)	48.00 (121.9)	69.50 (176.5)	35.00 (88.9)
SG3900-72	2	3940 (1787)	72.00 (182.9)	48.00 (121.9)	81.50 (207.0)	44.00 (111.8)
SG4600-72	2	4640 (2105)	72.00 (182.9)	48.00 (121.9)	93.00 (236.2)	47.00 (119.4)

¹ Add 8" (20.32 cm) to depth for lower door assembly (easily removed for installation access).

Single door Ice•DevIce ice storage and dispensing systems

- ice storage from 460 to 1660 lb (209 to 753 kg)

with

SC125

cart

-125

-125

-125

-125

-125

-125

-125

-125

-125

-125

-125

-125

with

Cambro

cart

-ICS125L

- gravity loading of ice through chute into Totes[™] ice carrier when chute door is opened

with

Totes

ice carrier

-LP

with

bagger

kit²

-BG

Max. bin

capacity

lb (kg)

460 (209)

680 (308)

860 (390)

1000 (454)

1185 (538)

1320 (599)

1170 (531)

1360 (617)

1080 (490)

1325 (601)

1490 (676)

Width

in (cm)

30.00 (76.2)

30.00 (76.2)

48.00 (121.9)

Depth³

in (cm)

31.00 (78.7)

31.00 (78.7)

31.00 (78.7)

48.00 (121.9) 31.00 (78.7) 74.50 (189.2)

1660 (753) 60.00 (152.4) 31.00 (78.7) 84.00 (213.4) 32.00 (81.3)

48.00 (121.9) 31.00 (78.7)

48.00 (121.9) 31.00 (78.7)

56.00 (142.2) 31.00 (78.7)

60.00 (152.4) 31.00 (78.7)

60.00 (152.4) 31.00 (78.7)

Height⁴

in (cm)

63.00 (160.0)

78.50 (199.4)

65.50 (166.4)

80.50 (204.5)

84.00 (213.4)

74.50 (189.2)

65.50 (166.4)

74.50 (189.2)

56.00 (142.2) 31.00 (78.7) 80.50 (204.5) 32.00 (81.3)

60.00 (152.4) 31.00 (78.7) 80.50 (204.5) 32.00 (81.3)

- eliminates shoveling and scooping

with

SC75

cart

-75

-75

-75

-75

-75

-75

-75

-75

-75

-75

-75

-75

- 7 times faster than scooping
- first ice made is first ice used

Model Number

DEV500SG-305

DEV700SG-30

DEV860SG-485

DEV1010SG-48

DEV1175SG-48

DEV1300SG-48

DEV1160SG-56

DEV1350SG-56

DEV1080SG-605

DEV1325SG-60

DEV1475SG-60

DEV1650SG-60



DEV1010SG-48-75

Required

door access

in (cm)

32.00 (81.3)

32.00 (81.3)

32.00 (81.3)

32.00 (81.3)

32.00 (81.3)

32.00 (81.3)

32.00 (81.3)

32.00 (81.3)

32.00 (81.3)

Cambro is a registered trademark of Cambro Manufacturing Company in the United States and other countries.
Ice•DevIce, Ice Pro, PowerHinge, SmartCART and Totes are trademarks of Follett LLC.
Follett and SmartGATE are registered trademarks of Follett LLC, registered in the US.

¹ Add 8" (20.32 cm) to depth for lower door assembly (easily removed for installation access). ³ 18.00" (45.7 cm) sleeve with window on 62.00" (157.5 cm) high bin ² Available only with stainless steel top. Correctional package not available.





Double door Ice•DevIce ice storage and dispensing systems

- ice storage from 2110 to 4640 lb (957 to 2105 kg)
- gravity loading of ice through chute into Totes ice carrier when chute door is opened
- eliminates shoveling and scooping
- first ice in is first ice out
- standard with two door assemblies, two chutes and two 75 lb (34 kg) SmartCART ice carts



DEV2250-72-75

Model Number	with SC75 cart	with SC125 cart	with Cambro cart	with bagger kit	Max. bin capacity lb (kg)	Width in (cm)	Depth ¹ in (cm)	Height in (cm)	Required door access in (cm)
DEV2100SG-72	-75	-125	-ICS125L	-BG	2110 (957)	72.00 (182.9)	40.00 (101.6)	75.50 (191.8)	41.00 (104.1)
DEV2250SG-72	-75	-125	-ICS125L	-BG	2250 (1021)	72.00 (182.9)	48.00 (121.9)	69.50 (176.5)	46.00 (116.8)
DEV2650SG-72	-75	-125	-ICS125L	-BG	2650 (1202)	72.00 (182.9)	40.00 (101.6)	85.50 (217.2)	41.00 (104.1)
DEV3200SG-72	-75	-125	-ICS125L	-BG	3240 (1470)	72.00 (182.9)	48.00 (121.9)	88.50 (224.8)	35.00 (88.9)
DEV3900SG-72	-75	-125	-ICS125L	-BG	3940 (1787)	72.00 (182.9)	48.00 (121.9)	100.50 (255.3)	44.00 (111.8)
DEV4600SG-72	-75	-125	-ICS125L	-BG	4640 (2105)	72.00 (182.9)	48.00 (121.9)	112.00 (284.5)	47.00 (119.4)
1	1 4 6 1		11.7.1	1.6	A 10 10 10	`			

¹ Add 8" (20.32 cm) to depth for lower door assembly (easily removed for installation access).

Ice transport systems (ITS)

- ice storage from 382 to 3255 lb (174 to 1477 kg), excluding carts; each cart stores an additional 240 lb (109 kg) of ice
- optional Totes ice carriers for SmartCART 240 ice cart limits lifted load to 25 lb (11 kg) for safe, easy ice distribution in displays, salad bars, ice dispensers
- each bay comes standard with one SmartCART 240 ice cart configurable with 1, 2 or 3 SmartCART ice cart bays
- gravity loading of ice through access door at the bottom of the bin easy ice retrieval
- eliminates shoveling and scooping
- 15 times faster than shoveling

Model Number	No. of Doors	Max. bin capacity lb (kg)	Width in (cm)	Depth ¹ in (cm)	Height in (cm)	Required door access in (cm)
ITS500NS-31 ²	1	382 (174)	31.00 (78.7)	40.00 (101.6)	60.00 (152.4)	32.00 (81.3)
ITS700SG-31	1	652 (296)	31.00 (78.7)	40.00 (101.6)	75.00 (190.5)	32.00 (81.3)
ITS1350SG-60	2	1327 (602)	60.00 (152.4)	40.00 (101.6)	75.00 (190.5)	41.00 (104.1)
ITS2250SG-60	2	2133 (968)	60.00 (152.4)	40.00 (101.6)	97.00 (246.4)	41.00 (104.1)
ITS1700SG-90	3	1716 (779)	228.6 (90.00)	40.00 (101.6)	70.00 (177.8)	41.00 (104.1)
ITS3250SG-90	3	3255 (1477)	228.6 (90.00)	40.00 (101.6)	97.00 (246.4)	41.00 (104.1)

¹ Add 8" (20.32 cm) to depth for lower door assembly (easily removed for installation access). Model ITS500NS-31 not equipped with door. ² ITS500NS-31 has sliding windows only, no SmartGATE ice shield or poly door.

Ice Pro automatic ice bagging and dispensing systems

- ice storage from 650 to 1000 lb (295 to 454 kg)
- 8 lb (3.6 kg) bags of packaged ice can be filled by one person at a rate of 6 to 8 bags per minute
- eliminates the need to shovel or scoop ice from a bin

Model Number	Max. bin capacity lb (kg)	Width in (cm)	Depth in (cm)	Height in (cm)	Required door access in (cm)
DB650SA	650 (295)	33.75 (85.7)	48.25 (122.6)	65.00 (165.1)	34.25 (87.0)
DB1000	1000 (454)	52.00 (132.1)	46.75 (118.7)	71.75 (182.2)	34.25 (87.0)
DB1000SA	1000 (454)	52.00 (132.1)	46.75 (118.7)	71.75 (182.2)	34.25 (87.0)



ITS1350SG-60

DB650SA

Optional ice handling accessories

SmartCART 75 ice cart

Perfect for moving small quantities of ice to manually fill storage receptacles. Transports 75 lb (34 kg) of ice at one time. Includes 3 Totes ice carriers for easy pouring. Stainless cart with easy-clean removable poly liner and fold-back lid.

SmartCART 125 ice cart

Fully insulated poly with flip-up lid makes an excellent working cart for portable bars. Transports 125 lb (57 kg) of ice at one time.

Cambro[®] cart -ICS125

Fully insulated poly and slide back lid is perfect for sliding under bars. Transports 125 lb (57 kg) of ice at one time

SmartCART 240 ice cart

Fully insulated poly with removable lid. Perfect for transporting large quantities of ice. Transports up to 240 lb (109 kg) of ice at one time. Shown with Totes ice carriers accessory (holds 150 lb (68 kg) of ice when Totes ice carriers are used).

Totes ice carrier

Comfortable handle, easy distribution of ice from longer side. Poly construction for strength and durability. Limits lifted load to 25 lb (11 kg).

Bagger kit

Makes manually bagging ice easy. Bagger kit includes bagger assembly, tape dispenser with tape and 250 plastic bags of 10 lb (4.5 kg) capacity.



801 Church Lane Easton, PA 18040 follettice.com

Distributed by:













