



| 2025

effective 07/01/25
revised 10/06/25



- medical-grade refrigerators 
- medical-grade freezers 
- ice and water dispensers 
- ice machines 
- slope front bins 

Contents

TERMS AND POLICIES	5
MEDICAL-GRADE REFRIGERATORS AND FREEZERS	6
Follett authorized installation services	7
COUNTERTOP REFRIGERATORS	8
REF1 and REF2 countertop refrigerators	8
REFVAC2 countertop NSF 456 certified vaccine refrigerators	8
UNDERCOUNTER REFRIGERATORS	9
REF4P and REF5P Performance Plus undercounter refrigerators	9
REF4P and REF5P Performance Plus undercounter refrigerators with Wi-Fi remote monitoring	9
REFOMN4P and REFOMN5P Performance Plus Omnicell FlexLock-ready undercounter refrigerators	10
REFVAC4P and REFVAC5P Performance Plus undercounter NSF 456 certified vaccine refrigerators	10
REF5BBP-T Performance Plus undercounter blood bank refrigerators	10
REFNAT5 Edge Series undercounter refrigerators	11
REFADV5-SD Follett Advantage undercounter refrigerator	11
INFINITY SERIES™ UPRIGHT REFRIGERATORS, VARIABLE SPEED	12
REF12i, REF20i, REF25i single door upright refrigerators	12
REF12i, REF20i and REF25i Omnicell FlexLock-ready single door upright refrigerators	14
REF20i-BB and REF25i-BB blood bank single door upright refrigerators	14
UPRIGHT REFRIGERATORS, FIXED SPEED	15
REF12-LB single door upright refrigerators for laboratory and pharmacy	15
UPRIGHT REFRIGERATORS, FIXED SPEED	16
REF45-LB/PH double door upright refrigerators for laboratory and pharmacy	16
REFVAC45 double door upright NSF 456 certified vaccine refrigerators	17
REF45-BB double door upright refrigerators for blood banks	17
COUNTERTOP FREEZERS	18
FZR1 and FZR2 countertop freezers	18
FZRVAC2 countertop NSF 456 certified vaccine freezers	18
UNDERCOUNTER FREEZERS	19
FZR4P and FZR5P Performance Plus undercounter freezers	19
FZRVAC4P and FZRVAC5P Performance Plus undercounter NSF 456 certified vaccine freezers	20
FZR5PLP-T Performance Plus undercounter plasma freezer	20
UPRIGHT FREEZERS	21
Infinity Series FZR20i and FZR25i single door upright freezers	21
Infinity Series FZR20i and FZR25i with Wi-Fi remote monitoring single door upright freezers	21
Infinity Series FZR20i and FZR25i plasma single door upright freezers	22
FZRMD24 -30 C single door upright freezer for laboratory	22
FZR8-PC plasma chiller	22
FZRDCMD17 dual chamber biomedical ECO upright freezer	22
COMBINATION REFRIGERATOR/FREEZER	23
REFFZR9 pharmaceutical combination refrigerator and freezer	23
REFFZR16 pharmaceutical combination refrigerator and freezer	23
REFFZR21 pharmaceutical combination refrigerator and freezer	23
ULTRA-LOW CHEST FREEZERS	24
FZRC3-80 C ultra-low temperature chest freezer	24
FZRC25-86 C ultra-low temperature chest freezer	24

ULTRA-LOW UPRIGHT FREEZERS	25
FZR19 -86 C ultra-low temperature VIP ECO upright freezer	25
FZR26 -86 C ultra-low temperature VIP ECO upright freezer	25
FZR29 -86 C ultra-low temperature VIP ECO upright freezer	25
FZRDR13 -86 C ultra-low temperature TwinGuard upright freezer	26
FZRDR19 -86 C ultra-low temperature TwinGuard upright freezer	26
FZRDR26 -86 C ultra-low temperature TwinGuard upright freezer	26
CRYOGENIC FREEZERS AND CO2 INCUBATORS	27
FZRC8 -150 C cryogenic chest freezer	27
CO2INC30 Reach-In CO2 incubator	27
REFRIGERATOR AND FREEZER ACCESSORIES	28
Countertop refrigerator and freezer accessories and warranties	28
Undercounter refrigerator and freezer accessories and warranties	28
Upright refrigerator and freezer accessories and warranties	29
ICE AND WATER DISPENSERS	30
Symphony Plus ice and water dispensers – 12 series	31
Symphony Plus ice-only dispensers – 12 series	31
Symphony Plus ice and water dispensers – 25 and 50 series	32
Symphony Plus series ice-only dispensers – 25 and 50 series	33
Symphony Plus ice and water dispensers – 110 series	33
Symphony Plus ice-only dispensers – 110 series	34
Symphony Plus base stand options	34
ICE AND WATER DISPENSER ACCESSORIES	35
Water treatment accessories for Symphony Plus ice and water dispensers	35
Cleaning and sanitizing accessories for Symphony Plus ice and water dispensers	35
Other accessories for Symphony Plus ice and water dispensers	35
Replacement ice machine for use in Symphony Plus 414 model dispensers	36
ICE MACHINES	37
Maestro Plus Chewblet and flake ice machine bins – 400 series	38
Maestro Plus Chewblet and flake ice machines – 400 series	38
Maestro Plus 414 RIDE installation kits (required)	39
Maestro Plus 414AT top kits for top mount applications used with countertop ice and beverage dispensers	39
Maestro Plus 414AS top kits for RIDE applications used with countertop ice and beverage dispensers	40
Horizon Elite Chewblet ice machines – 710 series	41
Horizon Elite installation kits – 710 series (required)	41
Horizon Elite ice transport tube kits for RIDE installations – 710 series (required)	41
Horizon Elite top kits for RIDE applications used with countertop ice and beverage dispensers	42
Top kits for Horizon Elite D710A and E710A ice machines for use with countertop ice and beverage dispensers	43
ICE MACHINE ACCESSORIES	44
Water treatment accessories for ice machines	44
Cleaning and sanitizing accessories for ice machines	44
Other accessories for ice machines	44
ICE STORAGE, ICE TRANSPORT AND ICE HANDLING	45
Slope front bins	46
Replacement stainless steel tops for slope front bins	46

Terms and policies

Terms

- Products for sale meet all regulatory compliances as noted in the appropriate Follett Product Specification Sheet at the time of sale. Customer understands and accepts these products as meeting the designated regulatory compliances.
- Net 30 day terms on approved accounts
- Prices subject to change without notice
- Specifications subject to change without notice
- This price list supersedes all others
- **Pricing is in USD**
- **Products priced with EX Works (EXW) terms**
- **Other shipping terms available upon request**

Return Policy

Non-standard equipment cannot be returned. Orders for non-standard equipment cannot be cancelled.

Follett equipment may be returned for credit under the following conditions:

- The equipment is new and unused
- A return authorization number has been issued by customer service within 45 days after shipment
- Follett receives the equipment at the factory in Easton, PA within 30 days after issuance of the return authorization number
- The equipment must be returned in Follett packaging. If the packaging has been damaged or discarded, Follett will forward new packaging at the customer's expense.

Note: Return freight charges are the responsibility of the customer. If equipment is returned and is damaged because of improper packaging, Follett Products, LLC will not be held responsible.

Credit will be issued when the equipment has been inspected by Follett and deemed suitable to be returned to stock.

Note: A 20% restocking charge will be deducted from the credit. If the cost to return the product to stock exceeds 20%, the actual cost will be deducted.

Medical-grade refrigerators and freezers

Follett medical-grade refrigerators and freezers provide the consistent, stable temperatures and access security required for patient floor, lab and pharmacy applications. Heavy-duty compressors and powerful forced-air cooling provide exceptional temperature consistency, quick temperature pull down and rapid recovery following door openings.

Warranty

PHCbi co-branded models

Please visit <https://www.phchd.com/global/biomedical>.

Follett medical-grade countertop, undercounter (Performance Plus and Edge Series™) and upright refrigerators and freezers (including Infinity Series™)

Follett Products, LLC warrants to the original end user that all parts shall be free from defects in material and workmanship under normal use and service for a period of 2 years from the date of installation. Date of installation shall not exceed 90 days from date of shipment. Parts and labor for repair within this 2 year period are covered under this warranty.

The compressor shall be covered for an additional 3 years (parts only), for a total of 5 years from the date of installation.

Follett Advantage® undercounter refrigerators

Follett Products, LLC warrants to the original end user that all parts shall be free from defects in material and workmanship under normal use and service for a period of 1 year from the date of installation. Date of installation shall not exceed 90 days from date of shipment. Parts and labor for repair within this 1 year period are covered under this warranty.

FOLLETT WARRANTY CONDITIONS

- Warranty labor must be performed by the local Follett authorized service provider
- The equipment has been installed and operated in compliance with instructions provided by Follett
- Malfunctions or damage due to alterations, improper operation, outdoor use, neglect, vandalism, fire, acts of God, or any situation beyond the control of Follett are expressly excluded from this warranty
- Follett reserves the right to require that any parts covered under this warranty be returned to Follett prepaid and verified as defective upon examination
- Any damages resulting from shipment of the unit are expressly excluded. Follett advises customers to carefully examine all shipments prior to acceptance and note all potential damage concerns on the appropriate shipping papers.
- Excess labor charges resulting from security clearance procedures, safety training, travel time greater than one hour or 50 miles (80 km), premium time labor; after hours, weekends, holidays, etc., will not be covered by Follett Products, LLC and are the responsibility of the equipment owner

This warranty is expressly made in lieu of other warranties, expressed or implied, including any implied warranty of merchantability or fitness for a particular purpose except as provided in the warranty with respect to defects in material and workmanship.

Follett Products, LLC will not be liable for any consequential damages, expenses, connecting or disconnecting charges, or any losses or damages resulting from a defect of the machine. Questions concerning this warranty should be directed to Follett Products, LLC, technical service at +1 (877) 612-5086 or +1 (610) 252-7301.

Follett authorized installation services

Authorized installation


Equipment is shipped via Follett logistics partner¹, delivered to customer's facility, and positioned in final customer-designated location by certified technicians. Certified Follett technician will remove and discard all packaging material, install casters, make all electrical connections, and complete set up to ensure the unit is fully operational and ready to be used by customer.

For additional product information and terms and conditions, request form# 8620.


¹ Authorized services available only with Follett contracted logistics provider and does not include dock-to-dock common carrier freight charges.

Countertop and undercounter refrigerators and freezers

Item number	Description	Net price
AS1	Authorized installation, first unit	\$350
	Authorized installation, subsequent units of the same model to the same location	\$175



Countertop



Undercounter

Single door upright refrigerators and freezers


Item number	Description	Net price
AS2	Authorized installation, first unit	\$500
	Authorized installation, subsequent units of the same model to the same location	\$250



Single door upright


Double door upright refrigerators

Item number	Description	Net price
AS3	Authorized installation, first unit	\$800
	Authorized installation, subsequent units of the same model to the same location	\$375




Double door upright

Countertop refrigerators



REF1



REF2/REFVAC2

REF1 and REF2 countertop refrigerators

Medical-grade countertop refrigerators for small storage needs. Forced air, external temperature display in F or C, integral high/low alarming and epoxy-coated shelving. Stainless steel construction on interior/exterior. Right-hinged door only. 115V/60/1 electrical.

For additional product information, request form# 6555 for REF1 or 6560 for REF2.

See page 28 for additional accessory information.

Item number	Cubic capacity cu ft (L)	Hinging	Keypad	Width in (cm)	Depth in (cm)	Height in (cm)	Approx. ship wt lb (kg)	List price
REF1	1.0 (28)	right	no	18.60 (47.2)	24.00 (61.0)	17.93 (45.5)	109 (50)	\$4,705
REF1-KP	1.0 (28)	right	yes	18.60 (47.2)	24.00 (61.0)	17.93 (45.5)	109 (50)	\$5,520
REF2	1.8 (51)	right	no	18.60 (47.2)	24.00 (61.0)	27.93 (70.9)	132 (60)	\$5,010
REF2-KP	1.8 (51)	right	yes	18.60 (47.2)	24.00 (61.0)	27.93 (70.9)	132 (60)	\$5,820

REFVAC2 countertop NSF 456 certified vaccine refrigerators


Medical-grade countertop NSF/ANSI 456 certified vaccine refrigerators for small storage needs. Forced air, external temperature display in F or C, integral high/low alarming and epoxy-coated shelving. Stainless steel construction on interior/exterior. Right-hinged door only. 115V/60/1 electrical.

For additional product information, request form# 9060.


See page 28 for additional accessory information.

Item number	Cubic capacity cu ft (L)	Hinging	Keypad	Width in (cm)	Depth in (cm)	Height in (cm)	Approx. ship wt lb (kg)	List price
REFVAC2	1.8 (51)	right	no	18.60 (47.2)	24.00 (61.0)	27.93 (70.9)	132 (60)	\$5,245


Undercounter refrigerators




Performance Plus
LED display



Performance Plus
7" LCD touchscreen display



Edge Series



Follett Advantage

REF4P and REF5P Performance Plus undercounter refrigerators

Medical-grade undercounter refrigerators, freestanding or stackable, with external temperature display in F or C, integral high/low alarming and 2 epoxy-coated shelves. Stainless steel construction on interior/exterior. Right-hinged or left-hinged door. 115V/60/1 electrical. For undercounter applications: model REF4P fits below 34.00" (86.4 cm) ADA-compatible counter and model REF5P fits below a standard 36.00" (91.4 cm) high counter. Ideal for heavy duty applications.

For additional product information, request form# 6455 for REF4P, 6460 for REF5P, 6505 for REF4P-T, or 6510 for REF5P-T.

See page 28 for additional accessory information.

Item number	Cubic capacity cu ft (L)	Hinging	Keypad	Door style	Width in (cm)	Depth in (cm)	Height in (cm)	Approx. ship wt lb (kg)	List price
LED digital temperature display									
REF4P-OR-00-00	3.9 (110)	right	no	stainless	23.75 (60.3)	27.00 (68.6)	31.38 (79.7)	205 (93)	\$5,880
REF5P-OR-00-00	4.5 (127)	right	no	stainless	23.75 (60.3)	27.00 (68.6)	34.00 (86.4)	205 (93)	\$5,880
REF4P-OR-KP-00	3.9 (110)	right	yes	stainless	23.75 (60.3)	27.00 (68.6)	31.38 (79.7)	205 (93)	\$6,695
REF5P-OR-KP-00	4.5 (127)	right	yes	stainless	23.75 (60.3)	27.00 (68.6)	34.00 (86.4)	205 (93)	\$6,695
REF4P-OL-00-00	3.9 (110)	left	no	stainless	23.75 (60.3)	27.00 (68.6)	31.38 (79.7)	205 (93)	\$5,880
REF5P-OL-00-00	4.5 (127)	left	no	stainless	23.75 (60.3)	27.00 (68.6)	34.00 (86.4)	205 (93)	\$5,880
REF4P-OL-KP-00	3.9 (110)	left	yes	stainless	23.75 (60.3)	27.00 (68.6)	31.38 (79.7)	205 (93)	\$6,695
REF5P-OL-KP-00	4.5 (127)	left	yes	stainless	23.75 (60.3)	27.00 (68.6)	34.00 (86.4)	205 (93)	\$6,695

7" LCD touchscreen digital temperature display									
REF4P-TR-00-00	3.9 (110)	right	no	stainless	23.75 (60.3)	27.00 (68.6)	31.38 (79.7)	205 (93)	\$7,500
REF5P-TR-00-00	4.5 (127)	right	no	stainless	23.75 (60.3)	27.00 (68.6)	34.00 (86.4)	205 (93)	\$7,500
REF4P-TR-KP-00	3.9 (110)	right	yes	stainless	23.75 (60.3)	27.00 (68.6)	31.38 (79.7)	205 (93)	\$7,975
REF5P-TR-KP-00	4.5 (127)	right	yes	stainless	23.75 (60.3)	27.00 (68.6)	34.00 (86.4)	205 (93)	\$7,975
REF4P-TL-00-00	3.9 (110)	left	no	stainless	23.75 (60.3)	27.00 (68.6)	31.38 (79.7)	205 (93)	\$7,500
REF5P-TL-00-00	4.5 (127)	left	no	stainless	23.75 (60.3)	27.00 (68.6)	34.00 (86.4)	205 (93)	\$7,500
REF4P-TL-KP-00	3.9 (110)	left	yes	stainless	23.75 (60.3)	27.00 (68.6)	31.38 (79.7)	205 (93)	\$7,975
REF5P-TL-KP-00	4.5 (127)	left	yes	stainless	23.75 (60.3)	27.00 (68.6)	34.00 (86.4)	205 (93)	\$7,975

REF4P and REF5P Performance Plus undercounter refrigerators with Wi-Fi remote monitoring

Medical-grade, undercounter refrigerators with Wi-Fi based cloud communication functionality for continuous temperature monitoring and remote alarming. Freestanding or stackable with LED control, integral high/low alarming and 2 epoxy-coated shelves. Stainless steel construction on interior/exterior. Right-hinged or left-hinged door. 115V/60/1 electrical. For undercounter applications: model REF4P fits below 34.00" (86.4 cm) ADA-compatible counter and model REF5P fits below a standard 36.00" (91.4 cm) high counter. Ideal for heavy duty applications.

For additional product information, request form# 9020.

See page 28 for additional accessory information.

Item number	Cubic capacity cu ft (L)	Hinging	Keypad	Door style	Width in (cm)	Depth in (cm)	Height in (cm)	Approx. ship wt lb (kg)	List price
LED digital temperature display									
REF4P-OR-00-00-N	3.9 (110)	right	no	stainless	23.75 (60.3)	27.00 (68.6)	31.38 (79.7)	205 (93)	Contact factory
REF5P-OR-00-00-N	4.5 (127)	right	no	stainless	23.75 (60.3)	27.00 (68.6)	34.00 (86.4)	205 (93)	Contact factory
REF4P-OL-00-00-N	3.9 (110)	left	no	stainless	23.75 (60.3)	27.00 (68.6)	31.38 (79.7)	205 (93)	Contact factory
REF5P-OL-00-00-N	4.5 (127)	left	no	stainless	23.75 (60.3)	27.00 (68.6)	34.00 (86.4)	205 (93)	Contact factory

REFOMN4P and REFOMN5P Performance Plus Omnicell FlexLock-ready undercounter refrigerators

Medical-grade, undercounter refrigerators with pre-drilled holes for installing Omnicell® XT FlexLock Refrigerator Lock and Temperature Monitor (not included). LED control, integral high/low alarming and 2 epoxy-coated shelves. Stainless steel construction on interior/exterior. Right-hinged door. 115V/60/1 electrical. For undercounter applications: model REFOMN4P fits below 34.00" (86.4 cm) ADA-compatible counter and model REFOMN5P fits below a standard 36.00" (91.4 cm) high counter. Ideal for heavy duty applications.

For additional product information, request form# 8970.

See page 28 for additional accessory information.

Item number	Cubic capacity cu ft (L)	Hinging	Keypad	Door style	Width in (cm)	Depth in (cm)	Height in (cm)	Approx. ship wt lb (kg)	List price
LED digital temperature display									
REFOMN4P-OR-00-00	3.9 (110)	right	no	stainless	23.75 (60.3)	27.00 (68.6)	31.38 (79.7)	205 (93)	Contact factory
REFOMN5P-OR-00-00	4.5 (127)	right	no	stainless	23.75 (60.3)	27.00 (68.6)	34.00 (86.4)	205 (93)	Contact factory

REFVAC4P and REFVAC5P Performance Plus undercounter NSF 456 certified vaccine refrigerators

Medical-grade undercounter NSF/ANSI 456 certified vaccine refrigerators. Freestanding or stackable, with external temperature display in F or C, integral high/low alarming and 2 epoxy-coated shelves. Stainless steel construction on interior/exterior. Right-hinged door. 115V/60/1 electrical. For undercounter applications: model REFVAC4P fits below 34.00" (86.4 cm) ADA-compatible counter and model REFVAC5P fits below a standard 36.00" (91.4 cm) high counter. Ideal for heavy duty applications.

For additional product information, request form# 9055.

See page 28 for additional accessory information.

Item number	Cubic capacity cu ft (L)	Hinging	Keypad	Door style	Width in (cm)	Depth in (cm)	Height in (cm)	Approx. ship wt lb (kg)	List price
LED digital temperature display									
REFVAC4P-OR-00-00	3.9 (110)	right	no	stainless	23.75 (60.3)	27.00 (68.6)	31.38 (79.7)	205 (93)	\$6,115
REFVAC5P-OR-00-00	4.5 (127)	right	no	stainless	23.75 (60.3)	27.00 (68.6)	34.00 (86.4)	205 (93)	\$6,115
7" LCD touchscreen digital temperature display									
REFVAC4P-TR-00-00	3.9 (110)	right	no	stainless	23.75 (60.3)	27.00 (68.6)	31.38 (79.7)	205 (93)	\$7,740
REFVAC5P-TR-00-00	4.5 (127)	right	no	stainless	23.75 (60.3)	27.00 (68.6)	34.00 (86.4)	205 (93)	\$7,750

REF5BBP-T Performance Plus undercounter blood bank refrigerators

Medical-grade, undercounter blood bank refrigerators, freestanding or stackable, with 7" LCD touchscreen user interface with integral data and event logging. Stainless steel construction on interior/exterior with internal LED lighting. Right-hinged or left-hinged door. 115V/60/1 electrical. For undercounter applications: fits below a standard 36.00" (91.4 cm) high counter. Two full extension, stainless drawers standard. Includes separate temperature surveillance module with audible/visual alarm, 7-day chart recorder and digital product temperature display. Meets AABB, FDA, ARC requirements for storage of blood products at 4 C. Ideal for heavy duty applications.

For additional product information, request form# 6475.

See page 28 for additional accessory information.

Item number	Cubic capacity cu ft (L)	Bags (450 ml)	Hinging	Keypad	Door style	Width in (cm)	Depth in (cm)	Height in (cm)	Approx. ship wt lb (kg)	List price
REF5BBP-TR-00-00	4.5 (127)	60	right	no	stainless	23.75 (60.3)	27.00 (68.6)	34.00 (86.4)	205 (93)	\$11,280
REF5BBP-TR-KP-00	4.5 (127)	60	right	yes	stainless	23.75 (60.3)	27.00 (68.6)	34.00 (86.4)	205 (93)	\$11,755
REF5BBP-TL-00-00	4.5 (127)	60	left	no	stainless	23.75 (60.3)	27.00 (68.6)	34.00 (86.4)	205 (93)	\$11,280
REF5BBP-TL-KP-00	4.5 (127)	60	left	yes	stainless	23.75 (60.3)	27.00 (68.6)	34.00 (86.4)	205 (93)	\$11,755

REFNAT5 Edge Series undercounter refrigerators

Medical-grade undercounter refrigerators with LED control, right-hinged door available in solid steel, painted steel exterior, preset automatic alarm tracking around set point, 3 coated steel wire shelves, variable speed compressor, R600a natural refrigerant. 115V/60/1 electrical. Fits below standard 36.00" (91.4 cm) counter. Ideal for medium to heavy duty applications.

For additional product information, request form# 9045.

See page 28 for additional accessory information.

Item number	Cubic capacity cu ft (L)	Hinging	Keypad	Door style	Width in (cm)	Depth in (cm)	Height in (cm)	Approx. ship wt lb (kg)	Net price
REFNAT5-SD	5.0 (142 L)	right	no	steel	23.84 (60.6)	24.50" (62.2)	34.10 (86.6)	130 (59)	\$1,930

REFADV5-SD Follett Advantage undercounter refrigerator

Medical-grade undercounter refrigerator with LED control, right-hinged painted steel door, audible and visual high/low temperature alarms, 2 adjustable wire shelves. 115V/60/1 electrical. Fits below 34.00" (86.4 cm) ADA-compatible counter. Ideal for light to medium duty applications.

For additional product information, request form# 8455.

See page 28 for additional accessory information.

Item number	Cubic capacity cu ft (L)	Hinging	Keypad	Door style	Width in (cm)	Depth in (cm)	Height in (cm)	Approx. ship wt lb (kg)	Net price
REFADV5-SD	4.7 (132 L)	right	no	painted steel	23.30 (59.2)	25.40 (64.5)	31.93 (81.1)	120 (54)	\$975

Infinity Series™ upright refrigerators, variable speed



Shelves



Baskets



Drawers



Blood Banks

REF12i, REF20i, REF25i single door upright refrigerators

Infinity Series upright refrigerator with variable capacity compressor, LCD touchscreen user interface, right-hinged or left-hinged door with ADA-compliant full length locking handle, stainless steel interior/exterior, integral data and event logging, user-programmable temperature display and integral alarming functions, quick-connect RTD probe with 1 year certificate of NIST-traceable calibration, heavy-duty dual casters. 115V/60/1 (103-132V) electrical. Interchangeable storage options allow the interior cabinet space to be configured with shelves, baskets or drawers to your exact needs. Certified to meet NSF/ANSI 456 standard for vaccine storage.

For additional product information, request form# 1027.

See page 29 for additional accessory information.

Item number	Cubic capacity cu ft (L)	Vaccine storage capacity cu ft (L)	Storage system	Hinging	Door style	Keypad	Width in (cm)	Depth in (cm)	Height in (cm)	Approx. ship wt lb (kg)	List price
REF12i-4S-R00G	12.0 (340)	7.2 (204)	4 shelves	right	glass	no	23.75 (60.3)	26.60 (67.6)	72.00 (182.9)	420 (191)	Contact factory
REF20i-4S-R0000G	19.7 (558)	12.7 (360)	4 shelves	right	glass	no	29.75 (75.6)	30.50 (77.5)	79.50 (201.9)	431 (196)	Contact factory
REF25i-4S-R0000G	24.6 (697)	16.8 (476)	4 shelves	right	glass	no	29.75 (75.6)	36.50 (92.7)	79.50 (201.9)	477 (217)	Contact factory
REF12i-4S-R00S	12.0 (340)	7.2 (204)	4 shelves	right	stainless	no	23.75 (60.3)	26.60 (67.6)	72.00 (182.9)	420 (191)	Contact factory
REF20i-4S-R0000S	19.7 (558)	12.7 (360)	4 shelves	right	stainless	no	29.75 (75.6)	30.50 (77.5)	79.50 (201.9)	431 (196)	Contact factory
REF25i-4S-R0000S	24.6 (697)	16.8 (476)	4 shelves	right	stainless	no	29.75 (75.6)	36.50 (92.7)	79.50 (201.9)	477 (217)	Contact factory
REF20i-4S-R00KPG	19.7 (558)	12.7 (360)	4 shelves	right	glass	yes	29.75 (75.6)	30.50 (77.5)	79.50 (201.9)	431 (196)	Contact factory
REF25i-4S-R00KPG	24.6 (697)	16.8 (476)	4 shelves	right	glass	yes	29.75 (75.6)	36.50 (92.7)	79.50 (201.9)	477 (217)	Contact factory
REF20i-4S-R00KPS	19.7 (558)	12.7 (360)	4 shelves	right	stainless	yes	29.75 (75.6)	30.50 (77.5)	79.50 (201.9)	431 (196)	Contact factory
REF25i-4S-R00KPS	24.6 (697)	16.8 (476)	4 shelves	right	stainless	yes	29.75 (75.6)	36.50 (92.7)	79.50 (201.9)	477 (217)	Contact factory
REF12i-4S-L00G	12.0 (340)	7.2 (204)	4 shelves	left	glass	no	23.75 (60.3)	26.60 (67.6)	72.00 (182.9)	420 (191)	Contact factory
REF20i-4S-L0000G	19.7 (558)	12.7 (360)	4 shelves	left	glass	no	29.75 (75.6)	30.50 (77.5)	79.50 (201.9)	431 (196)	Contact factory
REF25i-4S-L0000G	24.6 (697)	16.8 (476)	4 shelves	left	glass	no	29.75 (75.6)	36.50 (92.7)	79.50 (201.9)	477 (217)	Contact factory
REF12i-4S-L00S	12.0 (340)	7.2 (204)	4 shelves	left	stainless	no	23.75 (60.3)	26.60 (67.6)	72.00 (182.9)	420 (191)	Contact factory
REF20i-4S-L0000S	19.7 (558)	12.7 (360)	4 shelves	left	stainless	no	29.75 (75.6)	30.50 (77.5)	79.50 (201.9)	431 (196)	Contact factory
REF25i-4S-L0000S	24.6 (697)	16.8 (476)	4 shelves	left	stainless	no	29.75 (75.6)	36.50 (92.7)	79.50 (201.9)	477 (217)	Contact factory
REF20i-4S-L00KPG	19.7 (558)	12.7 (360)	4 shelves	left	glass	yes	29.75 (75.6)	30.50 (77.5)	79.50 (201.9)	431 (196)	Contact factory
REF25i-4S-L00KPG	24.6 (697)	16.8 (476)	4 shelves	left	glass	yes	29.75 (75.6)	36.50 (92.7)	79.50 (201.9)	477 (217)	Contact factory
REF20i-4S-L00KPS	19.7 (558)	12.7 (360)	4 shelves	left	stainless	yes	29.75 (75.6)	30.50 (77.5)	79.50 (201.9)	431 (196)	Contact factory
REF25i-4S-L00KPS	24.6 (697)	16.8 (476)	4 shelves	left	stainless	yes	29.75 (75.6)	36.50 (92.7)	79.50 (201.9)	477 (217)	Contact factory
REF12i-5B-R00G	12.0 (340)	7.6 (215)	5 baskets	right	glass	no	23.75 (60.3)	26.60 (67.6)	72.00 (182.9)	420 (191)	Contact factory
REF20i-6B-R0000G	19.7 (558)	12.8 (362)	6 baskets	right	glass	no	29.75 (75.6)	30.50 (77.5)	79.50 (201.9)	489 (222)	Contact factory
REF25i-6B-R0000G	24.6 (697)	16.4 (464)	6 baskets	right	glass	no	29.75 (75.6)	36.50 (92.7)	79.50 (201.9)	467 (212)	Contact factory
REF12i-5B-R00S	12.0 (340)	7.6 (215)	5 baskets	right	stainless	no	23.75 (60.3)	26.60 (67.6)	72.00 (182.9)	420 (191)	Contact factory
REF20i-6B-R0000S	19.7 (558)	12.8 (362)	6 baskets	right	stainless	no	29.75 (75.6)	30.50 (77.5)	79.50 (201.9)	489 (222)	Contact factory
REF25i-6B-R0000S	24.6 (697)	16.4 (464)	6 baskets	right	stainless	no	29.75 (75.6)	36.50 (92.7)	79.50 (201.9)	467 (212)	Contact factory
REF20i-6B-R00KPG	19.7 (558)	12.8 (362)	6 baskets	right	glass	yes	29.75 (75.6)	30.50 (77.5)	79.50 (201.9)	489 (222)	Contact factory
REF25i-6B-R00KPG	24.6 (697)	16.4 (464)	6 baskets	right	glass	yes	29.75 (75.6)	36.50 (92.7)	79.50 (201.9)	467 (212)	Contact factory

Item number	Cubic capacity cu ft (L)	Vaccine storage capacity cu ft (L)	Storage system	Hinging	Door style	Keypad	Width in (cm)	Depth in (cm)	Height in (cm)	Approx. ship wt lb (kg)	List price
REF20i-6B-R00KPS	19.7 (558)	12.8 (362)	6 baskets	right	stainless	yes	29.75 (75.6)	30.50 (77.5)	79.50 (201.9)	489 (222)	Contact factory
REF25i-6B-R00KPS	24.6 (697)	16.4 (464)	6 baskets	right	stainless	yes	29.75 (75.6)	36.50 (92.7)	79.50 (201.9)	467 (212)	Contact factory
REF12i-5B-L00G	12.0 (340)	7.6 (215)	5 baskets	left	glass	no	23.75 (60.3)	26.60 (67.6)	72.00 (182.9)	420 (191)	Contact factory
REF20i-6B-L0000G	19.7 (558)	12.8 (362)	6 baskets	left	glass	no	29.75 (75.6)	30.50 (77.5)	79.50 (201.9)	489 (222)	Contact factory
REF25i-6B-L0000G	24.6 (697)	16.4 (464)	6 baskets	left	glass	no	29.75 (75.6)	36.50 (92.7)	79.50 (201.9)	467 (212)	Contact factory
REF12i-5B-L00S	12.0 (340)	7.6 (215)	5 baskets	left	stainless	no	23.75 (60.3)	26.60 (67.6)	72.00 (182.9)	420 (191)	Contact factory
REF20i-6B-L0000S	19.7 (558)	12.8 (362)	6 baskets	left	stainless	no	29.75 (75.6)	30.50 (77.5)	79.50 (201.9)	489 (222)	Contact factory
REF25i-6B-L0000S	24.6 (697)	16.4 (464)	6 baskets	left	stainless	no	29.75 (75.6)	36.50 (92.7)	79.50 (201.9)	467 (212)	Contact factory
REF20i-6B-L00KPG	19.7 (558)	12.8 (362)	6 baskets	left	glass	yes	29.75 (75.6)	30.50 (77.5)	79.50 (201.9)	489 (222)	Contact factory
REF25i-6B-L00KPG	24.6 (697)	16.4 (464)	6 baskets	left	glass	yes	29.75 (75.6)	36.50 (92.7)	79.50 (201.9)	467 (212)	Contact factory
REF20i-6B-L00KPS	19.7 (558)	12.8 (362)	6 baskets	left	stainless	yes	29.75 (75.6)	30.50 (77.5)	79.50 (201.9)	489 (222)	Contact factory
REF25i-6B-L00KPS	24.6 (697)	16.4 (464)	6 baskets	left	stainless	yes	29.75 (75.6)	36.50 (92.7)	79.50 (201.9)	467 (212)	Contact factory
REF12i-5D-R00G	12.0 (340)	7.5 (212)	5 drawers	right	glass	no	23.75 (60.3)	26.60 (67.6)	72.00 (182.9)	420 (191)	Contact factory
REF20i-6D-R0000G	19.7 (558)	13.8 (391)	6 drawers	right	glass	no	29.75 (75.6)	30.50 (77.5)	79.50 (201.9)	519 (236)	Contact factory
REF25i-6D-R0000G	24.6 (697)	18.2 (515)	6 drawers	right	glass	no	29.75 (75.6)	36.50 (92.7)	79.50 (201.9)	541 (246)	Contact factory
REF12i-5D-R00S	12.0 (340)	7.5 (212)	5 drawers	right	stainless	no	23.75 (60.3)	26.60 (67.6)	72.00 (182.9)	420 (191)	Contact factory
REF20i-6D-R0000S	19.7 (558)	13.8 (391)	6 drawers	right	stainless	no	29.75 (75.6)	30.50 (77.5)	79.50 (201.9)	519 (236)	Contact factory
REF25i-6D-R0000S	24.6 (697)	18.2 (515)	6 drawers	right	stainless	no	29.75 (75.6)	36.50 (92.7)	79.50 (201.9)	541 (246)	Contact factory
REF12i-5D-L00G	12.0 (340)	7.5 (212)	5 drawers	left	glass	no	23.75 (60.3)	26.60 (67.6)	72.00 (182.9)	420 (191)	Contact factory
REF20i-6D-L0000G	19.7 (558)	13.8 (391)	6 drawers	left	glass	no	29.75 (75.6)	30.50 (77.5)	79.50 (201.9)	519 (236)	Contact factory
REF25i-6D-L0000G	24.6 (697)	18.2 (515)	6 drawers	left	glass	no	29.75 (75.6)	36.50 (92.7)	79.50 (201.9)	541 (246)	Contact factory
REF12i-5D-L00S	12.0 (340)	7.5 (212)	5 drawers	left	stainless	no	23.75 (60.3)	26.60 (67.6)	72.00 (182.9)	420 (191)	Contact factory
REF20i-6D-L0000S	19.7 (558)	13.8 (391)	6 drawers	left	stainless	no	29.75 (75.6)	30.50 (77.5)	79.50 (201.9)	519 (236)	Contact factory
REF25i-6D-L0000S	24.6 (697)	18.2 (515)	6 drawers	left	stainless	no	29.75 (75.6)	36.50 (92.7)	79.50 (201.9)	541 (246)	Contact factory

REF12i, REF20i and REF25i Omnicell FlexLock-ready single door upright refrigerators

Infinity Series upright refrigerators designed for installation of Omnicell® XT FlexLock Refrigerator Lock and Temperature Monitor, with variable capacity compressor, LCD touchscreen user interface, right-hinged or left-hinged door with ADA-compliant full length locking handle, stainless steel interior/exterior, integral data and event logging, user-programmable temperature display and integral alarming functions, quick-connect RTD probe with 1 year certificate of NIST-traceable calibration, heavy-duty dual casters. 115V/60/1 (103-132V) electrical. Interchangeable storage options allow the interior cabinet space to be configured with shelves, baskets or drawers to your exact needs. Certified to meet NSF/ANSI 456 standard for vaccine storage.

For additional product information, request form# 1027.

See page 29 for additional accessory information.

Item number	Cubic capacity cu ft (L)	Vaccine storage capacity cu ft (L)	Storage system	Hinging	Door style	Keypad	Width in (cm)	Depth in (cm)	Height in (cm)	Approx. ship wt lb (kg)	List price
REFOMN12i-4S-R00G	12.0 (340)	7.2 (204)	4 shelves	right	glass	no	23.75 (60.3)	26.60 (67.6)	72.00 (182.9)	420 (191)	Contact factory
REFOMN20i-4S-R0000G	19.7 (558)	12.7 (360)	4 shelves	right	glass	no	29.75 (75.6)	30.50 (77.5)	79.50 (201.9)	431 (196)	Contact factory
REFOMN25i-4S-R0000G	24.6 (697)	16.8 (476)	4 shelves	right	glass	no	29.75 (75.6)	36.50 (92.7)	79.50 (201.9)	477 (217)	Contact factory
REFOMN12i-4S-R00S	12.0 (340)	7.2 (204)	4 shelves	right	stainless	no	23.75 (60.3)	26.60 (67.6)	72.00 (182.9)	420 (191)	Contact factory
REFOMN12i-4S-L00G	12.0 (340)	7.2 (204)	4 shelves	left	glass	no	23.75 (60.3)	26.60 (67.6)	72.00 (182.9)	420 (191)	Contact factory
REFOMN20i-4S-L0000G	19.7 (558)	12.7 (360)	4 shelves	left	glass	no	29.75 (75.6)	30.50 (77.5)	79.50 (201.9)	431 (196)	Contact factory
REFOMN25i-4S-L0000G	24.6 (697)	16.8 (476)	4 shelves	left	glass	no	29.75 (75.6)	36.50 (92.7)	79.50 (201.9)	477 (217)	Contact factory
REFOMN20i-6B-R0000G	19.7 (558)	12.8 (362)	6 baskets	right	glass	no	29.75 (75.6)	30.50 (77.5)	79.50 (201.9)	489 (222)	Contact factory
REFOMN25i-6B-R0000G	24.6 (697)	16.4 (464)	6 baskets	right	glass	no	29.75 (75.6)	36.50 (92.7)	79.50 (201.9)	467 (212)	Contact factory
REFOMN20i-6B-L0000G	19.7 (558)	12.8 (362)	6 baskets	left	glass	no	29.75 (75.6)	30.50 (77.5)	79.50 (201.9)	489 (222)	Contact factory
REFOMN25i-6B-L0000G	24.6 (697)	16.4 (464)	6 baskets	left	glass	no	29.75 (75.6)	36.50 (92.7)	79.50 (201.9)	467 (212)	Contact factory

REF20i-BB and REF25i-BB blood bank single door upright refrigerators

Infinity Series upright refrigerators with variable capacity compressor, LCD touchscreen user interface, six full-extension stainless steel drawers, right-hinged door with ADA-compliant full length locking handle, stainless steel interior/exterior, integral data and event logging, user-programmable temperature display and integral alarming functions, integral 6.00" (15.24 cm) 7-day chart recorder standard with 50 Celsius charts, quick-connect RTD probe with 1 year certificate of NIST-traceable calibration, heavy-duty dual casters. 115V/60/1 (103-132V) electrical. Meets AABB, ARC and FDA standards for blood storage at 4 C.

For additional product information, request form# 1028.

See page 29 for additional accessory information.

Item number	Cubic capacity cu ft (L)	Bags (450 ml)	Storage system	Hinging	Door style	Heated door	Keypad	Width in (cm)	Depth in (cm)	Height in (cm)	Approx. ship wt lb (kg)	List price
REF20i-BB-R0000G	19.7 (558)	312	6 drawers	right	glass	no	no	29.75 (75.6)	30.50 (77.5)	79.50 (201.9)	519 (236)	Contact factory
REF25i-BB-R0000G	24.6 (697)	432	6 drawers	right	glass	no	no	29.75 (75.6)	36.50 (92.7)	79.50 (201.9)	541 (246)	Contact factory


Upright refrigerators, fixed speed

REF12-LB single door upright refrigerators for laboratory and pharmacy

Medical-grade laboratory and pharmacy refrigerators for critical product storage. Stainless steel interior/ exterior with top temperature probe and 16 oz bottle of glycerine. Right-hinged or left-hinged self-closing doors available in full-view, double pane glass with Low-E coating or solid stainless steel. External 7" touchscreen LCD user interface with integral data and event logging, user-programmable temperature display and integral alarming functions. 115V/60/1 (103-132V) electrical. 4 epoxy-coated shelves.

For additional product information, request form# 8545.


See page 29 for additional accessory information.





REF12-LB

Item number	Cubic capacity cu ft (L)	Storage system	Hinging	Door style	Keypad	Width in (cm)	Depth in (cm)	Height in (cm)	Approx. ship wt lb (kg)	List price
REF12-LB-R00G	11.8 (334)	4 shelves	right	glass	no	23.62 (60.0)	27.25 (69.2)	72.75 (184.8)	420 (191)	Contact factory
REF12-LB-R00S	11.8 (334)	4 shelves	right	stainless	no	23.62 (60.0)	27.25 (69.2)	72.75 (184.8)	420 (191)	Contact factory
REF12-LB-L00G	11.8 (334)	4 shelves	left	glass	no	23.62 (60.0)	27.25 (69.2)	72.75 (184.8)	420 (191)	Contact factory


Upright refrigerators, fixed speed



REF45-LB


REF45-PH
REFVAC45-LB/PH


REF45-PD



REF45-BB

REF45-LB/PH double door upright refrigerators for laboratory and pharmacy

Medical-grade laboratory and pharmacy refrigerators for critical product storage. Stainless steel interior/exterior with top temperature probe and 16 oz bottle of glycerine. Right-hinged, left-hinged or outer-hinged self-closing doors available in full-view, double pane glass with Low-E coating or solid stainless steel – must be specified at time of order. External 7" touchscreen LCD user interface with integral data and event logging, user-programmable temperature display and integral alarming functions. 115V/60/1 (103-132V) electrical. 8 epoxy-coated shelves, 12 roll-out baskets or 12 full-extension stainless steel drawers.

For additional product information, request form# 8150 for REF45-LB, 8155 for REF45-PH, or 8595 for REF45-PD.

See page 29 for additional accessory information.

Item number	Cubic capacity cu ft (L)	Storage system	Hinging	Door style	Keypad	Width in (cm)	Depth in (cm)	Height in (cm)	Approx. ship wt lb (kg)	List price
REF45-LB-R0000G	45.0 (1274)	8 shelves	right	glass	no	59.75 (151.8)	33.55 (85.2)	79.54 (202.0)	750 (341)	Contact factory
REF45-LB-L0000G	45.0 (1274)	8 shelves	left	glass	no	59.75 (151.8)	33.55 (85.2)	79.54 (202.0)	750 (341)	Contact factory
REF45-LB-00000G	45.0 (1274)	8 shelves	outer	glass	no	59.75 (151.8)	33.55 (85.2)	79.54 (202.0)	750 (341)	Contact factory
REF45-LB-00000S	45.0 (1274)	8 shelves	outer	stainless	no	59.75 (151.8)	33.55 (85.2)	79.54 (202.0)	750 (341)	Contact factory
REF45-LB-000KPG	45.0 (1274)	8 shelves	outer	glass	yes	59.75 (151.8)	33.55 (85.2)	79.54 (202.0)	750 (341)	Contact factory
REF45-LB-000KPS	45.0 (1274)	8 shelves	outer	stainless	yes	59.75 (151.8)	33.55 (85.2)	79.54 (202.0)	750 (341)	Contact factory
REF45-PH-R0000G	45.0 (1274)	12 baskets	right	glass	no	59.75 (151.8)	33.55 (85.2)	79.54 (202.0)	890 (404)	Contact factory
REF45-PH-L0000G	45.0 (1274)	12 baskets	left	glass	no	59.75 (151.8)	33.55 (85.2)	79.54 (202.0)	890 (404)	Contact factory
REF45-PH-00000G	45.0 (1274)	12 baskets	outer	glass	no	59.75 (151.8)	33.55 (85.2)	79.54 (202.0)	890 (404)	Contact factory
REF45-PH-00000S	45.0 (1274)	12 baskets	outer	stainless	no	59.75 (151.8)	33.55 (85.2)	79.54 (202.0)	890 (404)	Contact factory
REF45-PH-000KPG	45.0 (1274)	12 baskets	outer	glass	yes	59.75 (151.8)	33.55 (85.2)	79.54 (202.0)	890 (404)	Contact factory
REF45-PH-000KPS	45.0 (1274)	12 baskets	outer	stainless	yes	59.75 (151.8)	33.55 (85.2)	79.54 (202.0)	890 (404)	Contact factory
REF45-PD-00000G	45.0 (1274)	12 drawers	outer	glass	no	59.75 (151.8)	33.55 (85.2)	79.54 (202.0)	750 (341)	Contact factory

REFVAC45 double door upright NSF 456 certified vaccine refrigerators

Medical-grade NSF/ANSI 456 certified refrigerators for vaccine storage. Stainless steel interior/exterior with top temperature probe and 16 oz bottle of glycerine. Outer hinges, self-closing door in full-view, double pane glass with Low-E coating. External 7" touchscreen LCD user interface with integral data and event logging, user-programmable temperature display and integral alarming functions. 115V/60/1 (103-132V) electrical. 8 epoxy-coated shelves on REFVAC45-LB models, 12 roll-out baskets on REFVAC45-PH models or 12 stainless steel drawers on REFVAC45-PD models.

For additional product information, request form# 9010.

See page 29 for additional accessory information.

Item number	Cubic capacity cu ft (L)	Storage System	Hinging	Door style	Keypad	Width in (cm)	Depth in (cm)	Height in (cm)	Approx. ship wt lb (kg)	List price
REFVAC45-LB-00000G	45.0 (1274)	8 Shelves	outer	glass	no	59.75 (151.8)	33.55 (85.2)	79.54 (202.0)	750 (341)	Contact factory
REFVAC45-PH-00000G	45.0 (1274)	12 Baskets	outer	glass	no	59.75 (151.8)	33.55 (85.2)	79.54 (202.0)	890 (404)	Contact factory

REF45-BB double door upright refrigerators for blood banks


Blood bank refrigerators meet AABB and FDA requirements for storage of blood at 4 C. Stainless steel interior/exterior with top and bottom temperature probes and 16 oz bottle of glycerine. Right-hinged self-closing glass doors with full-view, double pane glass with Low-E coating. External 7" touchscreen LCD user interface with integral data and event logging, user-programmable temperature display and integral alarming functions. 6.00" (15.24 cm) chart recorder. 115V/60/1 (103-132V) electrical. 12 stainless steel, full-extension drawers standard.

For additional product information, request form# 8160.


See page 29 for additional accessory information.

Item number	Cubic capacity cu ft (L)	Bags (450 ml)	Storage system	Hinging	Door style	Keypad	Width in (cm)	Depth in (cm)	Height in (cm)	Approx. ship wt lb (kg)	List price
REF45-BB-R0000G	45.0 (1274)	816	12 drawers	right	glass	no	59.75 (151.8)	33.55 (85.2)	79.54 (202.0)	930 (422)	Contact factory

Countertop freezers



FZR1


FZR2
FZRVAC2

FZR1 and FZR2 countertop freezers

Medical-grade countertop freezers for small storage needs. Forced air, external temperature display in F or C, integral high/low alarming and epoxy-coated shelving. Stainless steel construction on interior/exterior. Right-hinged door only. 115V/60/1 electrical.

For additional product information, request form# 6860 for FZR1 or 6865 for FZR2.

See page 28 for additional accessory information.

Item number	Cubic capacity cu ft (L)	Hinging	Keypad	Door style	Width in (cm)	Depth in (cm)	Height in (cm)	Approx. ship wt lb (kg)	List price
FZR1	0.6 (16)	right	no	stainless	18.60 (47.2)	24.00 (61.0)	17.93 (45.5)	108 (49)	\$6,995
FZR1-KP	0.6 (16)	right	yes	stainless	18.60 (47.2)	24.00 (61.0)	17.93 (45.5)	108 (49)	\$7,805
FZR2	1.6 (44)	right	no	stainless	18.60 (47.2)	24.00 (61.0)	27.93 (70.9)	126 (57)	\$7,445
FZR2-KP	1.6 (44)	right	yes	stainless	18.60 (47.2)	24.00 (61.0)	27.93 (70.9)	126 (57)	\$8,260

FZRVAC2 countertop NSF 456 certified vaccine freezers


Medical-grade countertop NSF/ANSI 456 certified vaccine freezers. Forced air, external temperature display in F or C, integral high/low alarming and epoxy-coated shelving. Stainless steel construction on interior/exterior. Right-hinged door only. 115V/60/1 electrical.

For additional product information, request form# 9125.


See page 28 for additional accessory information.

Item number	Cubic capacity cu ft (L)	Hinging	Keypad	Door style	Width in (cm)	Depth in (cm)	Height in (cm)	Approx. ship wt lb (kg)	List price
FZRVAC2	1.6 (44)	right	no	stainless	18.60 (47.2)	24.00 (61.0)	27.93 (70.9)	126 (57)	\$7,680

Undercounter freezers



Performance Plus
LED display



Performance Plus
7" LCD touchscreen display

FZR4P and FZR5P Performance Plus undercounter freezers

Medical-grade -20 C (-4 F), undercounter freezers, freestanding or stackable, with external temperature display in F or C, integral alarming and 2 epoxy-coated shelves. Stainless steel construction on interior/exterior. Right-hinged or left-hinged door. 115V/60/1 electrical. For undercounter applications: model FZR4P fits below 34.00" (86.4 cm) ADA-compatible counter and model FZR5P fits below a standard 36.00" (91.4 cm) high counter.

For additional product information, request form# 6465 for FZR4P, 6470 for FZR5P, 6515 for FZR4P-T, or 6520 for FZR5P-T.

See page 28 for additional accessory information.

Item number	Cubic capacity cu ft (L)	Hinging	Keypad	Door style	Width in (cm)	Depth in (cm)	Height in (cm)	Approx. ship wt lb (kg)	List price
LED digital temperature display									
FZR4P-OR-00-00	3.9 (110)	right	no	stainless	23.75 (60.3)	27.00 (68.6)	31.38 (79.7)	205 (93)	\$9,310
FZR5P-OR-00-00	4.5 (127)	right	no	stainless	23.75 (60.3)	27.00 (68.6)	34.00 (86.4)	205 (93)	\$9,310
FZR4P-OR-KP-00	3.9 (110)	right	yes	stainless	23.75 (60.3)	27.00 (68.6)	31.38 (79.7)	205 (93)	\$10,120
FZR5P-OR-KP-00	4.5 (127)	right	yes	stainless	23.75 (60.3)	27.00 (68.6)	34.00 (86.4)	205 (93)	\$10,120
FZR4P-OL-00-00	3.9 (110)	left	no	stainless	23.75 (60.3)	27.00 (68.6)	31.38 (79.7)	205 (93)	\$9,310
FZR5P-OL-00-00	4.5 (127)	left	no	stainless	23.75 (60.3)	27.00 (68.6)	34.00 (86.4)	205 (93)	\$9,310
FZR4P-OL-KP-00	3.9 (110)	left	yes	stainless	23.75 (60.3)	27.00 (68.6)	31.38 (79.7)	205 (93)	\$10,120
FZR5P-OL-KP-00	4.5 (127)	left	yes	stainless	23.75 (60.3)	27.00 (68.6)	34.00 (86.4)	205 (93)	\$10,120
7" LCD touchscreen digital temperature display									
FZR4P-TR-00-00	3.9 (110)	right	no	stainless	23.75 (60.3)	27.00 (68.6)	31.38 (79.7)	205 (93)	\$10,935
FZR5P-TR-00-00	4.5 (127)	right	no	stainless	23.75 (60.3)	27.00 (68.6)	34.00 (86.4)	205 (93)	\$10,935
FZR4P-TR-KP-00	3.9 (110)	right	yes	stainless	23.75 (60.3)	27.00 (68.6)	31.38 (79.7)	205 (93)	\$11,410
FZR5P-TR-KP-00	4.5 (127)	right	yes	stainless	23.75 (60.3)	27.00 (68.6)	34.00 (86.4)	205 (93)	\$11,410
FZR4P-TL-00-00	3.9 (110)	left	no	stainless	23.75 (60.3)	27.00 (68.6)	31.38 (79.7)	205 (93)	\$10,935
FZR5P-TL-00-00	4.5 (127)	left	no	stainless	23.75 (60.3)	27.00 (68.6)	34.00 (86.4)	205 (93)	\$10,935
FZR4P-TL-KP-00	3.9 (110)	left	yes	stainless	23.75 (60.3)	27.00 (68.6)	31.38 (79.7)	205 (93)	\$11,410
FZR5P-TL-KP-00	4.5 (127)	left	yes	stainless	23.75 (60.3)	27.00 (68.6)	34.00 (86.4)	205 (93)	\$11,410

FZRVAC4P and FZRVAC5P Performance Plus undercounter NSF 456 certified vaccine freezers

Medical-grade undercounter NSF/ANSI 456 certified vaccine freezers. -20 C (-4 F), undercounter freezers, freestanding or stackable, with external temperature display in F or C, integral alarming and 2 epoxy-coated shelves. Stainless steel construction on interior/exterior. Right-hinged door only. 115V/60/1 electrical. For undercounter applications: model FZRVAC4P fits below a standard 34.00" (86.4 cm) ADA-compatible counter and model FZRVAC5P fits below a standard 36.00" (91.4 cm) high counter.

For additional product information, request form# 9120.

See page 28 for additional accessory information.

Item number	Cubic capacity cu ft (L)	Hinging	Keypad	Door style	Width in (cm)	Depth in (cm)	Height in (cm)	Approx. ship wt lb (kg)	List price
LED digital temperature display									
FZRVAC4P-OR-00-00	3.9 (110)	right	no	stainless	23.75 (60.3)	27.00 (68.6)	31.38 (79.7)	205 (93)	\$9,545
FZRVAC5P-OR-00-00	4.5 (127)	right	no	stainless	23.75 (60.3)	27.00 (68.6)	34.00 (86.4)	205 (93)	\$9,545
7" LCD touchscreen digital temperature display									
FZRVAC4P-TR-00-00	3.9 (110)	right	no	stainless	23.75 (60.3)	27.00 (68.6)	31.38 (79.7)	205 (93)	\$11,170
FZRVAC5P-TR-00-00	4.5 (127)	right	no	stainless	23.75 (60.3)	27.00 (68.6)	34.00 (86.4)	205 (93)	\$11,170

FZR5PLP-T Performance Plus undercounter plasma freezer


High performance -30 C (-22 F), undercounter plasma freezer, freestanding or stackable, with 7" LCD touchscreen user interface with integral data and event logging. Stainless steel construction on interior/exterior with interior LED lighting. Right-hinged or left-hinged door. 115V/60/1 electrical. For undercounter applications: fits below a standard 36.00" (91.4 cm) high counter. Two full extension stainless drawers standard. Includes separate temperature surveillance module with audible/visual alarm, 7-day chart recorder and digital product temperature display. Meets AABB, FDA, ARC requirements.

For additional product information, request form# 6480.

See page 28 for additional accessory information.

Item number	Cubic capacity cu ft (L)	Plasma boxes (300 ml)	Hinging	Keypad	Door style	Width in (cm)	Depth in (cm)	Height in (cm)	Approx. ship wt lb (kg)	List price
FZR5PLP-TR-00-00	4.5 (127)	40	right	no	stainless	23.75 (60.3)	27.00 (68.6)	34.00 (86.4)	205 (93)	\$15,440
FZR5PLP-TR-KP-00	4.5 (127)	40	right	yes	stainless	23.75 (60.3)	27.00 (68.6)	34.00 (86.4)	205 (93)	\$15,915
FZR5PLP-TL-00-00	4.5 (127)	40	left	no	stainless	23.75 (60.3)	27.00 (68.6)	34.00 (86.4)	205 (93)	\$15,440
FZR5PLP-TL-KP-00	4.5 (127)	40	left	yes	stainless	23.75 (60.3)	27.00 (68.6)	34.00 (86.4)	205 (93)	\$15,915

Upright freezers



FZR20/25i-4S




FZR20/25i-PL



FZRMD24



FZR8-PC



FZRDCMD17

Infinity Series FZR20i and FZR25i single door upright freezers

Infinity Series upright freezer with variable capacity compressor, LCD touchscreen user interface, right-hinged or left-hinged door with ADA-compliant full length locking handle, stainless steel interior/exterior, integral data and event logging, user-programmable temperature display and integral alarming functions, quick-connect RTD probe with 1 year certificate of NIST-traceable calibration, heavy-duty dual casters. 115V/60/1 (103-132V) electrical. Interchangeable storage options allow the interior cabinet space to be configured with shelves or drawers to your exact needs. Certified to meet NSF/ANSI 456 standard for vaccine storage.

For additional product information, request form# 1052.

See page 29 for additional accessory information.

Item number	Cubic capacity cu ft (L)	Vaccine storage capacity cu ft (L)	Storage system	Hinging	Door style	Heated door	Keypad	Width in (cm)	Depth in (cm)	Height in (cm)	Approx. ship wt lb (kg)	List price
FZR20i-4S-RHT00S	19.7 (558)	12.7 (360)	4 shelves	right	stainless	yes	no	29.75 (75.6)	30.50 (77.5)	79.50 (201.9)	449 (203)	Contact factory
FZR25i-4S-RHT00S	24.6 (697)	16.8 (476)	4 shelves	right	stainless	yes	no	29.75 (75.6)	36.50 (92.7)	79.50 (201.9)	485 (220)	Contact factory
FZR20i-4S-RHTKPS	19.7 (558)	12.7 (360)	4 shelves	right	stainless	yes	yes	29.75 (75.6)	30.50 (77.5)	79.50 (201.9)	449 (203)	Contact factory
FZR25i-4S-RHTKPS	24.6 (697)	16.8 (476)	4 shelves	right	stainless	yes	yes	29.75 (75.6)	36.50 (92.7)	79.50 (201.9)	485 (220)	Contact factory
FZR20i-4S-LHT00S	19.7 (558)	12.7 (360)	4 shelves	left	stainless	yes	no	29.75 (75.6)	30.50 (77.5)	79.50 (201.9)	449 (203)	Contact factory
FZR25i-4S-LHT00S	24.6 (697)	16.8 (476)	4 shelves	left	stainless	yes	no	29.75 (75.6)	36.50 (92.7)	79.50 (201.9)	485 (220)	Contact factory
FZR20i-4S-LHTKPS	19.7 (558)	12.7 (360)	4 shelves	left	stainless	yes	yes	29.75 (75.6)	30.50 (77.5)	79.50 (201.9)	449 (203)	Contact factory
FZR25i-4S-LHTKPS	24.6 (697)	16.8 (476)	4 shelves	left	stainless	yes	yes	29.75 (75.6)	36.50 (92.7)	79.50 (201.9)	485 (220)	Contact factory

Infinity Series FZR20i and FZR25i with Wi-Fi remote monitoring single door upright freezers

Infinity Series upright freezers with variable capacity compressor, Wi-Fi based cloud communication functionality, LCD touchscreen user interface, right-hinged or left-hinged door with ADA-compliant full length locking handle, stainless steel interior/exterior, integral data and event logging, user-programmable temperature display and integral alarming functions, quick-connect RTD probe with 1 year certificate of NIST-traceable calibration, heavy-duty dual casters. 115V/60/1 (103-132V) electrical. Interchangeable storage options allow the interior cabinet space to be configured with shelves or drawers to your exact needs. Certified to meet NSF/ANSI 456 standard for vaccine storage.

For additional product information, request form# 1052.

See page 29 for additional accessory information.

Item number	Cubic capacity cu ft (L)	Vaccine storage capacity cu ft (L)	Storage system	Hinging	Door style	Heated door	Keypad	Width in (cm)	Depth in (cm)	Height in (cm)	Approx. ship wt lb (kg)	List price
FZR20i-4S-RHT00SN	19.7 (558)	12.7 (360)	4 shelves	right	stainless	yes	no	29.75 (75.6)	30.50 (77.5)	79.50 (201.9)	449 (203)	Contact factory
FZR25i-4S-RHT00SN	24.6 (697)	16.8 (476)	4 shelves	right	stainless	yes	no	29.75 (75.6)	36.50 (92.7)	79.50 (201.9)	485 (220)	Contact factory
FZR20i-4S-LHT00SN	19.7 (558)	12.7 (360)	4 shelves	left	stainless	yes	no	29.75 (75.6)	30.50 (77.5)	79.50 (201.9)	449 (203)	Contact factory
FZR25i-4S-LHT00SN	24.6 (697)	16.8 (476)	4 shelves	left	stainless	yes	no	29.75 (75.6)	36.50 (92.7)	79.50 (201.9)	485 (220)	Contact factory

Infinity Series FZR20i and FZR25i plasma single door upright freezers

Infinity Series plasma freezers with variable capacity compressor. LCD touchscreen user interface, right-hinged or left-hinged door with ADA-compliant full length locking handle, stainless steel interior/exterior with top and bottom temperature probes and 16 oz bottle of glycerine, integral data and event logging, user-programmable temperature display and integral alarming functions, heavy-duty dual casters. 115V/60/1 (103-132V) electrical. 6.00" (15.24 cm) chart recorder with 50 Celsius charts and 8 full-extension stainless steel drawers. Meets AABB and FDA requirements for storage of blood plasma at -30 C.

For additional product information, request form# 1053.

See page 29 for additional accessory information.

Item number	Cubic capacity cu ft (L)	FFP ¹ cartons (5"x8"x1.13")	Storage system	Hinging	Door style	Heated door	Keypad	Width in (cm)	Depth in (cm)	Height in (cm)	Approx. ship wt lb (kg)	List price
FZR20i-PL-RHT00S	19.7 (558)	352	8 drawers	right	stainless	yes	no	29.75 (75.6)	30.50 (77.5)	79.50 (201.9)	539 (244)	Contact factory
FZR25i-PL-RHT00S	24.6 (697)	472	8 drawers	right	stainless	yes	no	29.75 (75.6)	36.50 (92.7)	79.50 (201.9)	598 (271)	Contact factory
FZR20i-PL-RHTKPS	19.7 (558)	352	8 drawers	right	stainless	yes	yes	29.75 (75.6)	30.50 (77.5)	79.50 (201.9)	539 (244)	Contact factory
FZR25i-PL-RHTKPS	24.6 (697)	472	8 drawers	right	stainless	yes	yes	29.75 (75.6)	36.50 (92.7)	79.50 (201.9)	598 (271)	Contact factory
FZR20i-PL-LHT00S	19.7 (558)	352	8 drawers	left	stainless	yes	no	29.75 (75.6)	30.50 (77.5)	79.50 (201.9)	539 (244)	Contact factory
FZR25i-PL-LHT00S	24.6 (697)	472	8 drawers	left	stainless	yes	no	29.75 (75.6)	36.50 (92.7)	79.50 (201.9)	598 (271)	Contact factory
FZR20i-PL-LHTKPS	19.7 (558)	352	8 drawers	left	stainless	yes	yes	29.75 (75.6)	30.50 (77.5)	79.50 (201.9)	539 (244)	Contact factory
FZR25i-PL-LHTKPS	24.6 (697)	472	8 drawers	left	stainless	yes	yes	29.75 (75.6)	36.50 (92.7)	79.50 (201.9)	598 (271)	Contact factory

¹ Fresh frozen plasma.

FZRMD24 -30 C single door upright freezer for laboratory

PHCbi brand high performance biomedical freezer, 24.4 cu ft capacity, -18 C to -40 C temperature range, solid door, 4 adjustable shelves, microprocessor controller with digital display. High/low temperature, power failure and door alarming. 115V/60/1 electrical. ENERGY STAR certified.

Item number	Cubic capacity cu ft (L)	Storage system	Width in (cm)	Depth in (cm)	Height in (cm)	Approx. ship wt lb (kg)	List price
FZRMD24	24.4 (690)	4 shelves	30.30 (77.0)	32.70 (83.0)	77.00 (195.5)	568 (258)	Contact factory

FZR8-PC plasma chiller

High performance -40 C to -40 F plasma chiller with touchscreen temperature controller and alarms. Stainless steel AISI 304 interior and exterior construction. 220V/60/3 electrical. 4 casters and 8 shelves.

Intended for use as a rapid freezer. This is not intended for long-term storage.

For additional product information, request form# 8930.

Item number	Cubic capacity cu ft (L)	Storage system	Width in (cm)	Depth in (cm)	Height in (cm)	Approx. ship wt lb (kg)	List price
FZR8-PC	7.5 cu ft (212) (72) bags	8 shelves	31.50 (80.0)	32.88 (83.5)	77.31 (196.4)	541 (245)	Contact factory


FZRDCMD17 dual chamber biomedical ECO upright freezer

PHCbi brand -40 C biomedical ECO dual chamber freezer, 16.9 cu ft capacity (8.46 cu ft per chamber), -20 C to -40 C temperature range, solid doors, 6 shelves (4 adjustable), microprocessor controller with LED display. Manual defrost function. High/low temperature, power failure alarming. ENERGY STAR certified.


For additional product information, request form# 12618.

Item number	Cubic capacity cu ft (L)	Storage system	Width in (cm)	Depth in (cm)	Height in (cm)	Voltage	Approx. ship wt lb (kg)	List price
FZRDCMD17	16.9 (479)	6 shelves	31.20 (79.3)	30.30 (77.0)	70.90 (180.1)	115/60	410 (186)	Contact factory


Combination refrigerator/freezer



REFFZR9



REFFZR16



REFFZR21

REFFZR9 pharmaceutical combination refrigerator and freezer

Model REFFZR9-GS. PHCbi brand pharmaceutical combination 6.3 cu ft refrigerator (+2 C to +14 C) and 2.8 cu ft freezer (-30 C to -20 C), independent refrigeration systems, glass door on refrigerator, solid door on freezer, 3 glass shelves in refrigerator/1 coated wire shelf in freezer.

Model REFFZR9-SS. PHCbi brand pharmaceutical combination 6.3 cu ft refrigerator (+2 C to +14 C) and 2.8 cu ft freezer (-30 C to -20 C), independent refrigeration systems, solid door on refrigerator and freezer, 3 glass shelves in refrigerator/1 coated wire shelf in freezer.

For additional product information, request form# 12839.

Item number	Cubic capacity cu ft (L)	Storage system	Width in (cm)	Depth in (cm)	Height in (cm)	Voltage	Approx. ship wt lb (kg)	List price
REFFZR9	6.3 (178) refrigerator 2.8 (79) freezer	3 glass shelves in refrigerator 1 wire shelf in freezer	20.00 (50.8)	25.00 (63.5)	71.20 (180.1)	115/60	210 (95)	Contact factory

REFFZR16 pharmaceutical combination refrigerator and freezer

Model REFFZR16-GS. PHCbi brand pharmaceutical combination 11.5 cu ft refrigerator (+2 C to +14 C) and 4.8 cu ft freezer (-30 C to -20 C), independent refrigeration systems, glass double doors on refrigerator, solid double doors on freezer, 3 adjustable shelves in refrigerator/2 shelves in freezer, microprocessor controller with softkey interface and OLED display. High/low temperature, power, sensor and door alarms.

Model REFFZR16-SS. PHCbi brand pharmaceutical combination 11.5 cu ft refrigerator (+2 C to +14 C) and 4.8 cu ft freezer (-30 C to -20 C), independent refrigeration systems, solid double doors on refrigerator and freezer, 3 adjustable shelves in refrigerator/2 shelves in freezer, microprocessor controller with LED display. High/low temperature, power, sensor and door alarms.

For additional product information, request form# 12507.

Item number	Cubic capacity cu ft (L)	Storage system	Width in (cm)	Depth in (cm)	Height in (cm)	Voltage	Approx. ship wt lb (kg)	List price
REFFZR16	11.5 (326) refrigerator 4.8 (136) freezer	3 shelves in refrigerator 2 shelves in freezer	31.50 (80.0)	25.20 (64.0)	71.30 (181.1)	115/60	337 (153)	Contact factory


REFFZR21 pharmaceutical combination refrigerator and freezer

PHCbi brand pharmaceutical combination 14.7 cu ft refrigerator (+2 C to +14 C) and 6.2 cu ft freezer (-30 C to -20 C), independent refrigeration systems, glass double doors on refrigerator, solid double doors on freezer, 3 adjustable shelves in refrigerator/2 shelves in freezer, microprocessor controller with softkey interface and OLED display. High/low temperature, power, sensor and door alarms.


For additional product information, request form# 12620.

Item number	Cubic capacity cu ft (L)	Storage system	Width in (cm)	Depth in (cm)	Height in (cm)	Voltage	Approx. ship wt lb (kg)	List price
REFFZR21-GS	14.7 (415) refrigerator 6.2 (176) freezer	3 shelves in refrigerator 2 shelves in freezer	35.40 (90.0)	28.10 (71.5)	75.20 (191.0)	115/60	439 (199)	Contact factory

Ultra-low chest freezers



FZRC3



FZRC25

FZRC3 -80 C ultra-low temperature chest freezer

PHCbi brand VIP Series -80 C ultra-low temperature chest freezer, 3.0 cu ft capacity, -60 C to -80 C temperature range, insulated locking lid with sub for additional temperature protection, microprocessor controller with LED display. High/low temperature, power failure alarming.

For additional product information, request form# 13419.

Item number	Cubic capacity cu ft (L)	Width in (cm)	Depth in (cm)	Height in (cm)	Voltage	Approx. ship wt lb (kg)	List price
FZRC3-ULT-115	3.0 (85)	21.70 (55.0)	27.00 (68.5)	37.20 (94.5)	115/60	190 (86)	Contact factory


FZRC25 -86 C ultra-low temperature chest freezer

PHCbi brand TwinGuard Series -86 C ultra-low temperature chest freezer with dual cooling system, 25.3 cu ft capacity, -50 C to -86 C temperature range, insulated locking lid with sub lid for additional temperature protection, microprocessor controller with touchscreen display. Comprehensive alarm system with audible and visual alarms.

For additional product information, request form# 12684.

Item number	Cubic capacity cu ft (L)	Width in (cm)	Depth in (cm)	Height in (cm)	Voltage	Approx. ship wt lb (kg)	List price
FZRC25-ULT-220	25.3 (708)	90.60 (230.0)	37.60 (95.5)	42.10 (107.0)	220/60	807 (366)	Contact factory

Ultra-low upright freezers



FZR19 -86 C ultra-low temperature VIP ECO upright freezer

PHCbi brand VIP ECO Series -86 C ultra-low temperature upright freezer, 18.6 cu ft capacity, -50 C to -86 C temperature range, 1 locking outer door with 2 insulated inner doors for additional temperature protection, 3 adjustable shelves, microprocessor controller with touchscreen display. Comprehensive alarm system with audible and visual alarms. ENERGY STAR certified.

For additional product information, request form# 12600.

Item number	Cubic capacity cu ft (L)	Storage system	Width in (cm)	Depth in (cm)	Height in (cm)	Voltage	Approx. ship wt lb (kg)	List price
FZR19-ULT-115	18.6 (528)	3 shelves	31.10 (79.0)	34.70 (88.2)	78.50 (199.3)	115/60	628 (285)	Contact factory
FZR19-ULT-220	18.6 (528)	3 shelves	31.10 (79.0)	34.70 (88.2)	78.50 (199.3)	220/60	628 (285)	Contact factory

FZR26 -86 C ultra-low temperature VIP ECO upright freezer

PHCbi brand VIP ECO Series -86 C ultra-low temperature upright freezer, 25.7 cu ft capacity, -40 C to -90 C temperature range, 1 locking outer door with 2 insulated inner doors for additional temperature protection, 3 adjustable shelves, microprocessor controller with touchscreen display. Comprehensive alarm system with audible and visual alarms. ENERGY STAR certified.

For additional product information, request form# 12506.

Item number	Cubic capacity cu ft (L)	Storage system	Width in (cm)	Depth in (cm)	Height in (cm)	Voltage	Approx. ship wt lb (kg)	List price
FZR26-ULT-115	25.7 (729)	3 shelves	25.7 (729)	36.80 (93.5)	78.50 (199.3)	115/60	827 (375)	Contact factory
FZR26-ULT-220	25.7 (729)	3 shelves	25.7 (729)	36.80 (93.5)	78.50 (199.3)	220/60	827 (375)	Contact factory

FZR29 -86 C ultra-low temperature VIP ECO upright freezer

PHCbi brand VIP ECO Series -86 C ultra-low temperature upright freezer, 29.8 cu ft capacity, -50 C to -86 C temperature range, 1 locking outer door with 2 insulated inner doors for additional temperature protection, 3 adjustable shelves, microprocessor controller with touchscreen display. Comprehensive alarm system with audible and visual alarms. ENERGY STAR certified.

For additional product information, request form# 12601.

Item number	Cubic capacity cu ft (L)	Storage system	Width in (cm)	Depth in (cm)	Height in (cm)	Voltage	Approx. ship wt lb (kg)	List price
FZR29-ULT-115	29.8 (845)	3 shelves	45.30 (115.0)	34.30 (87.0)	78.50 (199.3)	115/60	855 (387)	Contact factory

FZRDR13 -86 C ultra-low temperature TwinGuard upright freezer

PHCbi brand TwinGuard Series -86 C ultra-low temperature upright freezer with dual cooling system, 12.7 cu ft capacity, -50 C to -86 C temperature range, 1 locking outer door with 2 inner insulated doors for additional temperature protection, 3 adjustable shelves, microprocessor controller with touchscreen display. Comprehensive alarm system with audible and visual alarms.

For additional product information, request form# 12615.

Item number	Cubic capacity cu ft (L)	Storage system	Width in (cm)	Depth in (cm)	Height in (cm)	Voltage	Approx. ship wt lb (kg)	List price
FZRDR13-ULT-220	12.7 (360)	3 shelves	26.40 (67.0)	34.70 (88.2)	72.40 (184.0)	220/60	556 (252)	Contact factory

FZRDR19 -86 C ultra-low temperature TwinGuard upright freezer

PHCbi brand TwinGuard Series -86 C ultra-low temperature upright freezer with dual cooling system, 18.6 cu ft capacity, -50 C to -86 C temperature range, 1 locking outer door with 2 insulated inner doors for additional temperature protection, 3 adjustable shelves, microprocessor controller with touchscreen display. Comprehensive alarm system with audible and visual alarms.

For additional product information, request form# 12616.

Item number	Cubic capacity cu ft (L)	Storage system	Width in (cm)	Depth in (cm)	Height in (cm)	Voltage	Approx. ship wt lb (kg)	List price
FZRDR19-ULT-220	18.6 (528)	3 shelves	31.10 (79.0)	34.70 (88.2)	78.50 (199.3)	220/60	723 (328)	Contact factory


FZRDR26 -86 C ultra-low temperature TwinGuard upright freezer

PHCbi brand TwinGuard Series -86 C ultra-low temperature upright freezer with dual cooling system, -50 C to -86 C temperature range, 25.7 cu ft capacity, 1 locking outer door with 2 insulated inner doors for additional temperature protection, 3 adjustable shelves, microprocessor controller with touchscreen display. Comprehensive alarm system with audible and visual alarms.


For additional product information, request form# 12617.

Item number	Cubic capacity cu ft (L)	Storage system	Width in (cm)	Depth in (cm)	Height in (cm)	Voltage	Approx. ship wt lb (kg)	List price
FZRDR26-ULT-220	25.7 (729)	3 shelves	40.60 (103.0)	36.8 (93.5)	78.50 (199.3)	220/60	827 (375)	Contact factory

Cryogenic freezers and CO2 incubators



FZRC8



CO2INC30-G

FZRC8 -150 C cryogenic chest freezer

PHCbi brand -150 C cryogenic chest freezer with autocascade refrigeration system, 8.2 cu ft capacity, -125 C to -150 C temperature range, 1 locking outer door with 2 insulated inner doors for additional temperature protection, microprocessor controller with LCD display. High/low temperature, sensor, power, and lid alarms.

For additional product information, request form# 12602.

Item number	Cubic capacity cu ft (L)	Width in (cm)	Depth in (cm)	Height in (cm)	Voltage	Approx. ship wt lb (kg)	List price
FZRC8-220	8.2 (232.2)	68.10 (173.0)	30.10 (76.5)	39.80 (101.0)	220/60	961 (436)	Contact factory

CO2INC30 Reach-In CO2 incubator

PHCbi brand Reach-in CO2 incubator, 30.1 cu ft, glass door, normal (80% RH or above) or high (90% RH or above) humidity mode, microprocessor controller with 2 LED displays (temperature and CO2), 5 shelves. Comprehensive alarm system with audible and visual alarms.

For additional product information, request form# 12621.

Item number	Cubic capacity cu ft (L)	Storage system	Width in (cm)	Depth in (cm)	Height in (cm)	Voltage	Approx. ship wt lb (kg)	List price
CO2INC30-G	30.1 (851)	5 shelves	38.60 (98.6)	37.2 (94.5)	80.3 (204.0)	115/60	694 (315)	Contact factory

Refrigerator and freezer accessories

Countertop refrigerator and freezer accessories and warranties

Item number	Description	List price
00969931	Organizing bins, set of 6	\$145
00969956	Additional shelf (1)	\$145
00959296	Glycerine, 16 oz	\$115
00969949	Wall mount kit	\$895
01111947	Casters (set of 4)	\$515
01184845	Pedestal, 2.00" (5.08 cm)	\$810
01025899	Pedestal, fan-assist, 4.50" (11.43 cm)	\$590
01025881	Pedestal, 12.00" (30.5 cm)	\$590
01100742	Stacking kit (countertop on countertop)	\$820
01100759	Stacking kit (countertop on Performance Plus undercounter)	\$820
01142363	Stacking kit (countertop on REF/FZR Series undercounter)	\$820
01092022	NO/NC dry contacts for connection to remote alarm systems	\$95
01570860	Temperature surveillance module (includes alarm, 8.00" (20.32 cm) chart recorder, remote contacts)	\$2,910
01077841	Replacement NTC probe with certificate of NIST-traceable calibration	\$355
01528512	DicksonOne VFC-compliant freestanding display data logger with Wi-Fi and Ethernet capability for use with any refrigerator or freezer. NOTE: Subscription from Dickson required to access data on the cloud.	\$1,300
01528538	DicksonOne VFC-compliant freestanding touchscreen data logger with Power Over Ethernet and Wi-Fi capability for use with any refrigerator or freezer. NOTE: Subscription from Dickson required to access data on the cloud.	\$1,930
01539691	Ambient temperature and humidity sensor, right angle, for use with DicksonOne freestanding display and touchscreen data loggers	\$265
Item number	Description	Net price
EW12	Optional extended one year warranty on parts and labor only (available with new equipment only)	\$150
EW36	Optional extended three year warranty on parts and labor only (available with new equipment only)	\$300

Undercounter refrigerator and freezer accessories and warranties

Item number	Description	List price
01059484	Additional shelf (1), Performance Plus	\$210
01557727	Additional shelves (2), REFADV5-SD	\$105
01053644	Drawer accessory kit (1 drawer, glide hardware, flush front panel), Performance Plus. Not for use with VAC models.	\$450
01067750	Drawer accessory kit (2 drawers, glide hardware, flush front panel), Performance Plus. Not for use with VAC models.	\$610
00959296	Glycerine, 16 oz	\$115
00153700	Wall mount kit, Performance Plus	\$640
01059104	Seismic bracket kit, Performance Plus	\$545
01053636	Casters (set of 4 with spacers), Performance Plus	\$400
01059120	Pedestal base, 23.75" wide x 24.00" deep x 17.00" high (60.3 x 61.0 x 43.2 cm), stainless, Performance Plus	\$1,250
01528157	Stacking kit (Edge Series on Edge Series)	\$800
01054006	Stacking kit (Performance Plus on Performance Plus)	\$800
01067172	Stacking kit (REF/FZR Series on Performance Plus)	\$820
01059096	Universal ADC-compatible bracket (for all medication dispensing system locks), Performance Plus	\$190
01092022	NO/NC dry contacts for connection to remote alarm systems, Performance Plus	\$95
01570860	Temperature surveillance module (includes alarm, 8.00" (20.32 cm) chart recorder, remote contacts)	\$2,910
01077841	Replacement NTC probe with certificate of NIST-traceable calibration	\$355
01528512	DicksonOne VFC-compliant freestanding display data logger with Wi-Fi and Ethernet capability for use with any refrigerator or freezer. NOTE: Subscription from Dickson required to access data on the cloud.	\$1,300
01528538	DicksonOne VFC-compliant freestanding touchscreen data logger with Power Over Ethernet and Wi-Fi capability for use with any refrigerator or freezer. NOTE: Subscription from Dickson required to access data on the cloud.	\$1,930
01539691	Ambient temperature and humidity sensor, right angle, for use with DicksonOne freestanding display and touchscreen data loggers	\$265
Item number	Description	Net price
EW12	Optional extended one year warranty on parts and labor only (available with new equipment only)	\$300
EW36	Optional extended three year warranty on parts and labor only (available with new equipment only)	\$600

Upright refrigerator and freezer accessories and warranties

Item number	Description	List price
01548791	Replacement CRS (Complete Refrigeration System) module, all Infinty Series refrigerator models (REF12i, REF20i, REF25i)	\$4,515
01312529	Replacement CRS (Complete Refrigeration System) module, REF12	\$2,865
01147891	Replacement high-side refrigeration module (complete condensing unit), REF45, REFVAC45	\$3,645
01550870	Replacement CRS (Complete Refrigeration System) module, all Infinty Series freezer models (FZR20i, FZR25i)	\$4,515
01007004	Replacement CRS (Complete Refrigeration System) module, FZR20/25	\$7,510
01059484	Additional shelf kit (includes 1 shelf and 4 screws), REF12i	\$210
01548809	Additional shelf kit (includes 1 shelf and 4 screws), REF20i, FZR20i	\$265
01548817	Additional shelf kit (includes 1 shelf and 4 screws), REF25i, FZR25i	\$265
01461268	Additional shelf (1), REFVAC20-LB, FZRVAC20-LB	\$210
01460708	Additional shelf (1), REFVAC25/45-LB, FZRVAC25-LB	\$210
01311976	Additional shelf (1), REF12-LB	\$210
00927251	Additional shelves (2), REF20-LB, FZR20-LB	\$400
00927269	Additional shelves (2), REF25/45-LB, FZR25-LB	\$400
01543925	Basket kit (includes 1 basket, 8 rollers, 4 screws and nuts and 2 slides), REF12i	\$420
01548825	Basket kit (includes 1 basket, 8 rollers, 8 screws and nuts and 2 slides), REF20i	\$420
01548833	Basket kit (includes 1 basket, 8 rollers, 8 screws and nuts and 2 slides), REF25i	\$420
01543933	Drawer kit (includes 1 drawer, 8 rollers, 4 screws and nuts and 2 slides), REF12i	\$440
01548841	Drawer kit (includes 1 drawer, 8 rollers, 8 screws and nuts and 2 slides), REF20i	\$440
01548858	Drawer kit (includes 1 drawer, 8 rollers, 8 screws and nuts and 2 slides), REF25i	\$440
01554492	Drawer kit (includes 1 drawer, 8 rollers, 8 screws and nuts and 2 slides), FZR20i	\$440
01554500	Drawer kit (includes 1 drawer, 8 rollers, 8 screws and nuts and 2 slides), FZR25i	\$440
00927202	Pyxis® compatible door bracket, REF20/25/45	\$450
00978296	medDISPENSE® compatible door bracket, REF20/25/45, FZR20/25	\$450
00966432	Omnicell® compatible door bracket, REF20/25/45	\$450
01319441	Wall bracket kit, seismic anchoring, REF12	\$345
01543883	Wall bracket kit, seismic anchoring, REF12i	\$335
00927194	Wall bracket kit, seismic anchoring, REF20i/25i, REF20/25/45, FZR20i/25i, FZR20/25	\$345
01140458	Replacement "quick-connect" RTD probe with certificate of NIST-traceable calibration, REF12, REF20/25, REFVAC20/25, REF45 and REFVAC45 before serial number Q86639, FZR20/25 and FZRVAC20/25	\$610
01540640	Replacement "quick connect" RTD probe with certificate of NIST-traceable calibration, REF12i/20i/25i, REF45, REFVAC45 after serial number Q86638, FZR20i/25i	\$610
01528512	DicksonOne VFC-compliant freestanding display data logger with Wi-Fi and Ethernet capability for use with any refrigerator or freezer. NOTE: Subscription from Dickson required to access data on the cloud.	\$1,300
01528538	DicksonOne VFC-compliant freestanding touchscreen data logger with Power Over Ethernet and Wi-Fi capability for use with any refrigerator or freezer. NOTE: Subscription from Dickson required to access data on the cloud.	\$1,930
01539691	Ambient temperature and humidity sensor, right angle, for use with DicksonOne freestanding display and touchscreen data loggers	\$265
Item number	Description	Net price
EW12	Optional extended one year warranty on parts and labor only, REF12 (available with new equipment only)	\$450
EW36	Optional extended three year warranty on parts and labor only, REF12 (available with new equipment only)	\$900
EW12	Optional extended one year warranty on parts and labor only, REF20/25 (available with new equipment only)	\$450
EW36	Optional extended three year warranty on parts and labor only, REF20/25 (available with new equipment only)	\$900
EW12	Optional extended one year warranty on parts and labor only, REF45 (available with new equipment only)	\$600
EW36	Optional extended three year warranty on parts and labor only, REF45 (available with new equipment only)	\$1,300
EW12	Optional extended one year warranty on parts and labor only, FZR20/FZR25 (available with new equipment only)	\$600
EW36	Optional extended three year warranty on parts and labor, FZR20/FZR25 (available with new equipment only)	\$1,200

Ice and water dispensers

Follett ice and water dispensers are chosen by more healthcare facilities than any other brand for good reason. We offer the industry's largest selection, with more than 30 sizes and configurations to meet the needs of virtually any application. Designed specifically for healthcare, Follett dispensers offer 12, 25, 50 or 90 lb of storage in attractive, space-saving cabinets, with customer-valued features, exceptional reliability, and after-the-sale service and support.

Warranty

Symphony Plus™ ice and water dispensers

Follett Products, LLC warrants to the original end user that all parts shall be free from defects in material and workmanship under normal use and service for a period of 3 years from the date of installation. Date of installation shall not exceed 90 days from date of shipment. Parts and labor for repair within this 3 year period are covered under this warranty. For products sold outside of the U.S. and Canada, the labor warranty will apply only to equipment sold and serviced through a Follett Authorized Distributor in its designated territory.

The compressor shall be covered for an additional 2 years (parts only), for a total of 5 years from the date of installation.

WARRANTY CONDITIONS

- Warranty labor must be performed by the local Follett authorized service provider
- The equipment has been installed and operated in compliance with instructions provided by Follett
- Customer has documented record of preventive maintenance and cleaning of the machine every 6 months according to the instructions in the dispenser Installation, Operations and Service Manual
- Malfunctions or damage due to alterations, improper operation, outdoor use, neglect, vandalism, fire, acts of God, or any situation beyond the control of Follett are expressly excluded from this warranty
- Follett reserves the right to require that any parts covered under this warranty be returned to Follett prepaid and verified as defective upon examination
- Any damages resulting from shipment of the unit are expressly excluded. Follett advises customers to carefully examine all shipments prior to acceptance and note all potential damage concerns on the appropriate shipping papers.
- Excess labor charges resulting from security clearance procedures, safety training, travel time greater than one hour or 50 miles (80 km), premium time labor; after hours, weekends, holidays, etc., will not be covered by Follett Products, LLC and are the responsibility of the equipment owner

This warranty is expressly made in lieu of other warranties, expressed or implied, including any implied warranty of merchantability or fitness for a particular purpose except as provided in the warranty with respect to defects in material and workmanship.

Follett Products, LLC will not be liable for any consequential damages, expenses, connecting or disconnecting charges, or any losses or damages resulting from a defect of the machine. Questions concerning this warranty should be directed to Follett Products, LLC, technical service at +1 (877) 612-5086 or +1 (610) 252-7301.

Symphony Plus ice and water dispensers – 12 series

Countertop and wall mount ice and water dispensers with 12 lb (5.4 kg) of storage. Integral ice machine produces up to 425 lb (193 kg) of ice per day. E12CI models are not for use in the United States.


All models feature stainless steel cabinet with accent trim. Water station included. Choose appropriate item number for SensorSAFE infrared dispensing or lever dispensing. Wall mount models only available with SensorSAFE infrared dispensing.

For additional product information, request form# 1070 for 12CI models, 1071 for 12HI models, or 1000 for E12CI models.


12 series accessories

4.00" (10.16 cm) leg kit for 12CI (item# AF10LBLEGS) **List price** \$300

See page 35 for additional accessory information.



Countertop with
integral ice machine



Wall mount with
integral ice machine
(SensorSAFE dispensing only)

Item number	Configuration	Dispense	Width in (cm)	Depth in (cm)	Height in (cm)	Condenser	Ice machine location	Voltage	Approx. ship wt lb (kg)	List price
12CI414 series ice and water dispensers										
12CI414A-S	Countertop	SensorSAFE	16.12 (40.9)	23.50 (59.7)	32.50 (82.6)	air-cooled	integral	115/60/1	199 (90)	\$12,315
12CI414A-L	Countertop	Lever	16.12 (40.9)	23.50 (59.7)	32.50 (59.7)	air-cooled	integral	115/60/1	199 (90)	\$12,315
12HI414A-S0-00	Wall mount ¹	SensorSAFE	16.12 (40.9)	23.50 (59.7)	32.50 (82.6)	air-cooled	integral	115/60/1	179 (81)	\$15,625
12HI414A-S0-DP	Wall mount ¹	SensorSAFE	16.12 (40.9)	23.50 (59.7)	32.50 (82.6)	air-cooled	integral	115/60/1	184 (84)	\$16,105
E12CI414 series ice and water dispensers										
E12CI414A-S ²	Countertop	SensorSAFE	16.12 (40.9)	23.50 (59.7)	32.50 (82.6)	air-cooled	integral	230/50/1 ²	199 (90)	\$12,540
E12CI414A-L ^{2,3}	Countertop	Lever	16.12 (40.9)	23.50 (59.7)	32.50 (82.6)	air-cooled	integral	230/50/1 ²	199 (90)	\$12,540

¹ 12HI425A-S0-DP wall mount unit configured with drain pan. 12HI425A-S0-00 wall mount unit configured without drain pan.

² Models not for use in the United States.

³ Model includes 4.00" (10.16 cm) legs and UK cord.

Symphony Plus ice-only dispensers – 12 series

Countertop ice dispensers with 12 lb (5.4 kg) of storage. Ice-only; no water. Integral ice machine produces up to 425 lb (193 kg) of ice per day. E12CI models are not for use in the United States.


All models feature stainless steel cabinet with accent trim. Choose appropriate item number for SensorSAFE infrared dispensing or lever dispensing.

For additional product information, request form# 1070 for 12CI models, 1071 for 12HI models, or 1000 for E12CI models.

12 series accessories

4.00" (10.16 cm) leg kit for 12CI (item# AF10LBLEGS) **List price** \$300

See page 35 for additional accessory information.




Countertop with
integral ice machine


Item number	Configuration	Dispense	Width in (cm)	Depth in (cm)	Height in (cm)	Condenser	Ice machine location	Voltage	Approx. ship wt lb (kg)	List price
12CI425 series ice-only dispensers										
12CI414A-SI	Countertop	SensorSAFE	16.12 (40.9)	23.50 (59.7)	32.50 (82.6)	air-cooled	integral	115/60/1	199 (90)	\$12,315
12CI414A-LI	Countertop	Lever	16.12 (40.9)	23.50 (59.7)	32.50 (82.6)	air-cooled	integral	115/60/1	199 (90)	\$12,315
E12CI414 series ice-only dispensers										
E12CI414A-SI ¹	Countertop	SensorSAFE	16.12 (40.9)	23.50 (59.7)	32.50 (82.6)	air-cooled	integral	230/50/1 ¹	199 (90)	\$12,540
E12CI414A-LI ¹	Countertop	Lever	16.12 (40.9)	23.50 (59.7)	32.50 (82.6)	air-cooled	integral	230/50/1 ¹	199 (90)	\$12,540

¹ Models not for use in the United States.


Symphony Plus ice and water dispensers – 25 and 50 series



Countertop with
removable ice machine
behind splash panel



Wall mount with
removable ice machine
behind splash panel



Freestanding with
removable ice machine
in base

Countertop, freestanding and wall mount ice and water dispensers with 25 lb (11.3 kg) or 50 lb (22.7 kg) of storage. Removable icemaking module produces up to 425 lb (193.0 kg) of ice per day. Stainless steel cabinet with accent trim. Water station included. Choose appropriate item number for SensorSAFE infrared dispensing or lever dispensing. Wall mount models only available with SensorSAFE infrared dispensing.

For additional product information, request form# 1072 for 25CI and 50CI models, 1073 for 25HI models, or 1074 for 25FB and 50FB models.

25 and 50 series accessories**List price**

4.00" (10.16 cm) leg kit for 25CI and 50CI (item# 00188417) \$310

Caster kit for 25FB and 50FB (item# AFCASTERKIT) \$675

See page 35 for additional accessory information.

Item number	Configuration	Dispense	Width in (cm)	Depth in (cm)	Height in (cm)	Condenser	Ice machine location	Voltage	Approx. ship wt lb (kg)	List price
25 series ice and water dispensers										
25CI414A-S	Countertop	SensorSAFE	21.00 (53.3)	24.00 (61.0)	36.00 (91.4)	air-cooled	behind splash panel	115/60/1	240 (109)	\$16,985
25CI414A-L	Countertop	Lever	21.00 (53.3)	24.00 (61.0)	36.00 (91.4)	air-cooled	behind splash panel	115/60/1	240 (109)	\$16,985
25CI414W-S	Countertop	SensorSAFE	21.00 (53.3)	24.00 (61.0)	36.00 (91.4)	water-cooled	behind splash panel	115/60/1	240 (109)	\$16,985
25CI414W-L	Countertop	Lever	21.00 (53.3)	24.00 (61.0)	36.00 (91.4)	water-cooled	behind splash panel	115/60/1	240 (109)	\$16,985
25HI414A-S0-00	Wall mount ¹	SensorSAFE	21.50 (54.6)	24.50 (62.2)	36.50 (92.7)	air-cooled	behind splash panel	115/60/1	230 (104)	\$19,850
25HI414A-S0-DP	Wall mount ¹	SensorSAFE	21.50 (54.6)	24.50 (62.2)	36.50 (92.7)	air-cooled	behind splash panel	115/60/1	235 (107)	\$20,950
25FB414A-S	Freestanding ²	SensorSAFE	21.00 (53.3)	24.75 (62.9)	62.88 (159.7)	air-cooled	base mounted	115/60/1	250 (113)	\$18,610
25FB414A-L	Freestanding ²	Lever	21.00 (53.3)	24.75 (62.9)	62.88 (159.7)	air-cooled	base mounted	115/60/1	250 (113)	\$18,610
25FB414W-S	Freestanding ²	SensorSAFE	21.00 (53.3)	24.75 (62.9)	62.88 (159.7)	water-cooled	base mounted	115/60/1	250 (113)	\$18,610
25FB414W-L	Freestanding ²	Lever	21.00 (53.3)	24.75 (62.9)	62.88 (159.7)	water-cooled	base mounted	115/60/1	250 (113)	\$18,610
50 series ice and water dispensers										
50CI414A-S	Countertop	SensorSAFE	21.00 (53.3)	24.00 (61.0)	40.00 (101.6)	air-cooled	behind splash panel	115/60/1	245 (111)	\$18,220
50CI414A-L	Countertop	Lever	21.00 (53.3)	24.00 (61.0)	40.00 (101.6)	air-cooled	behind splash panel	115/60/1	245 (111)	\$18,220
50CI414W-S	Countertop	SensorSAFE	21.00 (53.3)	24.00 (61.0)	40.00 (101.6)	water-cooled	behind splash panel	115/60/1	245 (111)	\$18,220
50CI414W-L	Countertop	Lever	21.00 (53.3)	24.00 (61.0)	40.00 (101.6)	water-cooled	behind splash panel	115/60/1	245 (111)	\$18,220
50FB414A-S	Freestanding ²	SensorSAFE	21.00 (53.3)	24.75 (62.9)	66.88 (169.9)	air-cooled	base mounted	115/60/1	253 (115)	\$20,010
50FB414A-L	Freestanding ²	Lever	21.00 (53.3)	24.75 (62.9)	66.88 (169.9)	air-cooled	base mounted	115/60/1	253 (115)	\$20,010
50FB414W-S	Freestanding ²	SensorSAFE	21.00 (53.3)	24.75 (62.9)	66.88 (169.9)	water-cooled	base mounted	115/60/1	253 (115)	\$20,010
50FB414W-L	Freestanding ²	Lever	21.00 (53.3)	24.75 (62.9)	66.88 (169.9)	water-cooled	base mounted	115/60/1	253 (115)	\$20,010

¹ 25HI414A-S0-DP wall mount units configured with drain pan. 25HI414A-S0-00 wall mount units configured without drain pan.

² Freestanding models include 6.00" (15.24 cm) adjustable legs.

Symphony Plus series ice-only dispensers – 25 and 50 series

Countertop and wall mount ice dispensers with 25 lb (11.3 kg) or 50 lb (22.7 kg) of storage. Removable icemaking module produces up to 425 lb (193.0 kg) of ice per day. Stainless steel cabinet with accent trim. Choose appropriate item number for SensorSAFE infrared dispensing or lever dispensing.


For additional product information, request form# 1072 for 25CI and 50CI models or 1073 for 25HI models.

25 and 50 series accessories


4.00" (10.16 cm) leg kit for 25CI and 50CI (item# 00188417) \$310

List price

See page 35 for additional accessory information.



Countertop with
integral ice machine



Wall mount with
integral ice machine
(SensorSAFE dispensing only)

Item number	Configuration	Dispense	Width in (cm)	Depth in (cm)	Height in (cm)	Condenser	Ice machine location	Voltage	Approx. ship wt lb (kg)	List price
25 series ice-only dispensers										
25CI414A-SI	Countertop	SensorSAFE	21.00 (53.3)	24.00 (61.0)	36.00 (91.4)	air-cooled	behind splash panel	115/60/1	240 (109)	\$16,985
25CI414A-LI	Countertop	Lever	21.00 (53.3)	24.00 (61.0)	36.00 (91.4)	air-cooled	behind splash panel	115/60/1	240 (109)	\$16,985
25CI414W-SI	Countertop	SensorSAFE	21.00 (53.3)	24.00 (61.0)	36.00 (91.4)	water-cooled	behind splash panel	115/60/1	240 (109)	\$16,985
25CI414W-LI	Countertop	Lever	21.00 (53.3)	24.00 (61.0)	36.00 (91.4)	water-cooled	behind splash panel	115/60/1	240 (109)	\$16,985
25HI414A-SI-00	Wall mount ¹	SensorSAFE	21.50 (54.6)	24.50 (62.2)	36.50 (92.7)	air-cooled	behind splash panel	115/60/1	230 (104)	\$19,850
25HI414A-SI-DP	Wall mount ¹	SensorSAFE	21.50 (54.6)	24.50 (62.2)	36.50 (92.7)	air-cooled	behind splash panel	115/60/1	235 (107)	\$20,950
50 series ice-only dispensers										
50CI414A-SI	Countertop	SensorSAFE	21.00 (53.3)	24.00 (61.0)	40.00 (101.6)	air-cooled	behind splash panel	115/60/1	245 (111)	\$18,220
50CI414A-LI	Countertop	Lever	21.00 (53.3)	24.00 (61.0)	40.00 (101.6)	air-cooled	behind splash panel	115/60/1	245 (111)	\$18,220
50CI414W-SI	Countertop	SensorSAFE	21.00 (53.3)	24.00 (61.0)	40.00 (101.6)	water-cooled	behind splash panel	115/60/1	245 (111)	\$18,220
50CI414W-LI	Countertop	Lever	21.00 (53.3)	24.00 (61.0)	40.00 (101.6)	water-cooled	behind splash panel	115/60/1	245 (111)	\$18,220

¹ 25HI414A-SI-DP wall mount units configured with drain pan and 25HI414A-SI-00 wall mount units configured without drain pan.

Symphony Plus ice and water dispensers – 110 series

Freestanding ice and water dispensers with 90 lb (40.8 kg) of storage. Removable icemaking module produces up to 425 lb (193.0 kg) of ice per day. Stainless steel cabinet with accent trim. Water station and 6.00" (15.24 cm) adjustable legs included. Choose appropriate item number for SensorSAFE infrared dispensing or lever dispensing.


For additional product information, request form# 1075.

110 series accessories

Caster kit for 110FB (item# AFCASTERKIT)..... \$675

List price

See page 35 for additional accessory information.



Freestanding with removable
ice machine in base

Item number	Configuration	Dispense	Width in (cm)	Depth in (cm)	Height in (cm)	Condenser	Ice machine location	Voltage	Approx. ship wt lb (kg)	List price
110 series ice and water dispensers										
110FB414A-S	Freestanding	SensorSAFE	25.00 (63.5)	28.25 (71.8)	68.12 (173.0)	air-cooled	base mounted	115/60/1	285 (129)	\$29,115
110FB414A-L	Freestanding	Lever	25.00 (63.5)	28.25 (71.8)	68.12 (173.0)	air-cooled	base mounted	115/60/1	285 (129)	\$29,115
110FB414W-S	Freestanding	SensorSAFE	25.00 (63.5)	28.25 (71.8)	68.12 (173.0)	water-cooled	base mounted	115/60/1	285 (129)	\$29,115
110FB414W-L	Freestanding	Lever	25.00 (63.5)	28.25 (71.8)	68.12 (173.0)	water-cooled	base mounted	115/60/1	285 (129)	\$29,115

Symphony Plus ice-only dispensers – 110 series

Freestanding ice dispensers with 90 lb (40.8 kg) of storage. Removable icemaking module produces up to 425 lb (193.0 kg) of ice per day. Stainless steel cabinet with accent trim. Water station not included. 6.00" (15.24 cm) adjustable legs included. Choose appropriate item number for SensorSAFE infrared dispensing or lever dispensing.


For additional product information, request form# 1075.

110 series accessories

List price

Caster kit for 110FB (item# AFCASTERKIT)..... \$675

See page 35 for additional accessory information.




Freestanding with removable ice machine in base

Item number	Configuration	Dispense	Width in (cm)	Depth in (cm)	Height in (cm)	Condenser	Ice machine location	Voltage	Approx. ship wt lb (kg)	List price
110 series ice-only dispensers										
110FB414A-SI	Freestanding	SensorSAFE	25.00 (63.5)	28.25 (71.8)	68.12 (173.0)	air-cooled	base mounted	115/60/1	285 (129)	\$29,115
110FB414A-LI	Freestanding	lever	25.00 (63.5)	28.25 (71.8)	68.12 (173.0)	air-cooled	base mounted	115/60/1	285 (129)	\$29,115


Symphony Plus base stand options

Stainless steel base stand transforms Follett® countertop dispensers into freestanding dispensers. All bases include stainless steel exterior, and stainless legs with 6.00" (15.24 cm) adjustable flanged feet. Available with or without factory installed water filter system.

For additional product information, request form# 7010.



12 Series



25 and 50 Series

Item number	Description	Approx. ship wt lb (kg)	List price
12BASE-00	Base for 12 CI Series, 17.50" (44.4 cm) W x 22.00" (55.9 cm) D x 33.00" (83.8 cm) H	74 (34)	\$2,045
12BASE-CF	12BASE-00 with standard capacity carbon filter system (CARBONSTDCAPSYSTEM) installed	86 (39)	\$3,275
12BASE-HC	12BASE-00 with high capacity carbon filter system (CARBONHICAPSYSTEM) installed	86 (39)	\$3,510
12BASE-CL	12BASE-00 with carbonless high capacity filter system (CARBONLESSHICAPSYS) installed	86 (39)	\$3,360
25AND50BASE-00	Base for 25 and 50 CI series, 22.75" (57.8 cm) W x 24.38" (61.9 cm) D x 33.00"	78 (35)	\$2,125
25AND50BASE-CF	25AND50BASE-00 with standard capacity carbon filter system (CARBONSTDCAPSYSTEM) installed	95 (43)	\$3,360
25AND50BASE-HC	25AND50BASE-00 with high capacity carbon filter system (CARBONHICAPSYSTEM) installed	95 (43)	\$3,615
25AND50BASE-CL	25AND50BASE-00 with carbonless high capacity filter system (CARBONLESSHICAPSYS) installed	95 (43)	\$3,455

Ice and water dispenser accessories

Water treatment accessories for Symphony Plus ice and water dispensers

Item number	Description	List price
Follett bacterial-retentive filter system		
01233659	Bacterial-retentive filter system	\$1,180
01244615	Replacement filter kit for bacterial-retentive filter system	\$490
01233717	1 micron absolute rated pre-filter cartridge	\$115
01288034	Scale inhibitor pre-filter kit for bacterial-retentive filter system	\$410
01288042	Carbon with scale inhibitor pre-filter kit for bacterial-retentive filter system	\$410
01288067	Replacement filter for scale inhibitor pre-filter kit	\$165
01288059	Replacement filter for carbon and scale inhibitor pre-filter kit	\$165
Carbonless high capacity filter system		
CARBONLESSHICAPSYS	Carbonless high capacity water filter system (one per ice machine), filtration capacity based on water conditions	\$1,190
CARBONLESSHICAPFLT	Carbonless high capacity water filter cartridge – primary, single	\$285
CARBONLESSHICAPFLT6	Carbonless high capacity water filter cartridge – primary, carton of 6	\$1,375
SEDIMENTPREFILTER	Water pre-filter cartridge – pre-filter, single	\$105
SEDIMENTPREFILTER12	Water pre-filter cartridge – pre-filter, carton of 12	\$400
Standard capacity carbon filter system		
CARBONSTDCAPSYSTEM	Carbon standard capacity water filter system (one per ice machine), filtration capacity 5,000 gal (18,927 l)	\$1,115
CARBONSTDCAPFILTER	Water filter cartridge – primary, single	\$255
CARBONSTDCAPFILTER6	Water filter cartridge – primary, carton of 6	\$1,170
SEDIMENTPREFILTER	Water pre-filter cartridge – pre-filter, single	\$105
SEDIMENTPREFILTER12	Water pre-filter cartridge – pre-filter, carton of 12	\$400
High capacity carbon filter system		
CARBONHICAPSYSTEM	Carbon high capacity water filter system (one per ice machine), filtration capacity 17,500 gal (66,245 l)	\$1,330
CARBONHICAPFILTER	High capacity water filter cartridge – primary, single	\$460
CARBONHICAPFILTER6	High capacity water filter cartridge – primary, carton of 6	\$2,255
SEDIMENTPREFILTER	Water pre-filter cartridge – pre-filter, single	\$105
SEDIMENTPREFILTER12	Water pre-filter cartridge – pre-filter, carton of 12	\$400

Cleaning and sanitizing accessories for Symphony Plus ice and water dispensers

Item number	Description	List price
01563360	Pressurized water sanitizing kit for use with Follett dispensers that have a Follett water filtration system (includes dip tube and bypass plug). Applicable Follett water filter systems include CARBONSTDCAPSYSTEM, CARBONHICAPSYSTEM, CARBONLESSHICAPSYS.	\$130
01089580	Pressurized water sanitizing kit for use with Follett dispensers that do not have a Follett water filtration system (includes filter housing, dip tube and bypass plug)	\$260
01147826	SafeCLEAN Plus™, liquid – environmentally responsible ice machine cleaner (1 x 8 oz bottle)	\$75
01149954	SafeCLEAN Plus, liquid – environmentally responsible ice machine cleaner (6 x 8 oz bottles)	\$185
01149962	SafeCLEAN Plus, liquid – environmentally responsible ice machine cleaner (carton of 24 x 8 oz bottles)	\$550
01555077	SafeCLEAN Plus, liquid – environmentally responsible ice machine cleaner (carton of 4 x 1 gal bottles)	\$870
00979674	Nu-Calgon® IMS-III sanitizer, single 16 oz bottle (US only)	\$75
01038652	Nu-Calgon IMS-III sanitizer, case of 12 x 16 oz bottles (US only)	\$410
01075431	SaniSponge™, 24 pack of sanitary sponges	\$130

Other accessories for Symphony Plus ice and water dispensers

Item number	Description	List price
01049790	Symphony Plus external drain kit (includes 10 ft (3 m) clear tubing and fitting)	\$140
AFCONDUMP	Condensate pump	\$615

Replacement ice machine for use in Symphony Plus 414 model dispensers

The ice machine module can be swapped out between 25, 50 and 110 Series Symphony Plus 414 dispensers or replaced with a new module for faster, easier service, providing more up-time.

Note: Replacement ice machines are not compatible with Symphony 400 and Symphony Plus 425 dispensers.

Item number	Width in (cm)	Depth in (cm)	Height in (cm)	Production per 24 hr lb (kg)	Condenser	Voltage	Ship wt lb (kg)	List price
P414A	15.30 (38.9)	19.90 (50.5)	16.80 (42.7)	425 (193)	air-cooled	115/60/1	117 (53)	\$11,300
P414W	15.30 (38.9)	19.90 (50.5)	16.80 (42.7)	425 (193)	water-cooled	115/60/1	122 (55)	\$11,300

Ice machines

Compact, reliable Chewblet® extruded ice and flake ice machines in a variety of sizes to meet your needs. Choose from top mount or RIDE model configurations (extruded only).

Warranty

Maestro Plus™ and Horizon Elite™ series ice machines and remote condensing units

Follett Products, LLC warrants to the original end user that all parts shall be free from defects in material and workmanship under normal use and service for a period of 3 years from the date of installation. Date of installation shall not exceed 90 days from date of shipment. Parts and labor for repair within this 3 year period are covered under this warranty. For products sold outside of the U.S. and Canada, the labor warranty will apply only to equipment sold and serviced through a Follett Authorized Distributor in its designated territory.

The compressor shall be covered for an additional 2 years (parts only), for a total of 5 years from the date of installation.

WARRANTY CONDITIONS

- Warranty labor must be performed by the local Follett authorized service provider
- The equipment has been installed and operated in compliance with instructions provided by Follett
- Customer has documented record of preventive maintenance and cleaning of the machine every 6 months according to the instructions in the dispenser Installation, Operations and Service Manual
- Malfunctions or damage due to alterations, improper operation, outdoor use, neglect, vandalism, fire, acts of God, or any situation beyond the control of Follett are expressly excluded from this warranty
- Follett reserves the right to require that any parts covered under this warranty be returned to Follett prepaid and verified as defective upon examination
- Any damages resulting from shipment of the unit are expressly excluded. Follett advises customers to carefully examine all shipments prior to acceptance and note all potential damage concerns on the appropriate shipping papers.
- Excess labor charges resulting from security clearance procedures, safety training, travel time greater than one hour or 50 miles (80 km), premium time labor; after hours, weekends, holidays, etc., will not be covered by Follett Products, LLC and are the responsibility of the equipment owner

This warranty is expressly made in lieu of other warranties, expressed or implied, including any implied warranty of merchantability or fitness for a particular purpose except as provided in the warranty with respect to defects in material and workmanship.

Follett Products, LLC will not be liable for any consequential damages, expenses, connecting or disconnecting charges, or any losses or damages resulting from a defect of the machine. Questions concerning this warranty should be directed to Follett Products, LLC, technical service at +1 (877) 612-5086 or +1 (610) 252-7301.


Maestro Plus Chewblet and flake ice machine bins – 400 series

Flake (UF) or Chewblet® (UM) ice machines with 75 lb (34 kg) of bin storage for undercounter or freestanding applications.

Stainless steel exterior with moderate production and storage capacity in a small footprint.

For additional product information, request form# 1009.

See page 44 for additional accessory information.



undercounter ice machine bin

Item number		Width in (cm)	Depth in (cm)	Height ² in (cm)	Production capacity lb (kg)		Condensing unit	Voltage	Approx. ship wt lb (kg)	List price
					90 F air 70 F water (32/21 C)	70 F air 50 F water (21/10 C)				
UMD414A80 [†]	Chewblet	23.50 (59.7)	26.00 (66.0)	33.00 (83.8)	325 (148)	425 (193)	air-cooled, self-contained	115/60/1	194 (88)	\$13,935
UME414A80 [†]	Chewblet	23.50 (59.7)	26.00 (66.0)	33.00 (83.8)	325 (148)	425 (193)	air-cooled, self-contained	230/50/1 [†]	194 (88)	\$14,170
UFD414A80 [†]	Flake	23.50 (59.7)	26.00 (66.0)	33.00 (83.8)	325 (148)	425 (193)	air-cooled, self-contained	115/60/1	194 (88)	\$13,935
UFE414A80 [†]	Flake	23.50 (59.7)	26.00 (66.0)	33.00 (83.8)	325 (148)	425 (193)	air-cooled, self-contained	230/50/1 [†]	194 (88)	\$14,170

[†] ENERGY STAR® certified.

[†] Models not for use in the United States.

² 33.00" (83.8 cm) with leveling feet for undercounter use. 39.00" (99.1 cm) with bullet legs for freestanding application.


Maestro Plus Chewblet and flake ice machines – 400 series

Chewblet and flake air-cooled ice machines for top mount and RIDE (ice-through-a-tube) configurations.


E414A models are not for use in the United States.

For additional product information, request form# 1067 for top mount configurations and form 1069 for RIDE configurations.

See page 44 for additional accessory information.



Top mount



RIDE

Item number	Ice type	Width in (cm)	Depth in (cm)	Height in (cm)	Production capacity lb (kg)		Condensing unit	Voltage	Approx. ship wt lb (kg)	List price
					90 F air 70 F water (32/21 C)	70 F air 50 F water (21/10 C)				
414 series top mount configurations										
D414AT	Chewblet	22.70 (57.7)	24.25 (61.6)	21.25 (54.0)	340 (154)	423 (192)	air-cooled, self-contained	115/60/1	170 (77)	\$11,705
E414AT	Chewblet	22.70 (57.7)	24.25 (61.6)	21.25 (54.0)	325 (147)	425 (193)	air-cooled, self-contained	230/50/1 ¹	170 (77)	\$11,925
D414ATF	Flake	22.70 (57.7)	24.25 (61.6)	21.25 (54.0)	340 (154)	423 (192)	air-cooled, self-contained	115/60/1	170 (77)	\$11,705
E414ATF	Flake	22.70 (57.7)	24.25 (61.6)	21.25 (54.0)	325 (147)	425 (193)	air-cooled, self-contained	230/50/1 ¹	170 (77)	\$11,925

414 series RIDE configurations

D414AS	Chewblet	18.80 (47.8)	22.75 (57.8)	17.10 (43.4)	340 (154)	423 (192)	air-cooled, self-contained	115/60/1	127 (57)	\$11,950
E414AS	Chewblet	18.80 (47.8)	22.75 (57.8)	17.10 (43.4)	325 (147)	425 (193)	air-cooled, self-contained	230/50/1 [†]	127 (57)	\$12,175

[†] Models not for use in the United States. Model ships EXW Incoterms 2010 – Wislina, Poland.

Maestro Plus 414 RIDE installation kits (required)

Item number	Description	List price
-------------	-------------	------------

Countertop ice and beverage dispenser and ice storage bin installations

Top mount ice machine **requires stainless steel top kit**, sold separately. See top kit charts on page 39 for top kit numbers.

RIDE ice machines include 20' (6.1 m) of insulated ice transport tube and universal RIDE model adapter kit (item# 01054444). Factory approval required for ice transport tube lengths over 20' (6.1 m). See below for approved dispensers. All dispensers must be configured for nugget ice. See dispenser manufacturer for appropriate nugget ice kits, if required.

Refer to page 45 for available ice storage bin capacities and sizes.

01558824	Installation kit for Maestro Plus ice machines filling countertop ice and beverage dispensers and ice storage bins. Includes 20' (6 m) of ice transport tube.	\$645
----------	---	-------

Approved for RIDE model – ice and beverage dispensers manufactured by others¹

Coca-Cola Freestyle 7000 ^{2,4} / 7100 ^{3,4} / 9000 ⁴ / 9100 ⁴	Lancer 4500-22N	Servend MD175
Cornelius DB/DF/ED150BC Series	Lancer 4500-30N	Servend MD200
Cornelius DB/DF/ED175BC Series	Lancer FS-16N	Servend MD250
Cornelius DB/DF/ED200BC Series	Lancer FS-22N	Servend MDH302
Cornelius DB/DF/ED250BC Series	Lancer FS-30N	Servend MDH402
Cornelius DB/DF/ED300BC Series	Lancer FS-44N	Servend SV175
Cornelius IDC215/255 and Pro Fast Gate	Lancer Sensation and TouchPoint	Servend SV200
Cornelius IDC Pro	Pepsi Spire 3.0 ⁵ / 5.0 ⁵ / 4.1 ⁵	Servend SV250
Cornelius Flavor Fusion/Overload	Servend MD150	

Maestro Plus 414AT top kits for top mount applications used with countertop ice and beverage dispensers

For additional Maestro Plus product information, request form# 1067.

Top kit accessory item number	Dispenser manufacturer	Dispenser model number	Dispenser series width	List price
-------------------------------	------------------------	------------------------	------------------------	------------

Maestro Plus top mount applications¹				
MTF24SCP ^{4,6}	Coca-Cola	Freestyle 9000	24"	\$1,010
MTF26SCP ⁴	Coca-Cola	Freestyle 9100	26"	\$1,010
MTF30SCP ^{4,7}	Coca-Cola	Freestyle 7000	30"	\$1,225
MTF30SCP ^{4,8}	Coca-Cola	Freestyle 7100	30"	\$1,225
MTC22SCP	Cornelius	DB/DF/ED150BC	22"	\$1,005
MTC24SCP	Cornelius	DB/DF/ED175BC	24"	\$1,005
MTC30SCP	Cornelius	DB/DF/ED200/250	30"	\$1,225
MTC30SCP	Cornelius	IDC215/255	30"	\$1,225
MTL22SCP	Lancer	FS-22N/4500-22N	22"	\$995
MTL30SCP	Lancer	4500-30N	30"	\$1,225
MTL30SCP-STP	Lancer	Sensation/TouchPoint/Bold 30i	30"	\$1,225
MTL30SCP-STP	Lancer	Bold 30i	30"	\$1,225
MTP24SCP	Pepsi	Spire 3.0	24"	\$1,005
MTP30SCP	Pepsi	Spire 5.0 / 4.1	30"	\$1,225

¹ All dispensers must be configured for nugget ice. See dispenser manufacturer for appropriate nugget ice kits, if required. Approved dispensers for top mount ice machine applications are listed above.

² Top kit MSF30SC required with Coca-Cola Freestyle 7000. Top adapter IC Code 46412 and ice kit IC Code 46430 must also be ordered from Coca-Cola.

³ Top kit MSF30SC required with Coca-Cola Freestyle 7100. Top adapter IC Code 46751 and ice kit IC Code 46430 must also be ordered from Coca-Cola.

⁴ Consult with Coca-Cola and Follett to qualify application prior to ordering.

⁵ RIDE application is approved only for Pepsi Spire 3.0, 5.0 and 4.1 designed for top mount ice machines and requires MSP24SC for 3.0 and MSP30SC for 5.0 and 4.1, ordered separately. For manual fill versions of Pepsi Spire 3.0, 5.0 and 4.1, contact factory.

⁶ Adapter must also be ordered from Coca-Cola. IC Code: 46010 (Silver), 46011 (Red) or 46012 (Black).

⁷ Top adapter IC Code 46412 and ice kit IC Code 46430 must also be ordered from Coca-Cola.

⁸ Top adapter IC Code 46753 and ice kit IC Code 46430 must also be ordered from Coca-Cola.

Maestro Plus 414AS top kits for RIDE applications used with countertop ice and beverage dispensers

Top kit accessory item number	Dispenser manufacturer	Dispenser model number	Dispenser series width	List price
Required Maestro Plus RIDE application stainless steel adapter kits¹				
MSF30SC ^{2,4}	Coca-Cola	Freestyle 7000	30"	\$600
MSF26SC ⁴	Coca-Cola	Freestyle 9100	26"	\$570
MSP24SC ⁵	Pepsi	Spire 3.0	24"	\$570
MSP30SC ⁵	Pepsi	Spire 5.0 / 4.1	30"	\$600
Optional Maestro Plus RIDE application stainless steel adapter kits¹				
MSC22SC	Cornelius	DB/DF/ED150BC	22"	\$2,430
MSC24SC	Cornelius	DB/DF/ED175BC	24"	\$2,540
MSC30SC	Cornelius	DB/DF/ED200BC	30"	\$2,655
MSC30SC	Cornelius	DB/DF/ED250BC	30"	\$2,655
MSC44SC	Cornelius	DB/DF/ED300BC	44"	\$2,710
MSL22SC	Lancer	FS-22N	22"	\$2,430
MSL30SC	Lancer	4500-30N	30"	\$2,655
MSL30SC	Lancer	FS-30N	30"	\$2,655

¹ All dispensers must be configured for nugget ice. See dispenser manufacturer for appropriate nugget ice kits, if required. Approved dispensers for top mount ice machine applications are listed above.

² Top kit MSF30SC required with Coca-Cola Freestyle 7000. Top adapter IC Code 46412 and ice kit IC Code 46430 must also be ordered from Coca-Cola.

³ Top kit MSF30SC required with Coca-Cola Freestyle 7100. Top adapter IC Code 46751 and ice kit IC Code 46430 must also be ordered from Coca-Cola.

⁴ Consult with Coca-Cola and Follett to qualify application prior to ordering.

⁵ RIDE application is approved only for Pepsi Spire 3.0, 5.0 and 4.1 designed for top mount ice machines and requires MSP24SC for 3.0 and MSP30SC for 5.0 and 4.1, ordered separately. For manual fill versions of Pepsi Spire 3.0, 5.0 and 4.1, contact factory.

⁶ Adapter must also be ordered from Coca-Cola. IC Code: 46010 (Silver), 46011 (Red) or 46012 (Black).

⁷ Top adapter IC Code 46412 and ice kit IC Code 46430 must also be ordered from Coca-Cola.


⁸ Top adapter IC Code 46753 and ice kit IC Code 46430 must also be ordered from Coca-Cola.

Horizon Elite Chewblet ice machines – 710 series

Ice machines for top mount and RIDE (ice-through-a-tube) configurations.

For additional product information, request form# 1061.

See page 44 for additional accessory information.



Top mount or RIDE

Item number	Width in (cm)	Depth in (cm)	Height in (cm)	Production capacity lb (kg)		Condensing unit	Voltage	Approx. ship wt lb (kg)	List price
				90 F air 70 F water (32/21 C)	70 F air 50 F water (21/10 C)				
710 series ice machines									
D710A [†]	22.70 (57.7)	24.50 (62.2)	21.25 (54.0)	586 (266)	759 (345)	air-cooled, self-contained	115/60/1	190 (86)	\$15,390
E710A [†]	22.70 (57.7)	24.50 (62.2)	21.25 (54.0)	586 (266)	759 (345)	air-cooled, self-contained	230/50/1 ¹	190 (86)	\$15,605

[†] ENERGY STAR[®] certified.

[†] Models not for use in the United States.

Horizon Elite installation kits – 710 series (required)

Item number	Description	List price
Ice storage bin installations		
Refer to form# 8590 for available capacities and sizes.		
01564590	Installation kit for Horizon Elite ice machines filling bins	\$645
Countertop ice and beverage dispenser installations		
Top mount ice machine applications require stainless steel top kit, sold separately. See top kits on page 42.		
RIDE ice machine applications do not require stainless steel top except Coca Cola Freestyle and Pepsi Spire 3.0 and 5.0. See page 42 for approved dispensers and Coca Cola and Pepsi Spire 3.0 and 5.0 top kits.		
All dispensers must be configured for nugget ice. See dispenser manufacturer for appropriate nugget ice kits, if required.		
01564582	Installation kit for Horizon Elite ice machines filling countertop ice and beverage dispensers	\$645
Ventilation kit		
Required for self-contained air-cooled ice machines (710A) installed under counters.		
01564624	Ventilation kit required for Horizon Elite air-cooled (A) ice machines installed under a counter (includes grilles and gasket)	\$645

Horizon Elite ice transport tube kits for RIDE installations – 710 series (required)

Item number	Description	List price
For bins, countertop ice and beverage dispensers and drop-in dispensers		
01560549	Ice transport tube kit for RIDE installations except Vision dispensers, 10' (3 m)	\$755
01560556	Ice transport tube kit for RIDE installations except Vision dispensers, 35' (10.7 m)	\$2,635
01560564	Ice transport tube kit for RIDE installations except Vision dispensers, 80' (24.4 m)	\$6,020

Approved for RIDE model – ice and beverage dispensers manufactured by others¹

Coca-Cola Freestyle 7000 ² / 7100 ^{2,3} / 9000 ² / 9100 ²	Follett Symphony Plus™ 110CM	Pepsi Spire 3.0 ⁴ / 5.0 ⁴ / 4.1 ⁴	Servend SV250
Cornelius DB/DF/ED150BC Series	Lancer 4500-22N	Servend MD150	
Cornelius DB/DF/ED175BC Series	Lancer 4500-30N	Servend MD175	
Cornelius DB/DF/ED200BC Series	Lancer FS-16N	Servend MD200	
Cornelius DB/DF/ED250BC Series	Lancer FS-22N	Servend MD250	
Cornelius DB/DF/ED300BC Series	Lancer FS-30N	Servend MDH302	
Cornelius IDC215/255 and Pro Fast Gate	Lancer FS-44N	Servend MDH402	
Cornelius IDC Pro	Lancer Sensation/TouchPoint	Servend SV175	
Cornelius Flavor Fusion/Overload	Lancer Bevariety	Servend SV200	

¹ All dispensers must be configured for nugget ice. See dispenser manufacturer for appropriate nugget ice kits, if required. See table below for table of approved dispensers for top mount ice machines.

² Consult with Coca-Cola and Follett to qualify application prior to ordering.

³ Top kit MSF30SC required with Coca-Cola Freestyle 7100. Top adapter IC Code 46751 and ice kit IC Code 46430 must also be ordered from Coca-Cola.

⁴ RIDE application is approved only for Pepsi Spire 3.0, 5.0 and 4.1 designed for top mount ice machines and requires MSP24SC for 3.0 and MSP30SC for 5.0 and 4.1, ordered separately. For manual fill versions of Pepsi Spire 3.0, 5.0 and 4.1, contact factory.

Horizon Elite top kits for RIDE applications used with countertop ice and beverage dispensers

Top kit accessory item number	Dispenser	Dispenser model number	Dispenser series width	List price
Required Horizon Elite RIDE application stainless steel adapter kits¹				
HSF26SC ²	Coca-Cola	Freestyle 9100	26"	\$600
MSP24SC ³	Pepsi	Spire 3.0	24"	\$570
MSP30SC ³	Pepsi	Spire 5.0	30"	\$600

¹ All dispensers must be configured for nugget ice. See dispenser manufacturer for appropriate nugget ice kits, if required. See table below for table of approved dispensers for top mount ice machines.

² Consult with Coca-Cola and Follett to qualify application prior to ordering.

³ RIDE application is approved only for Pepsi Spire 3.0, 5.0 and 4.1 designed for top mount ice machines and requires MSP24SC for 3.0 and MSP30SC for 5.0 and 4.1, ordered separately. For manual fill versions of Pepsi Spire 3.0, 5.0 and 4.1, contact factory.

Top kit accessory item number	Dispenser manufacturer	Dispenser model number	Dispenser series width	List price
Optional Horizon Elite RIDE application stainless steel adapter kits¹				
MSC22SC	Cornelius	DB/DF/ED150BC	22"	\$2,430
MSC24SC	Cornelius	DB/DF/ED175BC	24"	\$2,540
MSC30SC	Cornelius	DB/DF/ED200BC	30"	\$2,655
MSC30SC	Cornelius	DB/DF/ED250BC	30"	\$2,655
MSC44SC	Cornelius	DB/DF/ED300BC	44"	\$2,710
MSL22SC	Lancer	FS-22N	22"	\$2,430
MSL30SC	Lancer	4500-30N	30"	\$2,655
MSL30SC	Lancer	FS-30N	30"	\$2,655

¹ All dispensers must be configured for nugget ice. See dispenser manufacturer for appropriate nugget ice kits, if required. Approved dispensers for top mount ice machine applications are listed above.

² Top kit MSF30SC required with Coca-Cola Freestyle 7000. Top adapter IC Code 46412 and ice kit IC Code 46430 must also be ordered from Coca-Cola.

³ Top kit MSF30SC required with Coca-Cola Freestyle 7100. Top adapter IC Code 46751 and ice kit IC Code 46430 must also be ordered from Coca-Cola.

⁴ Consult with Coca-Cola and Follett to qualify application prior to ordering.

⁵ RIDE application is approved only for Pepsi Spire 3.0, 5.0 and 4.1 designed for top mount ice machines and requires MSP24SC for 3.0 and MSP30SC for 5.0 and 4.1, ordered separately. For manual fill versions of Pepsi Spire 3.0, 5.0 and 4.1, contact factory.

⁶ Adapter must also be ordered from Coca-Cola. IC Code: 46010 (Silver), 46011 (Red) or 46012 (Black).

⁷ Top adapter IC Code 46412 and ice kit IC Code 46430 must also be ordered from Coca-Cola.

⁸ Top adapter IC Code 46753 and ice kit IC Code 46430 must also be ordered from Coca-Cola.

Top kits for Horizon Elite D710A and E710A ice machines for use with countertop ice and beverage dispensers

For additional Horizon Elite product information, request form# 1061.

Top kit accessory item number	Dispenser manufacturer	Dispenser model number	Dispenser series width	Installation orientation – Front or Back ¹	List price
Horizon top mount applications – 22 - 44 inch dispensers²					
H22F24-F ^{3,4}	Coca-Cola	Freestyle 9000	24"	F only	\$1,060
H22F26-F ³	Coca-Cola	Freestyle 9100	26"	F only	\$1,060
H22F30-F ^{3,5}	Coca-Cola	Freestyle 7000	30"	F only	\$1,280
H22F30-F ^{3,7}	Coca-Cola	Freestyle 7100	30"	F only	\$1,280
H22C22-F	Cornelius	DB/DF/ED150 series	22"	F only	\$1,045
H22C24-F	Cornelius	DB/DF/ED175 series	24.5"	F only	\$1,060
H22C30-F	Cornelius	DB/DF/ED200 series	30"	F only	\$1,280
H22C30-X ⁸	Cornelius	DB/DF/ED200 series	30"	F and B	\$1,185
H22C30-F	Cornelius	DB/DF/ED250 series	30"	F only	\$1,280
H22C30-X ⁸	Cornelius	DB/DF/ED250 series	30"	F and B	\$1,185
H22C30-F-FF	Cornelius	Flavor Fusion/Overload	30"	F only	\$1,700
H22C30-F-IDC	Cornelius	IDC 215/255 and Pro Fast Gate	30"	F only	\$1,700
H22C30-X-PRO	Cornelius	IDC Pro	30"	F and B	\$855
H22C44-__	Cornelius	DB/DF/ED300 series	44"	F or B	\$1,465
H22L22-F	Lancer	FS-22N/4500-22N	22"	F only	\$1,045
H22L30-F	Lancer	4500-30N	30"	F only	\$1,280
H22L30-F	Lancer	FS-30N	30"	F only	\$1,280
H22L30-F-STP	Lancer	Bevariety	30"	F only	\$1,280
H22L30-F-STP	Lancer	Sensation/Touchpoint	30"	F only	\$1,280
H22L30-F-STP	Lancer	Bold 30i	30"	F only	\$1,280
H22L44-F-STP	Lancer	44" Sensation/Twin Pour	44"	F only	\$1,280
H22P24-F ⁹	Pepsi	Spire 3.0	24"	F only	\$1,060
H22P30-F ⁹	Pepsi	Spire 5.0 / 4.1	30"	F only	\$1,280
H22S30-F	Servend	SV200	30"	F only	\$1,185
H22S44-__	Servend	MDH-302	44"	F or B	\$1,465
H22S60-__	Servend	MDH-402	60"	DF, DB	\$1,770
H22S60-__	Servend	MDH-402	60"	RF, LF, RB, LB	\$1,280

¹ Installation orientations available:

DF – 2 front facing Horizon Elite ice machines

LF – 1 Horizon Elite ice machine - left side - front facing

RB – 1 Horizon Elite ice machine - right side - back facing

RF – 1 Horizon Elite ice machine - right side - front facing

DB – 2 back facing Horizon Elite ice machines

LB – 1 Horizon Elite ice machine - left side - back facing

Note: For any other installation orientations, contact factory.

² All dispensers must be configured for nugget ice. See dispenser manufacturer for appropriate nugget ice kits, if required.

³ Consult with Coca-Cola and Follett to qualify application prior to ordering.

⁴ Adapter must also be ordered from Coca-Cola. IC Code: 46010 (Silver), 46011 (Red) or 46012 (Black).

⁵ Top adapter IC Code 46412 and ice kit IC Code 46430 must also be ordered from Coca-Cola.

⁶ Top adapter IC Code 46753 and ice kit IC Code 46430 must also be ordered from Coca-Cola.

⁷ Top adapter IC Code 46751 and ice kit IC Code 46430 must also be ordered from Coca-Cola.

⁸ Top designed with flexibility to accommodate front or back mounting.

⁹ RIDE application is approved only for Pepsi Spire 3.0, 5.0 and 4.1 designed for top mount ice machines and requires MSP24SC for 3.0 and MSP30SC for 5.0 and 4.1, ordered separately. For manual fill versions of Pepsi Spire 3.0, 5.0 and 4.1, contact factory.

Ice machine accessories

Water treatment accessories for ice machines

Item number	Description	List price
Follett bacterial-retentive filter system		
01233659	Bacterial-retentive filter system	\$1,180
01244615	Replacement filter kit for bacterial-retentive filter system	\$490
01233717	1 micron absolute rated pre-filter cartridge	\$115
01288034	Scale inhibitor pre-filter kit for bacterial-retentive filter system	\$410
01288042	Carbon with scale inhibitor pre-filter kit for bacterial-retentive filter system	\$410
01288067	Replacement filter for scale inhibitor pre-filter kit	\$165
01288059	Replacement filter for carbon and scale inhibitor pre-filter kit	\$165

Carbonless high capacity filter system

CARBONLESSHICAPSYS	Carbonless high capacity water filter system (one per ice machine), filtration capacity based on water conditions	\$1,190
CARBONLESSHICAPFILT	Carbonless high capacity water filter cartridge – primary, single	\$285
CARBONLESSHICAPFILT6	Carbonless high capacity water filter cartridge – primary, carton of 6	\$1,375
SEDIMENTPREFILTER	Water pre-filter cartridge – pre-filter, single	\$105
SEDIMENTPREFILTER12	Water pre-filter cartridge – pre-filter, carton of 12	\$400

Standard capacity carbon filter system

CARBONSTDCAPSYSTEM	Carbon standard capacity water filter system (one per ice machine), filtration capacity 5,000 gal (18,927 l)	\$1,115
CARBONSTDCAPFILTER	Water filter cartridge – primary, single	\$255
CARBONSTDCAPFILTER6	Water filter cartridge – primary, carton of 6	\$1,170
SEDIMENTPREFILTER	Water pre-filter cartridge – pre-filter, single	\$105
SEDIMENTPREFILTER12	Water pre-filter cartridge – pre-filter, carton of 12	\$400

High capacity carbon filter system

CARBONHICAPSYSTEM	Carbon high capacity water filter system (one per ice machine), filtration capacity 17,500 gal (66,245 l)	\$1,330
CARBONHICAPFILTER	High capacity water filter cartridge – primary, single	\$460
CARBONHICAPFILTER6	High capacity water filter cartridge – primary, carton of 6	\$2,255
SEDIMENTPREFILTER	Water pre-filter cartridge – pre-filter, single	\$105
SEDIMENTPREFILTER12	Water pre-filter cartridge – pre-filter, carton of 12	\$400

Cleaning and sanitizing accessories for ice machines

Item number	Description	List price
01147826	SafeCLEAN Plus, liquid – environmentally responsible ice machine cleaner (1 x 8 oz bottle)	\$75
01149954	SafeCLEAN Plus, liquid – environmentally responsible ice machine cleaner (6 x 8 oz bottles)	\$185
01149962	SafeCLEAN Plus, liquid – environmentally responsible ice machine cleaner (carton of 24 x 8 oz bottles)	\$550
01555077	SafeCLEAN Plus, liquid – environmentally responsible ice machine cleaner (carton of 4 x 1 gal bottles)	\$870
00979674	Nu-Calgon IMS-III sanitizer, single 16 oz bottle (US only)	\$75
01038652	Nu-Calgon IMS-III sanitizer, case of 12 x 16 oz bottles (US only)	\$410

Other accessories for ice machines

Item number	Description	List price
01068477	Slide-out ice machine accessory for air- and water-cooled ice machines (Harmony applications only) – allows air-cooled RMaestro Plus 414A RIDE ice machine to slide-out without disconnecting utilities	\$1,515
AFWALLMTBRKT	Wall mount bracket for Maestro Plus 414A RIDE model ice machines	\$540
00997098	Wall mount bracket for Horizon Elite 710A RIDE model ice machines	\$720
AFR400STND	Ice machine stand for Maestro 414A RIDE installations – height adjustable from 6.80" (17.27 cm) to 8.30" (21.08 cm)	\$1,120
00997080	Ice machine stand for Horizon Elite 710 series – height adjustable from 6.80" (17.27 cm) to 8.30" (21.08 cm)	\$1,130

Ice storage, ice transport and ice handling

Follett offers ice storage, dispensing and transport solutions in capacities and sizes to meet nearly every need. All with features that can make your ice management easier, safer, and more sanitary than you ever thought possible. Please visit www.follettice.com for more bin models than listed here.

Warranty

Slope front bins

Follett Products, LLC warrants to the original end user that the cabinet exterior, including the top and trim, and the interior liner will be free of corrosion for 3 years from the date of installation. Date of installation shall not exceed 90 days from date of shipment. Parts and labor for corrosion repair within this 3 year period are covered under this warranty.

All other integral components are covered against defects in material and workmanship under normal use and service for 2 years from the date of installation. Date of installation shall not exceed 90 days from date of shipment. Parts and labor for repair within this 2 year period are covered under this warranty. For products sold outside of the U.S. and Canada, the labor warranty will apply only to equipment sold and serviced through a Follett Authorized Distributor in its designated territory.

Removal of ice machine to service bin and any labor costs incurred are expressly excluded from this warranty.

WARRANTY CONDITIONS

- Warranty labor must be performed by the local Follett authorized service provider
- The equipment has been installed and operated in compliance with instructions provided by Follett. All 3rd party ice machines must be installed and operated in accordance with the manufacturer's instructions
- Malfunctions or damage due to alterations, improper operation, outdoor use, neglect, vandalism, fire, acts of God, or any situation beyond Follett's control are expressly excluded from this warranty
- Follett reserves the right to require that any parts covered under this warranty be returned to Follett prepaid and verified as defective upon examination
- Any damages resulting from shipment of the unit are expressly excluded. Follett advises customers to carefully examine all shipments prior to acceptance and note all potential damage concerns on the appropriate shipping papers.
- Excess labor charges resulting from security clearance procedures, safety training, travel time greater than one hour or 50 miles (80 km), premium time labor; after hours, weekends, holidays, etc., will not be covered by Follett Products, LLC and are the responsibility of the equipment owner


This warranty is expressly made in lieu of other warranties, expressed or implied, including any implied warranty of merchantability or fitness for a particular purpose except as provided in the warranty with respect to defects in material and workmanship.

Follett Products, LLC will not be liable for any consequential damages, expenses, connecting or disconnecting charges, or any losses or damages resulting from a defect of the machine. Questions concerning this warranty should be directed to Follett Products, LLC, technical service at +1 (877) 612-5086 or +1 (610) 252-7301.

Slope front bins

Small to medium capacity ice storage bins. Bin exterior for all models includes stainless steel front and sides. Bin interior includes polyethylene-lined walls and stainless steel bottom. All bins include stainless top, which is custom cut for ice machine(s) and 6.00" (15.24 cm) plastic adjustable legs.

For additional product information, request form# 9135.



Slope front bin

Item number †	Max. bin cap. lb (kg)	Width in (cm)	Depth in (cm)	Height w/ legs in (cm)	Req'd door access in (cm)	Approx. ship wt lb (kg)	List price
425-30	430 (195)	30.00 (76.2)	31.50 (80.0)	40.00 (101.6)	31.00 (78.7)	144 (65)	\$4,985
650-44	660 (299)	44.00 (111.8)	31.50 (80.0)	40.00 (101.6)	32.00 (81.2)	178 (81)	\$6,895
950-48	950 (431)	48.00 (121.9)	31.50 (80.0)	50.00 (127.0)	32.00 (81.2)	207 (94)	\$7,070
1025-52	1030 (467)	52.00 (132.1)	31.50 (80.0)	50.00 (127.0)	32.00 (81.2)	217 (98)	\$7,265

† Purchase orders must clearly indicate the make and model of the ice machine(s) being used with the bin to properly prepare the bin top. Lack of this information will result in a delay in order processing.

Additional bin types available. Contact factory.

Replacement stainless steel tops for slope front bins

Order must include complete model number of ice machine to be used in conjunction with bin.

Bin model	Width in (cm)	Depth (at top) in (cm)	Replacement top item number	Approx. ship wt lb (kg)	List price
425-30	30.00 (76.2)	27.50 (69.8)	AB425TOP00	36 (16)	\$1,250
650-44	44.00 (111.8)	27.50 (69.8)	AB650TOP00	45 (20)	\$1,690
950-48	48.00 (121.9)	27.50 (69.8)	AB725TOP00	70 (32)	\$1,850
1025-52	52.00 (132.1)	27.50 (69.8)	AB750TOP00	72 (33)	\$1,970

Incoterms is a trademark of the International Chamber of Commerce.

ENERGY STAR and the ENERGY STAR mark are registered trademarks owned by the U.S. Environmental Protection Agency.

Pyxis is a registered trademark of CareFusion in the United States and other countries.

Omnicell is a registered trademark of Omnicell, Inc. in the United States.

medDISPENSE is a registered trademark of InterMetro Industries Corp. in the United States and other countries.

EDGE SERIES, HORIZON ELITE, INFINITY SERIES, MAESTRO PLUS, SAFECLEAN PLUS, SANISPONGE, SENSNORSAFE, and SYMPHONY PLUS are trademarks of Follett Products, LLC.

CHEWBLET, FOLLETT, FOLLETT HEALTHCARE and RIDE are registered trademarks of Follett Products, LLC, registered in the US.



801 Church Lane | Easton, PA 18040, USA
+1 610.252.7301 | 800.523.9361 | folletthealthcare.com

2155-20251006 | © Follett Products, LLC