

Installation Instructions

Description

The DIP switches on the control board must be set to match your application. Please refer to the diagram below for the correct DIP switch settings.

If you experience any problems during the installation of this kit, please call Follett Technical Service toll-free at (877) 612-5086 for assistance.

OFF POSITION ON POSITION

**MC_425A/W_T, MC_425A/W_S, R425A/W,
Integrated Icemaker (all models)**

	OFF	ON	
[Sleep cycle disabled]	<input checked="" type="checkbox"/>	→	[Sleep cycle enabled]
Not used	<input type="checkbox"/>	↷	Not used
[Sleep cycle dispense duration]	<input checked="" type="checkbox"/>	↵	[Sleep cycle dispense duration]
20 min. time delay	<input checked="" type="checkbox"/>	∞	60 min. time delay
Flush disabled	<input type="checkbox"/>	↶	Flush enabled
Maint. timer ON	<input type="checkbox"/>	∞	Maint. timer OFF

**Symphony Plus 12/25/50/110 CI, CT, or FB;
E12CI; P425A/W or EP425A/W installed in
Symphony CT/FB**

	OFF	ON	
[Sleep cycle disabled]	<input type="checkbox"/>	→	[Sleep cycle enabled]
Not used	<input type="checkbox"/>	↷	Not used
[Sleep cycle dispense duration]	<input type="checkbox"/>	↵	[Sleep cycle dispense duration]
20 min. time delay	<input checked="" type="checkbox"/>	∞	60 min. time delay
Flush disabled	<input type="checkbox"/>	↶	Flush enabled
Maint. timer ON	<input type="checkbox"/>	∞	Maint. timer OFF

Replacement P425A/W installed in Symphony 25/50CI

	OFF	ON	
[Sleep cycle disabled]	<input checked="" type="checkbox"/>	→	[Sleep cycle enabled]
Not used	<input type="checkbox"/>	↷	Not used
[Sleep cycle dispense duration]	<input checked="" type="checkbox"/>	↵	[Sleep cycle dispense duration]
20 min. time delay	<input checked="" type="checkbox"/>	∞	60 min. time delay
Flush disabled	<input checked="" type="checkbox"/>	↶	Flush enabled*
Maint. timer ON	<input type="checkbox"/>	∞	Maint. timer OFF

Sleep cycle dispense duration

OFF	ON		
<input type="checkbox"/>	4	35 s	<input checked="" type="checkbox"/>
<input type="checkbox"/>	5		<input checked="" type="checkbox"/>
<input checked="" type="checkbox"/>	4	15 s	<input type="checkbox"/>
<input type="checkbox"/>	5		<input checked="" type="checkbox"/>
<input type="checkbox"/>	4	5 s	<input checked="" type="checkbox"/>
<input type="checkbox"/>	5		<input checked="" type="checkbox"/>
<input type="checkbox"/>	4	60 s	<input checked="" type="checkbox"/>
<input type="checkbox"/>	5		<input checked="" type="checkbox"/>

* Flush can be enabled on Symphony CT and FB models. Flush should be disabled on Symphony CI units due to risk of internal leak if drain line is blocked. All Symphony Plus models should be set to Flush enabled.