



REF5P Performance Plus

medical-grade undercounter refrigerator

Features

Superior temperature performance

- custom-designed microprocessor temperature controller
- air-cooled refrigeration system with heavy duty 1/5 horsepower compressor
- environmentally friendly, non-CFC R134a refrigerant
- programmed automatic defrost every 8 hours
- cabinet-wide temperature remains within ± 1 C (1.8 F), even with frequent door openings

Convenience and security

- fits below 36.00" (91.4 cm) standard countertops without casters
- refrigeration system settings accessed through door-mounted controls
- exterior LED digital temperature display available in user-programmable C or F with choice of product or air temperature
- user-programmable audible and visual high/low alarms
- mechanical lock – mounted on side of door
- lockable controller so set points cannot be inadvertently changed
- flexible internal storage configuration (drawers and shelves interchangeable)
- Agion® antimicrobial and UV product protection added to molded plastic façade¹

Durability and serviceability

- stainless steel construction on exterior and interior
- two epoxy-coated wire shelves standard
- back wall evaporator and front ventilation (no top, back or side clearance required)
- heavy-duty edge-mount self-closing hinges
- field-reversible door
- integral handle and magnetic gasket door closure

Warranty

- 2 year parts and labor on refrigeration system
- 5 year parts on compressor

¹ Disclaimer: Antimicrobial protection is limited to the plastic façade.

Undercounter refrigerators				
Controls	Keypad	Door configuration	V/Hz/Ph	Item number
LED	No	stainless	115/60/1	REF5P-00-00
		glass	115/60/1	REF5P-00-GD
	Yes	stainless	115/60/1	REF5P-KP-00
		glass	115/60/1	REF5P-KP-GD

Options and accessories

Glass door

Keypad and electronic lock with battery back-up

Extra shelf (item# 01059484)

One drawer kit (item# 01053644)

Two drawer kit (item# 01067750)

External digital data logger (item# 01057561)

Replacement probe for digital data logger (item# 01057595)

Temperature surveillance module (chart recorder) (item# 00168674)

Replacement charts for temperature surveillance module (item# 00162099)

Replacement pens for temperature surveillance module (item# 00162081)

Universal automated medication dispensing system bracket (item# 01059096)

Glycerine (16 oz) (item# 00959296)

Stacking kit – Performance Plus on Performance Plus (item# 01054006)

Stacking kit – REF/FZR Series (Legacy) on Performance Plus (item# 01067172)

Temperature alarm (item# 00112185)

17.00" (43.2 cm) pedestal kit (item# 01059120)

Extra key (item# 01059112)

Casters (set of 4) (item# 01053636)

Seismic bracket kit (item# 01059104)

NO/NC dry contacts for connection to remote alarm systems (item# 01092022)

Job

Item

801 Church Lane | Easton, PA 18040, USA
1.800.523.9361 | 1.610.252.7301 | folletthealthcare.com



10%
TOTAL RECOVERED FIBER
ALL POST-CONSUMER FIBER

Paper certified by:
The Forest Stewardship Council (FSC) and the Sustainable Forestry Initiative (SFI)

FOLLETT®

Specification

Nominal capacity	4.5 cu ft (127 L)
Ventilation clearance	0.0" for top, side and back clearance

Exterior

W1 Width	23.75" (60.3 cm)
D1 Depth cabinet	25.62" (65.1 cm)
Depth with façade	27.00" (68.6 cm)
H1 Height	34.00" (86.4 cm)
Height with casters	36.50" (92.7 cm)
Door swing	field-reversible

Interior

Width	19.75" (50.2 cm)
Depth	18.32" (46.5 cm)
Height	21.54" (54.7 cm)
Storage system	(2) 18.10" x 19.10" (46.0 cm x 48.5 cm) epoxy-coated steel shelves

Door configurations

Door	solid, foamed stainless 21.50" x 22.51" x 1.63" (54.6 cm x 57.2 cm x 4.0 cm)
Optional glass door	triple pane, low E glass window dimensions 16.30" x 10.90" (41.4 cm x 27.7 cm)
Door lock	cylinder lock
Door handle	molded into front façade
Door hinges	edge-mount, self-closing
Gasket	magnetic

Electrical

C1 115 V/60/1 electrical	4.1 run load amps, NEMA 5-15P 90° hospital-grade plug PVC, SJT, 16GA, 7' (2.1 m) cord
---------------------------------	--

Controls

Temperature display	standard 7 segment LED
Battery back-up on KP (keypad) models only	(8) AA batteries provide power to keypad, electronic lock and controls
C2 3rd party probe access	rear access port
Factory preset	4.4 C
Product simulation bottle	(1) 60 ml
Programmable operating range	2.2 to 10 C (36 to 50 F)

Alarming

High and low product temperature alarm	audible and visual; user programmable set points in C or F
Probe error alarm	audible and visual — product temperature probes, refrigeration and defrost
Alarm mute	user selectable
Alarm volume	0 -10 adjustable
Min/max temperature log	shows highest and lowest product temperature since last reset occurred

System performance

Refrigerant and charge	R134a refrigerant, 9 oz
Energy consumption	1.8 kWh/day
Max heat rejection	2185 BTU/hr


Shipping

Approximate net weight	170 lb (77 kg)
Approximate ship weight	205 lb (93 kg)

NOTE: For indoor use only

SHORT FORM SPECIFICATION: Performance Plus undercounter refrigerator with choice of solid stainless steel or glass door fits under 36.00" (91.4 cm) standard height counter height with 4.5 cubic feet (127 L) of nominal capacity. Includes (2) epoxy-coated wire shelves, adjustable in 1.5" (3.81 cm) increments. Environmentally responsible R134a forced-air cooled refrigeration system. Top-mounted controls display product or air temperature in user-selectable C or F. Integral high and low temperature alarming. Storage area insulated with CFC-free, high-density polyurethane foam. 7' (2.1 m) power cord with NEMA 5-15P 90° hospital-grade plug. NSF, UL and CUL listed.

Dimensional drawing



Agion is a registered trademark of Sciessent LLC.

Follett is a registered trademark of Follett LLC, registered in the US.

Follett reserves the right to change specifications at any time without obligation. Certifications may vary depending on country of origin.

REF5P undercounter refrigerator