

Chewblet<sup>®</sup> ice machine





NOTE: For use in applications with greater than 5 mg/l but less than 400 mg/l total dissolved solids in water and less than 200 mg/l hardness (either naturally occurring or treated with reverse osmosis or other TDS reducing technology).

Not recommended for use with softened water.



| Model configurations |   |                     |                      |  |
|----------------------|---|---------------------|----------------------|--|
| Ice storage capacity | Configuration/<br>Height                                      | Filter <sup>1</sup> | Item number          |  |
| 7 lb<br>(3.2 kg)     | Ice and water/<br>33.50" (85.1 cm)                            | no filter           | 7UC100A-IW-NF-ST-00  |  |
|                      |   | internal            | 7UC100A-IW-CF-ST-00  |  |
|                      | lce-only/<br>33.50" (85.1 cm)                                 | no filter           | 7UC100A-NW-NF-ST-00† |  |
|                      |   | internal            | 7UC100A-NW-CF-ST-00† |  |
|                      | Ice and water/<br>31.50" (80.0 cm)<br>for ADA<br>applications | no filter           | 7UD100A-IW-NF-ST-00  |  |
|                      |   | internal            | 7UD100A-IW-CF-ST-00  |  |
|                      | Ice-only/<br>31.50" (80.0 cm)<br>for ADA<br>applications      | no filter           | 7UD100A-NW-NF-ST-00† |  |
|                      |   | internal            | 7UD100A-NW-CF-ST-00† |  |

<sup>†</sup> ENERGY STAR certified

## **Features**

Compact size, only 14.62" (37.1 cm) wide and 22.12" (56.2 cm) depth to fit under standard counters

ADA model fits under 34.00" (86.4 cm) counters

7 lb (3.2 kg) ice storage capacity

Integral air-cooled ice machine with up to 125 lb (56.7 kg) daily production of popular Chewblet ice

- designed to serve up to 25 people (140 servings per 10 hr day<sup>1</sup>)
- soft, chewable, compressed nugget ice is preferred over cubes<sup>2</sup>
- environmentally responsible R134a refrigerant with zero ozone depletion potential
- energy saving sleep mode
- quiet production without noisy harvest cycles
- meets the Consortium for Energy Efficiency (CEE) Tier 2 specifications for highly efficient ice machines
- ice-only models ENERGY STAR® certified3

# Durable, attractive dispenser

- modern styling, stainless steel exterior with accent trim
- dispense-activated soft blue light illuminates point-of-use
- easy-to-clean, removable 20 oz (591 ml) drip tray

#### Designed with sanitation in mind

- Agion<sup>®</sup> silver-based antimicrobial product protection of key ice and water contact components<sup>4</sup>
- capacitive touch controls eliminate direct contact with ice

#### Installation

- comes fully assembled
- two easy connections electric and water
- drainless design allows dispenser to be placed anywhere a water line can be run and eliminates the cost of a drain installation

## Warranty

- 2 years parts and labor, 5 years compressor parts
- optional extended third year warranty (item# 00960732)

# Accessories

Drip tray drain kit (item# 00956375)

SafeCLEAN Plus™ ice machine cleaner

1 x 8 oz (237 ml) bottle (item# 01147826)

6 x 8 oz (237 ml) bottles (item# 01149954)

Carton of 24 x 8 oz (237 ml) bottles (item# 01149962)

Cartridge, replacement 5 micron particle/carbon (item# 00968107)

For additional water treatment and other accessories refer to form# 4025

Job Item

801 Church Lane | Easton, PA 18040, USA

1.800.523.9361 | 1.610.252.7301 | follettice.com




Internal filter is a 5 micron particle and carbon filter


| Specification  |   |  |
|--|---|--|
| Ice storage capacity   | 7 lb (3.2 kg)   |  |
| W1 Width   | 14.62" (37.1 cm)  |  |
| <b>D1</b> Depth  | 22.12" (56.2 cm)  |  |
| <b>D2</b> Kick recess depth                                    | 3.88" (9.86 cm)   |  |
| <b>H1</b> Height – 7UC100A                                     | 33.50" (85.1 cm)  |  |
| <b>H1</b> Height – 7UD100A                                     | 31.50" (80.0 cm)  |  |
| <b>H2</b> Kick recess height                                   | 4.00" (10.16 cm)  |  |
| <b>H3</b> Dispense height clearance                            | 8.50" (21.59 cm)  |  |
| Ventilation clearance  | 6.00" (15.24 cm) front of machine   |  |
| Service clearance  | 3.00" (7.62 cm) behind  |  |
| <b>C1</b> 115 V/60/1 electrical                                | 5 amps. Connect to dedicated 15 amp circuit fuse or breaker. 8' (2.4 m) cord w/ NEMA 5-15 90° plug. |  |
| C2 Water inlet   | 1/4" MPT  |  |
| Air temperature  | 50 -100 F (10 - 38 C)   |  |
| Water temperature  | 40 - 90 F (4 - 32 C)  |  |
| Water pressure   | 10 - 70 psi (69 - 482 kpa)  |  |
| Ice production at<br>70 F (21 C) air and<br>50 F (10 C) water  | 125 lb (56.7 kg)  |  |
| Ice production at<br>90 F (32 C) air and<br>70 F (21 C) water  | 100 lb (45.4 kg)  |  |
| Energy consumption<br>90 F (32 C) air and<br>70 F (21 C) water | 6.9 kWh per 100 lb (45.4 kg) ice  |  |
| Heat rejection   | 1700 BTU/hr   |  |
| Water consumption  | 12 gal (45.4 L) of potable water per<br>100 lb (45.4 kg) of ice                                     |  |
| Approximate net weight   | 94 lb (43 kg)   |  |
| Approximate shipping weight                                    | 117 lb (53 kg)  |  |

NOTE: For indoor use only. Designed for commercial use. Follett is not able to provide in-house services for residential installations.

SHORT FORM SPECIFICATION: (Choose one) Ice and water \_\_\_\_\_ or ice-only \_\_\_ dispenser to be Follett\* automatic load in (choose one) \_\_\_\_\_ 33.50" (85.1 cm) tall undercounter or \_\_\_\_\_ 31.50" (80.0 cm) tall ADA undercounter configuration, with 7 lb (3.2 kg) of storage. Environmentally responsible R134a ice machine to be air-cooled. Ice machine to produce approximately 125 lb (56.7 kg) of Chewblet compressed nugget ice at air temperature of 70 F (21 C) and water temperature of 50 F (10 C). Ice machine to be equipped with printed circuit board and diagnostics to allow simplified servicing and with capacitive touch user interface. Storage area to be insulated with non-CFC, high density foam-in-place polyurethane. 8' (2.4 m) cord and NEMA 5-15 right angle plug provided 115 V/60/1. Dispenser ETL and NSF listed. For use in applications with greater than 5 mg/l but less than 400 mg/l total dissolved solids in water and less than 200 mg/l hardness (either naturally occurring or treated with reverse osmosis or other TDS reducing technology).

# Dimensional drawing





- 1 16 oz (473 ml) cups, 2/3 full of ice.
- Independent third party studies. Contact Follett for details.
- <sup>3</sup> ENERGY STAR certification applies only to ice-only dispensers. While the 7 Series ice and water dispensers have the same efficient ice makers and refrigeration systems with the same ice machine electrical and water consumption as their complementary ice-only models, there is no ENERGY STAR category for ice and water dispensers at this time.
- 4 Disclaimer: Antimicrobial protection is limited to the treated components and does not treat water or ice.

Agion is a registered trademark of Sciessent LLC.

ENERGY STAR and the ENERGY STAR mark are registered trademarks owned by the U.S. Environmental Protection Agency.

SafeCLEAN Plus is a trademark of Follett LLC.

Chewblet and Follett are registered trademarks of Follett LLC, registered in the US. Follett reserves the right to change specifications at any time without obligation. Certifications may vary depending on country of origin.



