

7 Series and 15 Series Pre-installation Survey

Qualification / Site Validation

There are four important steps to qualify a site for the 7 Series or 15 Series

1. Dispenser is sized for the correct number of people
 - a. Refer to sizing chart and assess specific characteristics of the application
 - b. Remember, a 7 Series will deliver 140 servings (16 oz cups 2/3 full of ice) per work day (7 am to 5 pm) and the 15 Series will deliver 160 servings (16 oz cups 2/3 full of ice) per work day (7 am to 5 pm)
2. Water requirements
 - a. Water has less than 400 mg/L (ppm) total dissolved solids (TDS) and hardness level below 200 mg/L (ppm) – i.e. below 12 grains per gallon. Check by using TDS meter or by consulting with local water company
 - b. Treat with reverse osmosis or other TDS removal technology if water exceeds TDS or hardness limits
Note: Customer acknowledges that the product warranty will only apply if TDS and water hardness readings are below the specified levels
 - c. Inlet water temperature: 40 - 90 F (4 - 32 C)
3. Clearances meet Follett specifications
 - a. 3" clearance on the each side and back of the countertop and freestanding units
 - b. No blockage in front of 7 Series undercounters
4. Customer has been informed of the need for performing recommended maintenance, specifically cleaning at least twice a year

Specification and quotation

There are 3 important items to provide when specifying or requesting a quote for a 7 Series or 15 dispenser

1. Specific model (must choose one)

Configuration	7 Series	15 Series
Countertop	<input type="checkbox"/> 7CI100A	<input type="checkbox"/> 15CI100A
Freestanding	<input type="checkbox"/> 7FS100A	<input type="checkbox"/> 15FS100A
Undercounter	<input type="checkbox"/> 7UC100A	N/A
Undercounter for 34.00" ADA-compliant counters	<input type="checkbox"/> 7UD100A	N/A

2. Desired dispensing (must choose one)

- Ice-only
- Ice and water

3. Internal filtration (must choose one)

- No – for no filtration or when a Follett 0.5 micron externally-mounted system is used
- Yes – for internal 5 micron single cartridge filter

7 Series and 15 Series Pre-installation Survey

Customer/end user: _____

Address: _____ City, State Zip: _____



Phone: _____ Fax: _____ Email: _____

Instructions: Check the appropriate boxes and sign to acknowledge all points.

Site requirements

- Yes No Dispenser sized for the correct number of people (refer to sizing chart for sizing guidelines)
- Yes No Potable water source within 5 ft of unit and readily accessible
- Yes No Potable water connection point with shut off valve and ability to accommodate 1/4" O.D. plastic tubing
- Yes No Test and record the supply water TDS* level: _____ mg/L (ppm)
- Yes No Test and record the water hardness* level: _____ mg/L (ppm) _____ grains per gallon
- *TDS exceeding 400 ppm or hardness exceeding 200 ppm (12 grains per gallon) require reverse osmosis or other TDS removal technology
- Yes No Internal water filtration option
- Yes No External Follett water filtration option
- Yes No Dedicated 15 Amp, 115 VAC circuit within 5 ft and readily accessible
- Yes No Clearances meet Follett specifications
- Yes No Drip tray drain option
- Yes No Drain connection point within 5 ft (if drip tray drain is specified)
- Yes No Customer acknowledges the requirement to clean dispenser two times per year

Required clearances
for countertop and
freestanding models



Dealer/purchaser

Company _____ Contact _____

Address _____ City, State, Zip _____

Phone _____ Fax _____ Email _____

Name (print) _____

Signature _____ Date ____/____/____