

Chewblet® ice machine



Shown with optional base stand

NOTE: For use in applications with greater than 5 mg/l but less than 400 mg/l total dissolved solids in water and less than 200 mg/l hardness (either naturally occurring or treated with reverse osmosis or other TDS reducing technology).

Not recommended for use with softened water.



| Model configurations - 220 V 60 Hz | | | | |
|--|-----------------------------|---------------------|----------------------|--|
| Ice storage capacity | Configuration | Filter ¹ | Item number | |
| 3.2 kg (7 lb) | countertop ice and water | no filter | C7CI100A-IW-NF-ST-00 | |
| | | internal | C7CI100A-IW-CF-ST-00 | |
| | countertop ice-only | no filter | C7CI100A-NW-NF-ST-00 | |
| | | internal | C7CI100A-NW-CF-ST-00 | |
| For freestanding models | | | | |
| Optional base stand to convert countertop models to freestanding | | | 00956292 | |

¹ Internal filter is a 5 micron particle and carbon filter.

Features

Compact size, only 44.8 cm (17.62") tall to fit on counters under standard cabinets

3.2 kg (7 lb) ice storage capacity

Integral air-cooled ice machine with up to 56.7 kg (125 lb) daily production of popular Chewblet ice

- soft, chewable, compressed nugget ice is preferred over cubes¹
- environmentally responsible R134a refrigerant with zero ozone depletion potential
- energy saving sleep mode
- quiet production without noisy harvest cycles

Durable, attractive dispenser

- modern styling, stainless steel exterior with accent trim
- dispense-activated soft blue light illuminates point-of-use
- easy-to-clean, removable 590 ml (20 oz) drip tray

Designed with sanitation in mind

- Agion® silver-based antimicrobial product protection of key ice and water contact components²
- capacitive touch controls eliminate direct contact with ice

Installation

- two easy connections electric and water
- drainless design allows dispenser to be placed anywhere a water line can be run and eliminates the cost of a drain installation

Warrantv

- 2 years parts and labor, 5 years compressor parts

Accessories

10.16 cm (4.00") leg kit for CI - countertop models (item# 00956300)

15.24 cm (6.00") leg kit for base stand (item# 00956318)

Drip tray drain kit for countertop models (includes 10.16 cm (4.00") legs) (item# 00981977)

Drip tray drain kit without 10.16 cm (4.00") legs (item# 00956375)

Filter cartridge, replacement 5 micron particle/carbon (item# 00968107)

Claris® hardness removal filtration system (item# 00986059)


Follett Europe Polska Sp. z o.o. Mokry Dwór 26C 83-021 Wiślina, Poland Phone: +48 (58) 785-6140 | Fax: +48 (58) 785-6159 folletteurope.com


| Specification | |
|--|---|
| Ice storage capacity | 3.2 kg (7 lb) |
| W1 Width | 37.1 cm (14.62") |
| D1 Depth | 56.2 cm (22.12") |
| H1 Height, countertop models | 44.8 cm (17.62") |
| H2 Height, with optional base stand | 106.7 cm (42.00") |
| H3 Height, optional base stand | 62.0 cm (24.41") |
| H4 Dispense height clearance | 21.59 cm (8.50") |
| Ventilation clearance | 7.62 cm (3.00") on each side |
| Service clearance | 7.62 cm (3.00") behind and on each side of dispenser |
| C1 220 V/60/1 electrical | 5 amps. Connect to dedicated 10 amp circuit, fuse or breaker. Dispenser has IEC 60320-C13 connector in rear of dispenser for use with appropriate modular cord. |
| C2 Water inlet | 1/4" MPT |
| Air temperature | 10 - 38 C (50 -100 F) |
| Water temperature | 4 - 32 C (40 - 90 F) |
| Water pressure | 69 - 483 kpa (10 - 70 psi) |
| Ice production at 21 C (70 F) air and 10 C (50 F) water | 56.7 kg (125 lb) |
| Ice production at 32 C (90 F) air and 21 C (70 F) water | 45.4 kg (100 lb) |
| Energy consumption 32 C (90 F) air and 21 C (70 F) water | 6.9 kWh per 45.4 kg (100 lb) ice |
| Heat rejection | 498 W (1700 BTU/hr) |
| Water consumption | 45.4 L (12 gal) of potable water per 45.4 kg (100 lb) of ice |
| Approximate net weight – countertop models | 34 kg (74 lb) |
| Approximate shipping weight – countertop models | 41 kg (90 lb) |
| Approximate net weight – optional base stand | 11 kg (24 lb) |
| Approximate shipping weight – optional base stand | 14 kg (30 lb) |
| | |

NOTE: Intended for commercial use only. Follett can't guarantee freight carriers ability to deliver to residential locations. Follett service providers may not be bonded to perform on-site warranty repairs in certain areas.

SHORT FORM SPECIFICATION: (Choose one) ____ Ice and water or _ dispenser to be Follett automatic load in countertop configuration, with 3.2 kg (7 lb) of storage. Environmentally responsible R134a ice machine to be air-cooled. Ice machine to produce approximately 56.7 kg (125 lb) of Chewblet compressed nugget ice at air temperature of 21 C (70 F) and water temperature of 10 C (50 F). Ice machine to be equipped with printed circuit board and diagnostics to allow simplified servicing and with capacitive touch user interface. Storage area to be insulated with non-CFC, high density foam-in-place polyurethane. 220 V/60/1. Dispenser has IEC 60320-C13 connector in rear of dispenser for use with appropriate modular cord. NSF listed. Total dissolved solids in water not to exceed 400 mg/l (ppm) and hardness not to exceed 200 mg/l (ppm).

Dimensional drawing





- Independent third party studies. Contact Follett for details.
- Disclaimer: Antimicrobial protection is limited to the treated components and does not treat water or ice.

Claris is a registered trademark of the Aquis GmbH in Switzerland.

Agion is a registered trademark of Sciessent LLC.

Chewblet and Follett are registered trademarks of Follett LLC, registered in the US. Follett reserves the right to change specifications at any time without obligation. Certifications may vary depending on country of origin.

C7 Series ice and water dispenser

Follett Europe Polska Sp. z o.o. Mokry Dwór 26C 83-021 Wiślina, Poland Phone: +48 (58) 785-6140 | Fax: +48 (58) 785-6159 folletteurope.com

