



#### Removable ice machine for easy service



| Model configurations |            |                     |                          |  |
|----------------------|------------|---------------------|--------------------------|--|
| Ice storage capacity | Dispense   | Ice machine cooling | Item number              |  |
| 90 lb<br>(40.9 kg)   | Lever      | air                 | 110FB425A-L <sup>1</sup> |  |
|                      |            | water               | 110FB425W-L              |  |
|                      | SensorSAFE | air                 | 110FB425A-S <sup>1</sup> |  |
|                      |            | water               | 110FB425W-S              |  |

<sup>1</sup> Ice-only available, add -I Example: 110FB425A-LI

| Ice production                                       |   |  |
|--|---|--|
| Temperatures air/water                               | 70/50 F (21/10 C)   | 90/70 F (32/21 C)                          |
| Air-cooled   | 425 lb (193.0 kg)   | 325 lb (147.6 kg)                          |
| Water-cooled   | 486 lb (220.6 kg)   | 408 lb (185.2 kg)                          |
| Energy<br>consumption<br>per 100 lb<br>(45.4 kg) ice | N/A   | 6.0 kWh air-cooled<br>4.3 kWh water-cooled |
| Condenser<br>water<br>consumption                    | N/A   | 0.5 gpm (1.9 Lpm) at<br>70 F (21 C) water  |
| Water consumption                                    | 12.0 gal (45.4 L) of potable water per<br>100 lb (45.4 kg) of ice |  |

# $Symphony\ Plus^{^{\mathsf{TM}}} \ \mathsf{ice\ and\ water\ dispenser}$

110 FB series freestanding with Chewblet<sup>®</sup> ice machine

#### **Features**

90 lb (40.9 kg) ice storage capacity

Removable air- or water-cooled ice machine with up to 425 lb (193.0 kg) daily production of Chewblet ice

- soft, chewable, compressed nugget ice is preferred over cubes<sup>1</sup> and is ideal for patient care
- Quiet Night™ sleep mode turns off ice machine when idle

## Designed with sanitation in mind

- automatic self-flushing of ice machine removes impurities
- drain cup provides internal air gap for added protection of food zone components from drain line contaminants
- Agion<sup>®</sup> silver-based antimicrobial provides protection of key ice and water contact components<sup>2</sup>
- one-hand lever or SensorSAFE™ infrared ice dispense

#### Dependable design, easy to service and clean

- cleaning and sanitizing of entire machine takes only 1 hour
- LED control board provides at-a-glance machine status
- panels are easily removed for accessibility to all components
- ice machine parts are common across all Symphony Plus dispensers
- stainless steel evaporator and auger deliver long life

#### Environmentally responsible

- meets Consortium for Energy Efficiency Tier 2 specifications
- R404a refrigerant has zero ozone depletion potential
- continuous ice making process uses less electricity and water

#### Durable, attractive dispenser

- stainless steel cabinet with accent trim
- poly drain pan, grille and dispenser lid are corrosion-resistant
- secured top lid

#### Easy installation

- comes fully assembled and installs with three easy connections – electric, water and drain

#### Warranty

- 3 years parts and labor, 5 years compressor parts

### Certifications





#### Accessories

Pressurized water sanitizing kits (refer to form# 6830)

SafeCLEAN Plus™ ice machine cleaner

1 x 8 oz (237 ml) bottle (item# 01147826)

6 x 8 oz (237 ml) bottles (item# 01149954)

Carton of 24 x 8 oz (237 ml) bottles (item# 01149962)

Nu-Calgon\* IMS-III sanitizer, 16 oz (0.5 L) bottle (item# 00979674)

Additional filters (refer to form# 9905 and 8320)

Additional Symphony Plus accessories (refer to price list)





| Specification   |   |  |
|---|---|--|
| Ice storage capacity  | 90 lb (40.9 kg)   |  |
| <b>W1</b> Width, top  | 25.00" (63.5 cm)  |  |
| W2 Width, bottom  | 26.25" (66.7 cm)  |  |
| <b>D1</b> Depth, top  | 28.25" (71.8 cm)  |  |
| <b>D2</b> Depth, drain pan  | 7.00" (17.8 cm)   |  |
| D3 Depth, bottom  | 29.44" (74.8 cm)  |  |
| <b>H1</b> Height  | 68.12" (173.0 cm)   |  |
| <b>H2</b> Dispense height clearance   | 7.75" (19.68 cm)  |  |
| Ventilation clearance   | air-cooled models only –<br>4.00" (10.16 cm) rear   |  |
| Service clearance   | 12.00" (30.5 cm) top  |  |
| <b>C1</b> 115 V/60/1 electrical   | 11 amps, 0.8 kW<br>7' (2.1 m) cord, NEMA 5-15 90°<br>hospital-grade plug                                      |  |
| <b>C2</b> Potable water inlet, ice machine and dispenser  | 3/8" FPT  |  |
| C3 Drain, dispenser   | 3/4" MPT  |  |
| Water-cooled ice machine connections C4 condenser inlet C5 condenser drain C6 Ice machine drain | 3/8" FPT<br>3/8" FPT<br>3/4" MPT  |  |
|   | 50 -100 F (10 - 38 C)   |  |
| Air temperature   | ,   |  |
| Water temperature Potable water pressure  | 45 - 90 F (7 - 32 C)<br>10 - 70 psi (69 - 483 kpa)  |  |
| · ·   | 10 - 70 psi (69 - 463 kpa)<br>10 - 125 psi (69-861 kpa)   |  |
| Condenser water pressure  |   |  |
| Heat rejection  | air-cooled models – 5000 BTU/hr<br>water-cooled models – 1400 BTU/hr<br>to air, 3600 BTU/hr to water          |  |
| Water flow requirement for water-cooled models  | 0.25 gpm (0.95 lpm) at 50 F (10 C)<br>0.5 gpm (1.90 lpm) at 70 F (21 C)<br>1.25 gpm (4.73 lpm) at 90 F (32 C) |  |
| Approximate net weight  | 253 lb (115 kg)   |  |
| Approximate ship weight   | 285 lb (129 kg)   |  |

NOTE: For indoor use only

SHORT FORM SPECIFICATION: (Choose one) \_\_\_ Ice and water or \_\_\_ ice-only dispenser to be Follett® automatic load in freestanding configuration, with 90 lb (40.9 kg) of storage, water station and (choose one) \_\_\_ air- or \_\_\_ water-cooled ice machine in base. Environmentally responsible R404a ice machine mounted in base and to be removable as one unit for cleaning and maintenance. Ice machine to produce approximately 425 lb (193.0 kg) per day of Chewblet compressed nugget ice at air temp. of 70 F (21 C), water temp. of 50 F (10 C). Ice machine equipped with automatic self-flushing and Quiet Night sleep mode. Dispenser to have automatic bin level control to start and stop ice machine and separate circuitry to allow dispensing to continue with ice machine removed. Dispenser equipped with 6.00" (15.24 cm) adjustable legs, flanged feet and lightweight plastic top that allows full access to the ice storage area for manual loading of back-up ice. Storage area to be insulated with CARB compliant non-HFC foam. 7' (2.1 m) cord and NEMA 5-15 90° hospital-grade plug provided. NSF and ETL listed.

# Dimensional drawing





- Independent third party studies. Contact Follett for details.
- Disclaimer: Antimicrobial protection is limited to the treated components and does not treat water or ice. Agion is a registered trademark of Sciessent LLC.

Calgon is a licensed tradename distributed by Nu-Calgon, in the United States. SYMPHONY PLUS, SENSORSAFE, SAFECLEAN PLUS and QUIET NIGHT are trademarks of Follett Products, LLC. CHEWBLET and FOLLETT are registered trademarks of Follett Products, LLC, registered in the US. Follett reserves the right to change specifications at any time without obligation. Certifications may vary depending on country of origin.

110 FB series freestanding