



Horizon Elite™

self-contained E710A series Chewblet® ice machine

Features

High performance Horizon Elite ice machines

- automatically transport ice through a tube with RIDE® technology from up to 22.9 m (75') away
- consumer-preferred Chewblet ice is preferred 2:1 over cube ice
- ice dispenses reliably from ice and beverage dispensers
- quiet production without noisy harvest cycles

Revolutionary, scale inhibiting design

- produces ice that has 15% the TDS of the incoming water for optimum dispensing and long life in drinks
- quarantines and regularly expels scale producing dissolved solids to dramatically reduce scale buildup
- increases time between descaling and reduces or eliminates the need for expensive scale treatment
- uses 35% less water than comparable cubers

Durable, attractive ice machine

- regular bearing inspection or replacement is not required
- upgraded, easy-to-read LED operating status and diagnostic display

Designed with sanitation in mind

- Agion® silver-based antimicrobial product protection of key ice and water contact components¹
- floatless, sealed design inhibits formation of biofilms
- semi-automatic cleaning and sanitizing system

Remote monitoring with Open Kitchen™

- provided in partnership with Powerhouse Dynamics (separate subscription required)
- real-time alerts and notifications
- remote diagnostics to maximize equipment uptime
- connects with equipment across other Middleby brands

Warranty

- 3 years parts and labor, 5 years compressor parts²

Certifications (applied to all products unless otherwise noted)



Model configurations			
Production capacity	Condenser	V/Hz/Ph	Item number
up to 345 kg (759 lb)	air-cooled	230/50/1 ¹	E710A

¹ Model not for use in the United States.

Installation kits (required) ³		
Description	Ship wt kg (lb)	Item number
Installation kit for filling ice storage bins	5 (10)	01585371
Installation kit for filling countertop ice and beverage dispensers	5 (10)	01585363
Installation kit for filling drop-in dispensers	5 (10)	01585389
Ventilation kit required for ice machines installed under a counter (includes grilles and gasket)	5 (10)	01564624

Ice transport tube kits for RIDE installations (required), not needed for top mount applications ³		
Description	Ship wt kg (lb)	Item number
For bins, countertop ice and beverage dispensers and drop-in dispensers		
RIDE installations, 3 m (10')	5 (10)	01585397
RIDE installations, 10.7 m (35')	10 (22)	01585405
RIDE installations, 24.4 m (80')	27 (60)	01585413

Options and accessories⁴

- ☐ Top kit for ice and beverage dispensers (page 4)
- ☐ Wall mount bracket (item# 00997098)
- ☐ Ice machine stand, height-adjustable (item# 00997080)
- ☐ Timer to control one or two ice machines (item# 00967265)
- ☐ Sleep cycle kit for countertop dispenser applications for improved energy efficiency and component life (item# 01338276)
- ☐ One-year remote monitoring subscription and hardware for Open Kitchen (item# MDD-1003).
- ☐ Water filters (refer to form# 1058)
- ☐ SafeCLEAN Plus™ ice machine cleaner (refer to form# 8295)
- ☐ Additional accessories (refer to form# 4025 or 2435)


¹ Disclaimer: Antimicrobial protection is limited to the treated components and does not treat water or ice.

² Refer to form# 4025 or 2435 for additional warranty information.

³ Certifications do not apply to installation kits or ice transport tube kits.

⁴ Certifications do not apply to options and accessories.

Dimensional drawing






Specification



W1 Width	57.7 cm (22.70") Fits on 55.9 cm (22.00") wide dispensers
D1 Depth	62.2 cm (24.50")
H1 Height	54.0 cm (21.25")
Clearance	top, left and right – 2.54 cm (1.00")
C1 Electrical	6.0 amps, requires dedicated 15 amp circuit, 2 m (6.5') cord only
Operating power	0.7 kW
C2 Ice transport tube	see page 8 for details
C3 Water inlet	3/8" OD push-in water inlet
C4 Drain	3/4" MPT, 1" drain required. See page 7 for details.
C5 Auxiliary drain (required)	3/8" OD push-in
Air temperature	10 - 38 C (50 - 100 F)
Water temperature	7 - 32 C (45 - 90 F)
Potable water pressure	69 - 483 kPa (10 - 70 psi). NOTE: The potable water total dissolved solids (TDS) content must be greater than 10 ppm for the water control system to function properly.
Ice production	see ice production chart on page 8
Energy consumption	4.78 kWh per 45.4 kg (100 lb) ice
90 F (32 C) air, 70 F (21 C) water	
Heat rejection	2,143 Kcal/hr (8,500 BTU/hr)
Water consumption	45 L (12.0 gal) of potable water per 45.4 kg (100 lb) of ice (per AHRI test standards). 46.9 L (12.4 gal) at low TDS flush setting.
Refrigerant	R449A
Approximate ship weight	82 kg (180 lb)
Approximate net weight	96 kg (152 lb)
NOTE: For indoor use only	

SHORT FORM SPECIFICATION: Follett® Horizon Elite ice machine model E710A capable of producing compressed nugget ice using an efficient, sanitary horizontal evaporator/auger system and delivering ice by a flexible wire reinforced transport tube to ____ ice storage bin, ____ ice and water dispenser, ____ countertop ice and beverage dispenser, or ____ drop-in dispenser. Slide-out compressor/condenser/evaporator with utility docking station, front-mounted unit status display, evaporator water inlet at harvest end with automatic flush while producing ice, and semi-automatic cleaning and sanitizing system.

1 – Locating the ice machine

Horizon Elite self-contained Chewblet ice machines allow top-mounting or mounting in a base cabinet, on a wall or on a floor stand up to 22.9 m (75') from the dispenser or ice bin with RIDE technology. In-cabinet mounting (RIDE applications) require special attention to service access, unit ventilation and ice tube runs (see pages 4-8).

Top mounting – ice and beverage dispensers (by others)	RIDE model – ice and beverage dispensers (by others)	RIDE model – drop-in beverage dispensers (by others)
		
Important specifier notes 1. Dispenser must be compatible with nugget ice. See page 4 for compatible ice and beverage dispenser models and top kit numbers. 2. Verify ceiling or soffit height to ensure sufficient top clearance.	Important specifier notes 1. Dispenser must be compatible with nugget ice. Compatible dispensers include Servend MD150/175/200/250, SV175/200/250, MDH-402, and Follett Symphony Plus™ 110CM as well as the dispensers listed on page 4. 2. Coca-Cola Freestyle 7100 requires top adapter IC Code 46751 and ice kit IC Code 46430 and must be ordered from Coca-Cola. Coca-Cola Freestyle 9100 requires top kit HSF26SC. Consult with Coca-Cola and Follett to qualify application prior to ordering. 3. RIDE application is approved only for Pepsi Spire 3.0, 5.0 and 4.1 designed for top mount ice machines and requires MSP24SC for 3.0 and MSP30SC for 5.0 and 4.1, ordered separately. For manual fill versions of Pepsi Spire 3.0, 5.0 and 4.1, contact factory. 4. See pages 4-6 for critical clearance and venting requirements.	Important specifier notes 1. Compatible with the following dispensers: Cornelius 1522, 1722, 2323 and Lancer 2200, 2300, 23300. 2. Requires 30.5 cm (12.00") of access space for installation on transport tube side. 3. See page 5-6 for critical clearance requirements.

Top mount on Follett ice storage bins	RIDE model – Follett ice storage bins
	
Important specifier notes 1. See form# 8590 for bin sizing. Not for use with Ice•Device or Ice Pro™. 2. Verify ceiling or soffit height to ensure top clearance. 3. Locate floor sink or grate and drains in front of storage bin.	Important specifier notes 1. See form# 8590 for bin sizing. Not for use with Ice•Device or Ice Pro. 2. Locate floor sink or grate and drains in front of storage bin.

1 – Locating the ice machine (continued)

Top mounting – compatible ice and beverage dispensers ¹					
Manufacturer	Model number	Width cm (in)	Depth ² cm (in)	Height ³ cm (in)	Top kit
Coca-Cola dispensers	Freestyle 7000	76.5 (30.10)	79.0 (33.11)	119.4 (47.00)	H22F30-F ⁴
	Freestyle 7100	76.2 (30.00)	85.8 (33.80)	119.4 (47.00)	H22F30-F ^{4,5}
	Freestyle 9000	64.8 (25.50)	90.2 (35.50)	187.3 (73.75)	H22F24-F ^{4,6}
	Freestyle 9100	64.8 (25.50)	99.7 (39.25)	196.2 (77.25)	H22F26-F ⁴
Cornelius dispensers	DB/ED/DF 150 series	55.9 (22.00)	78.1 (30.75)	90.5 (35.63)	H22C22-F
	DB/ED/DF 175 series	62.2 (24.50)	76.2 (30.00)	90.5 (35.63)	H22C24-F
	DB/ED/DF 200 series	76.2 (30.00)	78.6 (30.95)	90.5 (35.63)	H22C30-F or H22C30-X ⁷
	DB/ED/DF 250 series	76.2 (30.00)	78.6 (30.95)	100.7 (39.63)	H22C30-F or H22C30-X ⁷
	DB/ED/DF 300 series	112.7 (44.38)	76.2 (30.00)	100.7 (39.63)	H22C44-F or B ⁸
	FlavorFusion / Overload	76.2 (30.00)	84.2 (33.13)	104.1 (41.00)	H22C30-F-FF
	IDC215	76.2 (30.00)	84.2 (33.13)	93.2 (36.69)	H22C30-F-IDC
	IDC255 and Pro Fast Gate	76.2 (30.00)	84.2 (33.13)	101.0 (39.75)	H22C30-F-IDC
	IDC Pro	76.2 (30.00)	84.2 (33.13)	102.2 (40.25)	H22C30-X-PRO ⁸
Lancer dispensers	4500-22N	55.9 (22.00)	77.5 (30.50)	93.1 (36.66)	H22L22-F
	4500-30N	76.2 (30.00)	77.5 (30.50)	93.1 (36.66)	H22L30-F
	FS-22N	55.9 (22.00)	77.5 (30.50)	104.8 (41.28)	H22L22-F
	FS-30N	76.2 (30.00)	77.5 (30.50)	104.8 (41.28)	H22L30-F
	Bevariety	76.2 (30.00)	78.7 (31.00)	95.9 (37.75)	H22L30-F-STP
	Bold 30i	76.2 (30.00)	87.0 (34.25)	111.12 (43.75)	H22L30-F-STP
	Sensation 30"	76.2 (30.00)	78.7 (31.00)	97.2 (38.25)	H22L30-F-STP
	Sensation 44" / Twin Pour	111.8 (44.00)	78.7 (31.00)	100.0 (39.38)	H22L44-F-STP
	Touchpoint	82.6 (32.50)	85.6 (33.70)	101.6 (40.00)	H22L30-F-STP
Pepsi dispensers	Spire 3.0	68.6 (27.00)	88.9 (35.00)	96.8 (38.12)	H22P24-F
	Spire 5.0 / 4.1	77.5 (30.50)	91.4 (36.00)	108.6 (42.75)	H22P30-F
Servend dispensers	SV200	76.2 (30.00)	84.2 (33.13)	95.6 (37.63)	H22S30-F
	MDH-302	108.6 (42.75)	77.5 (30.50)	89.3 (35.16)	H22S44-F or B ⁹

¹ All approved dispensers can be filled with a RIDE model Horizon Elite ice machine without a top kit except Pepsi Spire 3.0, 5.0 and 4.1, see page 3 for details.

² Requires minimum 2.54 cm (1.00") clearance between back of dispenser and wall.

³ Net height after installation of top kit (excluding height of ice machine).

⁴ Consult with Coca-Cola and Follett to qualify application prior to ordering.

⁵ Top adapter IC Code 46753 and ice kit IC Code 46430 must also be ordered from Coca-Cola.


⁶ Adapter must also be ordered from Coca-Cola. IC Code: 46010 (Silver), 46011 (Red) or 46012 (Black).

⁷ Top designed with flexibility to accommodate front or back mounting.

⁸ Top designed with flexibility to accommodate front or back mounting.

⁹ Specify "F" for front facing, or "B" for backward facing units.



2 – Undercounter/in-cabinet mounting

Cabinet details	
Important specifier notes	 Cabinet interior dimensions Requires 2.54 cm (1.00") top, left and right, 7.62 cm (3.00") minimum clearance at rear slides out Cabinet base must be flat and free of obstructions (no lip or utilities to block removal)

3 – Undercounter/in-cabinet mounting and ventilation

Using Follett ventilation kit, item# 01564624

Horizon Elite ice machines can be installed undercounter/in-cabinet to fill bins or dispensers using RIDE technology. Care must be taken to ensure proper cabinet venting to avoid recirculation of hot air. Improper venting can cause ice machine outages.





Important specifier notes for using Follett ventilation kit, item# 01564624

1. The exhaust grille must be located at least 45.7 cm (18.00") from the supplied air intake grille (exhaust air must not recirculate with intake air).
2. Cabinet interior must be open to allow for unrestricted exhaust air flow.
3. Ice transport tube needs minimum 2 cm per meter (1/4" per foot) pitch toward ice machine and should be secured to prevent dips and traps from forming.
4. Cabinet door must mate directly to air intake gasket.
5. Cabinet interior must provide a minimum clear space of 62.2 cm (24.50") deep by 56.5 cm (22.25") high.
6. Cutout for grilles must meet minimum size requirements shown above.
7. Utilities should be conveniently located as shown.


3 – Undercounter/in-cabinet mounting and ventilation (continued)

Using grilles by others/alternate cabinet ventilation

Cabinets with ventilation or louvers other than the Follett ventilation kit require special consideration to provide proper ventilation. Recirculation of hot air will reduce ice machine performance and can cause ice machine outages.





Minimum open air space





Important specifier notes for using grilles supplied by others/alternate cabinet ventilation

1. Exhaust must be at least 45.7 cm (18.00") from air intake (exhaust air must not recirculate with intake air).
2. Cabinet interior must be open to allow for unrestricted exhaust air flow.
3. Ice transport tube needs minimum 1/4" per foot (2 cm per meter) pitch toward ice machine and should be secured to prevent dips and traps from forming.
4. Ducting must be provided if cabinet door does not mate directly to air intake gasket.
5. Cabinet interior must provide a minimum clear space of 62.2 cm (24.50") deep by 56.5 cm (22.25") high.
6. Grilles by others must meet minimum requirements for open air space shown above.
7. Utilities should be conveniently located as shown.

4 – Horizon Elite ice machine mounting accessories

Optional wall mount bracket	Optional machine stand	Important specifier notes
		1. For secure wall mounting, specify optional wall mount bracket. 2. Wall and fasteners must support the weight of the ice machine, bracket, supply water and ice. Use of a backing board may be required with hollow wall construction. 3. Machine stand mounting adds 17.5 cm (6.88") to height of ice machine. 4. No dips in tube routing allowed. 5. Ice transport tube needs minimum 2 cm per meter (1/4" per foot) pitch toward ice machine and should be secured to prevent dips and traps from forming.

5 – Horizon Elite drains - specifier guidelines

Ice machine drain plumbing	Important specifier notes: Where code allows, follow recommendation below.
	1. Apply Teflon tape to 3/4" male outlet ice machine fitting. Thread on either the provided straight 3/4" barb adapter or a 90 degree adaptor. Connect the supplied 0.61 m (2') silicone hose to the 3/4" drain barb ①. 2. It is recommended that the silicone hose be routed down into a 1.5" or 2" standpipe/drain. The minimum drain size for the ice machine is 1". Note: 3/4" to 1" PVC adapter fittings are provided if a larger drain size is not possible ② ③. Note: Minimum 8" radius on silicone drain line. Drain line from the ice machine must have at least 2 cm per meter (1/4" per foot). Note: Standpipe/drain provided by others. All other components provided with ice machine.
Chassis drain plumbing – Required	Important specifier notes: Where code allows, follow recommendation below.
	1. Remove white 3/8" plug from rear push-in fitting ①. 2. Route 3/8" OD drain tubing (preferably copper) through rear of docking station and fully insert into chassis base push-in fitting. Route into drain standpipe. 3. Gravity drain. Ensure 3/8" OD tubing slopes down into drain standpipe without forming a trap.

6 – Horizon Elite ice tube runs - specifier guidelines

Long tube runs for RIDE remote ice delivery equipment

The diagram illustrates the installation of an ice transport tube in a kitchen setting. A beverage dispenser is connected to a wall-mounted ice machine via an ice transport tube. The tube is supported by straps and follows a path that includes a 90-degree turn. Key specifications and labels include: 'support straps', 'maximum 60.9 cm (2')' for the straight section, 'minimum of 15.24 cm (6.00") turn/corner radius' for the bend, 'ice transport tube – 1 3/16" OD, 2 1/8" OD with insulation', 'transport tube slope (toward ice machine) 1/4" 1' (2 cm per meter)', and 'wall-mounted ice machine'.

Important specifier notes

- 22.9 m (75') maximum ice transport tube run.
- Tubing routing bends must have a 15.24 cm (6.00") radius or larger.
- Dips and traps are not allowed. A 7.62 cm (3.00") or larger PVC pipe chase is suggested to support the tubing run. If not supported, secure insulated ice transport tube at least every 0.61 m (2') to prevent drips and traps.
- Relative humidity levels above 80% in areas where the ice machine or ice transport tube is located may produce excessive condensation that will cause water damage.
- Contact factory for recommendations on running tubing through a decorative soffit or chase.

Ice production – Horizon Elite E710A series

Inlet water temperature C (F)	Ambient air temperature C (F)					
	16 (60)	21 (70)	27 (80)	32 (90)	38 (100)	
10 (50)	301 (664)	280 (617)	261 (576)	244 (538)	227 (500)	kg (lb) production in 24 hr
16 (60)	293 (645)	272 (601)	254 (560)	236 (521)	218 (481)	
21 (70)	284 (626)	264 (582)	247 (544)	229 (506)	210 (464)	
27 (80)	267 (588)	247 (544)	232 (512)	218 (481)	176 (389)	
32 (90)	252 (557)	235 (519)	221 (487)	207 (455)	149 (328)	

Agion is a registered trademark of Sciessent LLC.
Open Kitchen is a trademark of Powerhouse Dynamics.
HORIZON ELITE, ICE•DEVICE, ICE PRO, SAFECLEAN PLUS, SANISPONGE and SYMPHONY PLUS are trademarks of Follett Products, LLC.
CHEWBLET, FOLLETT and RIDE are registered trademarks of Follett Products, LLC, registered in the US.
Follett reserves the right to change specifications at any time without obligation. Certifications may vary depending on country of origin.

Self-contained E710A series ice machine

